PRODUCT DATA SHEET NC-10HF Flux Coating for Solder Preforms

Introduction

Flux-coated solder preforms give you exact, repeatable amounts of solder for your manufacturing process without adding an extra step for applying flux. Both the solder preforms and flux are made to very tight tolerances, resulting in consistent solder joints. This improves efficiency and manufacturing yields.

The formulation and application of the flux coating for **NC-10HF** provide increased adherence of the flux to the preform. This formula minimizes clogging of pick and place equipment or bowl feeders, while putting the flux between the solder and the substrate where it is the most efficient.

NC-10HF is a halide-free, no-clean formulation that can be used on any substrate surface and coated onto any solder material.

Features

- Halide-free
- No-clean
- Usable on all substrate surfaces
- Usable with all alloys
- Compatible with pick and place or bowl feeding equipment
- Available in colors to distinguish similar parts (color has no impact on soldering ability)

Flux Percentage

The recommended amount of flux coating is generally $1\% \pm 0.5\%$ by weight. This precise amount of flux eliminates operator variations when applying flux as a separate step. It also reduces the post reflow flux residue. Coatings up to 3% are possible, although not generally required.

Cleaning

NC-10HF is designed for no-clean applications. If desired, the flux residue can be removed by a commercially available flux cleaner.



IPC Classification	Substrate Finishes	Reliability J-STD-004
ROLO	Au, Ag, Pd, Pt, Cu, HASL, ENIG, Sn, Ni	Pass

Technical Support

Indium Corporation's internationally experienced engineers provide in-depth technical assistance to our customers. Thoroughly knowledgeable in all facets of Material Science as it applies to the electronics and semiconductor sectors, Technical Support Engineers provide expert advice in solder properties, alloy compatibility and selection of solder preforms, wire, ribbon, and paste. Indium Corporation's Technical Support engineers provide rapid response to all technical inquiries.

Safety Data Sheets

The SDS for this product can be found online at http://www.indium.com/sds

This product data sheet is provided for general information only. It is not intended, and shall not be construed, to warrant or guarantee the performance of the products described which are sold subject exclusively to written warranties and limitations thereon included in product packaging and invoices. All Indium Corporation's products and solutions are designed to be commercially available unless specifically stated otherwise.

From One Engineer To Another

Contact our engineers today: askus@indium.com Learn more: www.indium.com



Form No. 98602 R0

ASIA +65 6268 8678 • CHINA +86 (0) 512 628 34900 • EUROPE +44 (0) 1908 580400 • USA +1 315 853 4900

©2018 Indium Corporation