

PRODUCT DATA SHEET

NC-10HF

Flux Coating for Solder Preforms

Features

- Halide-free
- No-clean
- Usable on all substrate surfaces
- Usable with all alloys
- Compatible with pick & place or bowl feeding equipment
- Available in colors to distinguish similar parts (color has no impact on soldering ability)

IPC Classification	Substrate Finishes	Reliability J-STD-004
ROLO	Au, Ag, Pd, Pt, Cu, HASL, ENIG, Sn, Ni	Pass

Introduction

Flux-coated solder preforms give you exact, repeatable amounts of solder for your manufacturing process without adding an extra step for applying flux. Both the solder preforms and flux are made to very tight tolerances, resulting in consistent solder joints. This improves efficiency and manufacturing yields.

The formulation and application of the flux coating for **NC-10HF** provide increased adherence of the flux to the preform. This formula minimizes clogging of pick & place equipment or bowl feeders, while putting the flux between the solder and the substrate where it is the most efficient.

NC-10HF is a halide-free, no-clean formulation that can be used on any substrate surface and coated onto any solder material.

Technical Support

Indium Corporation's internationally experienced engineers provide in-depth technical assistance to our customers. Thoroughly knowledgeable in all facets of Material Science as it applies to the electronics and semiconductor sectors, Technical Support Engineers provide expert advice in solder properties, alloy compatibility, and selection of solder preforms, wire, ribbon, and paste. Indium Corporation's Technical Support engineers provide rapid response to all technical inquiries.

Safety Data Sheets

The SDS for this product can be found online at <http://www.indium.com/sds>

Flux Percentage

The recommended amount of flux coating is generally 1% +/- 0.5% by weight. This precise amount of flux eliminates operator variations when applying flux as a separate step. It also reduces the post reflow flux residue. Coatings up to 3% are possible, although not generally required.

Cleaning

NC-10HF is designed for no-clean applications. If desired, the flux residue can be removed by a commercially available flux cleaner.

This product data sheet is provided for general information only. It is not intended, and shall not be construed, to warrant or guarantee the performance of the products described which are sold subject exclusively to written warranties and limitations thereon included in product packaging and invoices. All Indium Corporation's products and solutions are designed to be commercially available unless specifically stated otherwise.

Form No. 98602 R0

www.indium.com

askus@indium.com

ASIA: Singapore, Cheongju, Malaysia: +65 6268 8678
 CHINA: Suzhou, Shenzhen: +86 (0)512 628 34900
 EUROPE: Milton Keynes, Torino: +44 (0) 1908 580400
 USA: Utica, Clinton, Chicago, Rome: +1 315 853 4900

