SDS – 4809 NC585 FLUX



INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: NC 585 FLUX

SDS Number: SDS-4809 Revised Date: 17 JUNE 2016

Product Use: Industrial Use – ball attach flux

MANUFACTURER:

In America:

The Indium Corporation of America 1676 Lincoln Ave., Utica NY 13502 Information: (315) 853-4900 nswarts@indium.com

In Europe: Indium Corporation of Europe

7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore 29 Kian Teck Avenue

Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou) Co., Ltd.

No.428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Information: (86) 512-6283-4900

SDS – 4809 NC585 FLUX

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Carcinogen listed in

⊗Eye ⊗Inhalation ⊗Skin ⊗Ingestion NTP IARC OSHA ⊗Not Listed

GHS:





Hazard statements(s)

H317 May cause an allergic skin reaction H319 Causes serious eye irritation

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

EUH208 Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 + P364 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 + P352 IF ON SKIN: Wash with plenty of soap and water

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + P351 IF IN EYES: Rinse continuously with water for several minutes (15 MINS)

P337 + P313 If eye irritation persists: Get medical advice/attention

Classification:

Eye irritation - Category 2A

POTENTIAL HEALTH EFFECTS:

Eye Contact: Irritating to the eyes and if not removed promptly, may result in serious eye

irritation. Do not allow material to come in contact with the eyes.

Ingestion: May cause irritation.

Inhalation: Heated vapor concentrations may be harmful if inhaled. Irritating to respiratory tract. Rosin may

cause occupational asthma.

Skin Contact: May cause skin irritation or dermatitis. Rosin may cause skin sensitization.

Chronic: Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its

products for human consumption.

SDS - 4809 NC585 FLUX

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
ROSIN	40-50	65997-05-9	N.E.	N.E.	N.E.
		(EU)	0.05		0.15
PROPRIETARY ACTIVATORS	5-14	-	N.E.	N.E.	N.E <u>.</u>
POLYGLYCOL ETHER	36-55	9038-95-3	N.E.	N.E.	N.E.

N.E. = Not established

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: >100C Method: Not available

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions. Foam, dry

chemical, water spray.

Special Fire Fighting Firefighters must wear NIOSH approved self-contained breathing apparatus and full

Procedures: protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Wearing a respirator may be necessary and appropriate personal protection (See

Exposure Controls/Personal Protective Section). Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Dispose of following all

Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills. Avoid breathing

SDS – 4809 NC585 FLUX

Precautions: vapors from heated material. Avoid contact with eyes, skin and clothing. Use with adequate

ventilation.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Keep away from heat

and flame. Store away from incompatible materials. Empty containers may be hazardous as

they contain product residue.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Exhaust ventilation is necessary to control airborne levels and to keep exposures

as low as possible, especially during heating.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An approved or compliant marked air-purifying respirator with a fume/acid/organic

chemical cartridge is recommended under certain circumstances where airborne concentrations are

expected to be elevated.

Skin: Compatible chemical resistant gloves such as nitrile should be worn. Protective outer garment,

apron and sleeves as appropriate.

Other: Eyewash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately.

Practices: Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water

immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Flux - yellow Boiling Point: Not established

Odor: Mild characteristic odor. Melting Point: Not applicable

Specific Gravity: 1 g/cc pH: 4 - 8

Vapor Pressure: Not applicable.

Vapor Density: (air=1) Not applicable.

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: High temperatures, open flame.

Incompatible Materials: Not established Hazardous Decomposition / Not established

Combustion:

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

OSHA: No IARC: No

LD50: Not established. **LC50:** Not established.

SDS - 4809 NC585 FLUX

.Product not tested. Product does not contain any carcinogens.

12. ECOLOGICAL INFORMATION

Product not tested.

An environmental hazard cannot be ruled out when mishandling and improperly disposing.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local environmental regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated.

Non - hazardous under all shipping modes.

UN - NONE

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

SARA 313 Listing - 40 CFR 372.65 - 15% polyglycol ether

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS:

D2B Materials Causing Other Toxic Effects -irritant

This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

This product has been classified under the Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products

SDS - 4809 NC585 FLUX

GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 1

Fire: 0 Physical Hazard: 0

Revised Date: 17 JUNE 2016

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.