



A table is provided that lists all metal groupings with this flux. To better serve all of our customers Indium Corporation has generated one SDS, for this product, to be used within the United States as well as internationally. Some of the regulatory information contained within may not be applicable to the customer's individual state or country. Unless otherwise stated the health and safety information provided within is applicable to all products.

## SAFETY DATA SHEET

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** INDALLOY WITH FLUXCAKE 501 (CW-501)

**SDS Number:** SDS-4316

**Revised Date:** 3 DECEMBER 2018

**Product Use:** Industrial Use - solder flux cored wire (flux 1 – 4%). Review alloy table for list of metal mixtures. See alloy table for metal mixtures under Indalloy numbers.

#### MANUFACTURER:

##### In America:

The Indium Corporation of America®.  
34 Robinson Rd., Clinton, New York 13323  
Information: (315) 853-4900  
[nswarts@indium.com](mailto:nswarts@indium.com)

#### EMERGENCY PHONE:

**CHEMTREC 24 hrs.**  
**USA: 1 (800) 424-9300**  
**Outside USA: +1 (703) 527-3887**

Indium Corporation of America  
Chicago Materials Division  
80 Scott Street  
Elk Grove Village, Illinois 60007  
Information: (847) 439-9135

##### In Europe:

The Indium Corporation of America® (European Operations)  
7 Newmarket Ct.  
Kingston, Milton Keynes, UK, MK 10 OAG  
Information: +44 [0] 1908 580400

##### In China:

Indium Corporation (Suzhou) Co., Ltd.  
No. 428 Xinglong Street  
Suzhou Industrial Park  
Suchun Industrial Square  
Unit No. 14-C  
Jiangsu Province, China 215126  
Information: (86) 512-6283-4900

##### In Asia:

The Indium Corporation of America  
Asia-Pacific Operations-Singapore  
29 Kian Teck Avenue  
Singapore 628908  
Information: +65 6268-8678

**2. HAZARDS IDENTIFICATION**

**PRIMARY ROUTES OF ENTRY:**

⊕Eye    ⊕Inhalation    ⊕Skin    ⊕Ingestion    NTP    IARC    OSHA    ⊕Not Listed

**Carcinogen listed in**

**GHS:**

Lead-free products:



Signal Word: Warning

Hazard statement(s)

H319                      Causes serious eye irritation

Precautionary statement(s)

- P233                      Keep container tightly closed
- P261                      Avoid breathing dust/fume/gas/mist/vapors/spray
- P270                      Do not eat, drink or smoke when using this product
- P273                      Avoid release to the environment
- P280                      Wear protective gloves/protective clothing/eye protection/face protection
- P362 +P364              Take off contaminated clothing and wash before reuse
- P301 + P314              IF SWALLOWED: Get Medical advice/attention if you feel unwell
- P302 +P352              IF ON SKIN: Wash with plenty of soap and water
- P304 + 341              IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305 + 351              IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Lead containing products:



Signal Word: Warning

Hazard statement(s)

- H303                      May be harmful if swallowed
- H319                      Causes serious eye irritation
- H332                      Harmful if inhaled (lead)
- H351                      Suspected of causing cancer (lead)
- H361                      Suspected of damaging fertility or the unborn child ( lead)
- H373                      May cause damage to organs through prolonged or repeated exposure (lead)
- H410                      Very toxic to aquatic life with long lasting effects (lead)
- EUH201A                Warning! Contains lead.

Precautionary statement(s)

- P233                      Keep container tightly closed
- P261                      Avoid breathing dust/fume/gas/mist/vapors/spray
- P270                      Do not eat, drink or smoke when using this product
- P273                      Avoid release to the environment
- P280                      Wear protective gloves/protective clothing/eye protection/face protection
- P362 + P364              Take off contaminated clothing and wash before reuse
- P301 + P314              IF SWALLOWED: Get Medical advice/attention if you feel unwell
- P302 +P352              IF ON SKIN: Wash with plenty of soap and water
- P304 + 341              IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing

P305 + 351

IF IN EYES: Rinse continuously with water for several minutes (15 mins)

**Classification:**

Carcinogenicity (Category 2) (lead)

Reproductive toxicity (Category 2 ) (lead)

Skin sensitizer-Category 1B

Respiratory sensitizer-Category 1B

Eye irritation-Category 2A

Acute aquatic toxicity – Category 1 for lead containing products (H400)

Chronic aquatic toxicity – Category 1 for lead containing products (H410)

**POTENTIAL HEALTH EFFECTS:**

**Eye Contact:** Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause eye irritation. Molten metal may cause burns to the eyes. Flux causes serious irritation.

**Ingestion:** This product contains metal alloys and organic chemicals. May be harmful if swallowed.

**Inhalation:** Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to the respiratory system. May be harmful if inhaled.

**Skin Contact:** If molten may cause skin irritation. Antimony may cause irritation.

**Chronic:** SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Has been shown to increase incidence of sarcoma in animal tests.

COPPER: Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.



**WARNING:** This product can expose you to chemicals such as [lead] which is known to the State of California to cause cancer, and can cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**NOTE:** The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

**WARNING:** This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making joints or fittings in any private or public water supply system. Keep out of the reach of children.

Solid metal wire as is does not pose any danger.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Components	% wt	CAS Registry #/ EINECS#	PEL mg/m <sup>3</sup>	TLV-TWA mg/m <sup>3</sup>	TLV-STEL mg/m <sup>3</sup>
<b>TIN</b>	*	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
		(Singapore)	2	-	-
<b>SILVER</b>	*	7440-22-4/231-131-3			
		(US)	0.01	0.1	-
		(EU)	-	0.1	-
		(Canada)	-	0.1	0.3
		(Mexico)	-	0.1	-
(Singapore)	0.1	-	-		
<b>COPPER</b>	*	7440-50-8/231-159-6			
		(US)	0.1 (fume)	0.2 (fume)	-
		(EU)	-	0.2 (fume)	-
		(Canada)	-	0.2 (fume)	0.6 (fume)
		(Mexico)	-	0.2(fume)	2
		(Singapore)	0.2	-	-
		(China)	-	1(dust)	2.5
			0.2(fume)	0.6	
<b>LEAD</b>	*	7439-92-1/231-100-4			
		(US)	0.05	0.05	-
		(EU)	-	0.15	-
		(Singapore)	0.15	-	-
		(Mexico)	-	0.15	-
		(China)	-	0.05(dust) 0.03(fume)	-
(Canada)	0.05	0.05	-		
<b>ANTIMONY</b>	*	7440-36-0/231-146-5			
		(US)	0.5	0.5	-
		(EU)	0.5	-	-
(Canada)	-	0.5	1.5		

		(Mexico)	N.E.	0.5	-
		(Singapore)	0.5	-	-
		(China)	-	0.5	-
<b>BISMUTH</b>	*	7440-69-9	N.E.	N.E.	N.E.
<b>PROPRIETARY FLUX</b>	1-4.0	-	N.E.	N.E.	N.E.

Product complies with \*RoHS Restriction of Hazardous Substances (review directive for applicable exemptions)  
 \* See Alloy Table

**4. FIRST AID MEASURES**

**Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.

**Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.

**Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

**5. FIRE FIGHTING MEASURES**

**Flash Point:** Not established. **Method:** Not established.

**Auto-ignition Temperature:** Not established.

**Flammable Limits:** Limits not established.

**Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions.

**Special Fire Fighting Procedures:** Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

**Spill or Leak Procedures:** Solid material may be picked up and recycled. Molten metal should not be allowed to flow to any drain. Contain and allow to solidify, pick up and recycle material. Wear protective clothing when handling molten materials. Follow all Federal, State and Local regulations regarding disposal of or recycling of product.

**7. HANDLING AND STORAGE**

**Handling** Keep containers tightly closed when not in use. Use care to avoid spills. Use only with

**Precautions:** production equipment specifically designed for use with solder. Wear appropriate personal protective equipment when working or handling solder. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.

**Storage Precautions:** Store product in tightly sealed original containers in a cool, dry area. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Use only with production equipment, adequate ventilation and other safety features specifically designed for use with solder activities. Control concentration of all components so that any permissible exposure limits are not exceeded. Ventilate areas where molten metal is used, by using exhaust ventilation. Keep exposures as low as possible. Avoid inhalation of fumes. Product fumes may contain lead or small amounts (<0.2%) of a flux ingredient listed that may cause cancer.

### Personal protection:

**Eyes:** Chemical safety glasses/goggles and face shield for molten metal.

**Respirator:** An authority approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated or exceed exposure limits.

**Skin:** Compatible chemical resistant gloves. Use hot gloves for handling molten metal.

**Other:** Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses.

**Work/Hygienic** Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Solid wire	<b>Boiling Point:</b>	Not applicable.
<b>Odor:</b>	No apparent odor	<b>Melting Point:</b>	Not applicable
<b>Specific Gravity:</b>	Not applicable.	<b>pH:</b>	Not applicable
<b>Vapor Pressure:</b>	Not applicable.	<b>Solubility in Water:</b>	Insoluble
<b>Vapor Density:</b>	(air=1) Not applicable.		

## 10. STABILITY AND REACTIVITY

**General:** Stable.

**Conditions to Avoid:** Not established.

**Incompatible Materials:** Avoid contact with acids, bases or oxidizing agents.

**Hazardous Decomposition / Combustion:** Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.

**Hazardous Polymerization:** Will not occur.

**11. TOXICOLOGICAL INFORMATION**

**Carcinogenicity:**            **NTP:** No  
    **OSHA:** No                    29CFR1910.1025  
    **IARC:** Yes – Lead (International Agency on Research for Cancer) Lead and lead compounds are listed as possible carcinogens.

(Product contains <0.2% of a proprietary flux ingredient listed as a potential carcinogen)

**LD50:**                            Not established.                            **LC50:**                            Not established.

**12. ECOLOGICAL INFORMATION**

Product not tested. No information available.

**13. DISPOSAL CONSIDERATION**

**Waste Disposal Method:**    Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations.

**14. TRANSPORT INFORMATION**

Transport in accordance with applicable international regulations and requirements. Not regulated under US DOT (United States Department of Transportation).

Non hazardous material under all shipping requirements and modes (GROUND/IATA/OCEAN).

UN - none

**15. REGULATORY INFORMATION**

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).



**WARNING:** This product can expose you to chemicals such as [lead] which is known to the State of California to cause cancer, and can cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Some ingredients are contained on the New Jersey State Right To Know List

SARA 313 Listing - 40 CFR 372.65

Silver CAS# 7440-22-4

Copper CAS# 7440-50-8

Lead CAS# 7439-92-1

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS: D2B materials Causing Other Toxic Effects – irritant (resin)

D2B Materials Causing Other Toxic Effects – Very Toxic Material (chronic) (lead)

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with the Mexican guidelines, NOM-018-STPS-2015 and NOM-010-STPS-2014.

Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS). (GHS)

In China:

Decree No. 591: Regulations on the Control over Safety of Hazardous Chemicals

GB 30000.2-29-2013, Rules for classification and labeling of chemicals. (GHS)

GB/T 16483-2008, GB/T 17517-2013

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007.

Japan:

Poisonous and Deleterious Substance Control Law (PDSCL): No ingredients are listed.

Fire Service Law (FSL): Not regulated/not dangerous.

Industrial Safety and Health Law (ISHL): ingredients are listed

Waste Disposal and Public Cleaning Law: Specific Harmful Industrial Wastes: Some contents of the family grouping may contain lead within the solder paste. Review alloy table and product label/ purchased and used.

Class II Designated Chemical Substances: No ingredients are listed.

CSSL: Monitoring Chemical Substances: No ingredients contained on this list

Ingredients are listed on the Japanese Inventory Chemical Substance List/Industrial Safety and Health Law Substance List

## 16. OTHER INFORMATION

<b>HMIS Hazard Rating:</b>	<b>Health:</b>	2
	<b>Fire:</b>	1
	<b>Reactivity:</b>	0

<b>Revised Date:</b>	3 DECEMBER 2018
<b>Prepared by:</b>	Nancy Swarts, Indium Corporation of America
<b>Approved by:</b>	Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and



recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

**ALLOY TABLE**

**%Metal mix with 1-4% flux**

INDALLOY (METAL MIX)	%COPPER Cu	%TIN Sn	%SILVER Ag	%BISMUTH Bi	%LEAD Pb	%ANTIMONY Sb	RoHS 2/3 Compliance
<b>106</b> (Sn63/Pb37)	-	60.5 - 62.4	-	-	35.5 - 36.6	-	NO
<b>133</b> (95Sn/5Sb)	-	91 - 94	-	-	-	4.8 - 4.96	YES
<b>241</b> (SAC 387) (95.5Sn/3.8Ag/ 0.7Cu)	0.67 - 0.69	91.7 - 94.5	3.6 - 3.76	-	-	-	YES
<b>256</b> (SAC 305) (96.5Sn/3Ag/0. 5Cu)	0.48 - 0.495	92.6 - 95.5	2.88 - 2.97	-	-	-	YES
<b>97</b> (43Sn/43Pb/14 Bi)	-	41.3 - 42.6	-	13.4 - 13.9	41.3 - 42.6	-	NO
Non-standard (96Sn/4Ag)	-	92-95	3.84-3.96	-	-	-	YES

RoHS 2 = Restriction of Hazardous Substances EU Directive 2011/65/EU

RoHS 3 = products do not contain any listed phthalates

Product does not contain any flame-retardants.

Refer to <http://www.indium.com>