



SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH FLUXCAKE-802 (CW-802)

SDS Number: SDS-CW 4833

Revised Date: 11 JUNE 2018

Product Use: Industrial Use - Flux cored wire for soldering applications. (See alloy table for metal alloy mixtures)

MANUFACTURER:

In America:

The Indium Corporation of America®.
34 Robinson Road, Clinton NY 13323
Information: (315) 853-4900
nswarts@indium.com

EMERGENCY PHONE:

CHEMTREC 24 hrs.
USA: 1 (800) 424-9300
Outside USA: +1 (703) 527-3887

In Europe:

The Indium Corporation of America® (European Operations)
7 Newmarket Ct.
Kingston, Milton Keynes, UK, MK 10 OAG
Information: +44 [0] 1908 580400

In China:

Indium Corporation (Suzhou), Co., Ltd.
No. 428 Xinglong Street
Suzhou Industrial Park
Suchun Industrial Square
Unit No. 14-C
Jiangsu Province, China 215126
Information: (86) 512-6283-4900

In Asia:

The Indium Corporation of America
Asia-Pacific Operations-Singapore
29 Kian Teck Avenue
Singapore 628908
Information: +65 6268-8678

2. HAZARDS IDENTIFICATION**PRIMARY ROUTES OF ENTRY:**

⊕Eye ⊕Inhalation ⊕Skin ⊕Ingestion NTP

Carcinogen listed in

IARC OSHA ⊕Not Listed

GHS

Lead Free Products



Signal Word: Warning

Hazard statement(s)

H317 May cause an allergic skin reaction
 H319 Causes serious eye irritation
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
 EUH208 Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233 Keep container tightly closed
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P270 Do not eat, drink or smoke when using this product
 P273 Avoid release to the environment
 P280 Wear protective gloves/protective clothing/eye protection/face protection
 P362 + P364 Take off contaminated clothing and wash before reuse
 P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water
 P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Lead containing products



Signal Word: Warning

Hazard statement(s)

H303 May be harmful if swallowed
 H317 May cause an allergic skin reaction
 H319 Causes serious eye irritation
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
 H351 Suspected of causing cancer
 H361 Suspected of damaging fertility or the unborn child
 H373 May cause damage to organs through prolonged or repeated exposure
 H410 Very toxic to aquatic life with long lasting effects
 EUH201A Warning! Contains lead. Review listing.
 EUH208 Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233 Keep container tightly closed
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P270 Do not eat, drink or smoke when using this product
 P273 Avoid release to the environment
 P280 Wear protective gloves/protective clothing/eye protection/face protection
 P362 + P364 Take off contaminated clothing and wash before reuse
 P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water
 P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification:

Carcinogenicity (Category 2) (lead)

Reproductive toxicity (Category 2) (lead)

Skin sensitizer-Category 1B

Respiratory sensitizer-Category 1B

Eye irritation-Category 2A

Acute aquatic toxicity – Category 1 for lead containing products (H400)

Chronic aquatic toxicity – Category 1 for lead containing products (H410)

POTENTIAL HEALTH EFFECTS:

Eye Contact: Irritating to the eyes and if not removed, may result in serious irritation. Contact with fume from molten metal may cause irritation.

Ingestion: This product contains metal and organic chemicals. May be harmful if swallowed.

Inhalation: Inhalation of fume or dust may cause local irritation to the respiratory system. Inhalation of lead fume may be harmful. Rosin may cause occupational asthma. Cobalt may cause sensitization.

Skin Contact: May cause skin irritation. Antimony and Cobalt may cause dermatitis.

Chronic:

SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Prolonged inhalation of fume may result in lung complications.

COPPER: Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning.

INDIUM: May cause irritation to respiratory system.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.



WARNING: This product can expose you to chemicals including [lead] which is known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

WARNING: This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making of joints in any private or public potable (drinking) water supply system. Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #/EINECS#	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
TIN	*	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
		(Singapore)	2	-	-
SILVER	*	7440-22-4/231-131-3			
		(US)	0.01	0.1	-
		(EU)	-	0.1	-
		(Canada)	-	0.1	0.3
		(Singapore)	0.1	-	-
(Mexico)	-	0.1	-		
COPPER	*	7440-50-8/231-159-6			
		(US)	0.1 (fume)	0.2 (fume)	-
		(EU)	-	0.2 (fume)	-
		(Canada)	-	0.2 (fume)	0.6 (fume)
		(Singapore)	0.2(fume)	-	-
		(Mexico)	-	0.2(fume)	2
(China)	-	0.2(fume)	0.6		
LEAD	*	7439-92-1/231-100-4			
		(US)	0.05	0.05	-
		(EU)	-	0.15	-
		(Canada)	0.05	0.05	-
		(Singapore)	0.15	-	-
		(Mexico)	N.E.	0.15	-
(China)	-	0.05(dust) 0.03(fume)	- -		
ANTIMONY	*	7440-36-0/231-146-5			
		(US)	0.5	0.5	-
		(EU)	0.5	-	-

			(Canada)	-	0.5	1.5
			(Mexico)	N.E.	0.5	-
			(Singapore)	0.5	-	-
			(China)	-	0.5	-
INDIUM	*	7440-74-6/231-180-0				
			(US)	0.1	0.1	-
			(EU)	-	0.1	0.3
			(Canada)	-	0.1	0.3
			(Mexico)	-	0.1	0.3
			(Singapore)	0.1	-	-
			(China)	-	0.1	0.3
COBALT	*	7440-48-4/231-158-0		0.1	0.02	-
			(EU)	-	0.1	-
			(Canada)	-	0.05	0.1
			(Singapore)	0.02	-	-
ROSIN MIX	1.0-4.0	65997-05-9		N.E.	N.E.	N.E.
			(EU)	0.05	N.E.	0.15 (sensitizer)

N.E. = Not established
 * See alloy table TWA = time weighted average STEL= short term exposure limit

Handling of plain metal wire is not hazardous.

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. **Method:** Not established.

Auto-ignition Temperature:	Not established.
Flammable Limits:	Limits not established.
Extinguishing Media:	Use extinguishers appropriate for the surrounding fire conditions.
Special Fire Fighting	Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Pick up solids and put in container for reuse or recycling. Do not sweep powder or small particulate. Use vacuum. Reduce airborne dust and prevent scattering by moistening with water. Dispose of following all Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.

Storage Precautions: Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Local exhaust ventilation is recommended to keep exposures below established limits and protect operators. Use proper ventilation when working with leaded products.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated or exceed exposure limits.

Skin: Compatible chemical resistant gloves may be required for certain applications. Hot gloves as needed for melting applications. Handling of plain metal is not harmful.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas. Follow standard lead work practices when working with lead containing products.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area. When applicable, follow lead work practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Solid metal - wire	Boiling Point:	Not applicable.
Odor:	Odorless	Melting Point:	See table
Specific Gravity:	See table	pH:	Not applicable
Vapor Pressure:	Not established	Solubility in Water:	Insoluble
Vapor Density:	(air=1) Not applicable.		

10. STABILITY AND REACTIVITY

General:	Stable.
Conditions to Avoid:	Not established.
Incompatible Materials:	Avoid contact with acids, bases or oxidizing agents.
Hazardous Decomposition	Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity:	NTP: No		
	OSHA: No		
	IARC: Yes	Lead and lead compounds are listed as possible carcinogens.	
LD50:	Not established.	LC50:	Not established.

Chronic Toxicity: Lead can cause potential harm to the developing fetus.

12. ECOLOGICAL INFORMATION

Protect not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements. Not regulated under US DOT (United States Department of Transportation).

Not hazardous under all shipping regulations - all modes.

UN – none Marine Pollutant: No

Not regulated-ground/IATA, ocean

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

SARA 313 Listing - 40 CFR 372.65
Silver Copper Lead

All ingredients are listed on the EPA TSCA Inventory.

EPA Genetic Toxicology Program – Lead CAS# 7439-92-1



WARNING: This product can expose you to chemicals including [lead] which is known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

This product has been classified in accordance with the Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR)



Canadian WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic). (lead)
D2B Materials Causing Other Toxic Effects -irritant

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products

GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace GBZ2-2007.

16. OTHER INFORMATION

HMIS Hazard Rating:	Health:	2
	Fire:	1
	Reactivity:	0

Revised Date: 11 JUNE 2018

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

ALLOY TABLE**Metal alloy mixed with rosin (1- 4%)**

INDALLOY (metal mixtures)	Lead Pb	Tin Sn	Copper Cu	Silver Ag	Indium In	Cobalt Co	Antimony Sb	Specific Gravity	RoHS 2/3 Compliance
104 (62.5Sn/36.1Pb/1.4Ag)	34.7-35.7	60-61.9	-	1.34-1.39	-	-	-	8.41	No
(62Sn/36Pb/2Ag)	34.6-35.6	59.5-61.4	-	1.92-1.98	-	-	-	8.41	No
106 (Sn63/Pb37)	34.6-36.6	60.5-62.4	-	-	-	-	-	8.40	No
109 (60Sn/40Pb)	38.4 - 39.6	57.6 - 59.4	-	-	-	-	-	8.5	No
121 (96.5Sn/3.5Ag)	-	92.6-95.5	-	3.4-3.47	-	-	-	7.5	Yes
227 (77.2Sn/20In/2.8Ag)	-	74-76-4	-	2.69-2.77	19.2-19.8	-	-	7.25	Yes
228 (88Pb/10Sn/2Ag)	84-87	9.6-9.9	-	1.92-1.98	-	-	-	10.75	Yes
241 (SAC387) (95.5Sn/3.8Ag/0.7Cu)	-	91.7 - 94.5	0.67 - 0.69	3.65 - 3.76	-	-	-	7.40	Yes
256 (SAC 305) (96.5Sn/3Ag/0.5Cu)	-	92.6-95.5	0.48-0.495	2.88-2.97	-	-	-	7.40	Yes
Indalloy 262 (Cobalt995) (Sn995) (Sn99.5/0.5Cu/0.05 Co (doped))	-	99.5 - 98.5	0.48 - 0.495	-	-	0.048 - 0.0495	-	7.32	Yes
Non Standard Alloy (91.5Sn/8.5Sb)	-	87.8 – 90.6	-	-	-	-	8.16 – 8.42	7.22	Yes
Non Standard Alloy (95Pb/5Sn)	91-94	4.8-4.95	-	-	-	-	-		Yes
Non Standard Alloy 96Sn/4Ag	-	92-95	-	3.84-3.96	-	-	-	7.37	Yes
Non Standard Alloy (Sn99.3/Cu 0.7)	-	95.3-98.3	0.67-0.69	-	-	-	-	7.29	Yes

RoHS 2 ((2011/65/EU) = restriction of hazardous substances. +Review applicable EU guidelines for any exemptions that may apply for lead.

RoHS 3= products do not contain any listed phthalates

Other combinations of non- standard alloy mixes, not specifically listed may occur within the above.