

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ® SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: TACFLUX 055

SDS Number: SDS- 4821 Revised Date: 22 FEBRUARY 2017

Product Use: INDUSTRIAL USE- FLUX APPLICATIONS

MANUFACTURER:

In America:

The Indium Corporation of America 34 Robinson Rd., Clinton, New York 13323

Information: (315) 853-4900 nswarts@indium.com

In Europe:

Indium Corporation of Europe 7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore

29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou) Co., Ltd.

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Carcinogen listed in

⊗Eye ⊗Inhalation ⊗Skin ⊗Ingestion NTP IARC OSHA ⊗Not Listed

GHS





Signal Word: Warning Hazard statement(s)

H317 May cause an allergic skin reaction

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

EUH208 Contains rosin. May product an allergic reaction

Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 MINS)

POTENTIAL HEALTH EFFECTS:

Eye Contact: May cause Irritation to the eyes and if not removed promptly, may result in serious eye injury. Do

not allow material to come in contact with the eyes.

Ingestion: May be harmful if swallowed.

Inhalation: Heated vapor concentrations may irritation to respiratory tract. Rosin may cause occupational

asthma.

Skin Contact: May cause skin irritation or dermatitis. Allergic reactions are possible, especially with repeated or

prolonged exposure.

Chronic: Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of it's

product's for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS					
Components	% wt	CAS Registry #	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
ROSIN	40-50	65997-05-9	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15 (sensitiser)
POLYGLYCOL ETHER	35-45	9038-95-3	N.E.	N.E.	N.E.
NON HAZARDOUS PROPRIETARY ACTIVATORS	5 - 25	-	N.E.	N.E.	N.E.
N.E. = Not established	EU = European Union Occupational Exposure Limits				

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. Method: Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established, not flammable.

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Firefighters must wear NIOSH approved self-contained breathing apparatus and full

Procedures: protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Wear a respirator and appropriate Personal Protection (See Exposure

Controls/Personal Protective Section). Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Dispose of following all Federal, State and Local regulations. Ensure area is properly vented. In the EU refer to the Special

Waste Regulations.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills. Avoid breathing

Precautions: vapors from heated material. Avoid contact with eyes, skin and clothing. Use with adequate

ventilation.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Keep away from heat

and flame. Store away from incompatible materials. Empty containers may be hazardous as

they contain product residue.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Good general exhaust ventilation should be sufficient to control airborne levels and keep

exposures to as low as possible.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended under certain circumstances where airborne concentrations are expected

to be elevated.

Skin: Compatible chemical resistant gloves. Protective outer garment, apron and sleeves as appropriate.

Protective skin from direct exposure.

Other: Eyewash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately.

Practices: Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water

immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: **Boiling Point:** Not established Flux-creamy Odor: Mild characteristic odor. **Melting Point:** Not established **Specific Gravity:** Not established pH: Not applicable Vapor Pressure: Not established Solubility in Water: Insoluble

Vapor Density: (air=1) Not applicable.

10.STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Freezing temperatures. High temperatures.

Incompatible Materials: Not established

Hazardous Decomposition /

Toxic oxides-carbon dioxide/carbon monoxide

Combustion:

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

> OSHA: No IARC: No

LD50: Not established. LC50: Not established.

Other: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational asthma.

None of the ingredients including proprietary are listed as a carcinogen.

Product mixture not tested.

ECOLOGICAL INFORMATION

. Product not tested.

DISPOSAL CONSIDERATION 13.

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local environmental regulations.

In Europe follow the Special Waste Regulations.

TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States Department of Transportation). Non hazardous for shipping. Not regulated under IATA.

UN - none Marine Pollutant: No


REGULATORY INFORMATION 15.

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

SARA 313 Listing (TRI Reporting) - 40 CFR 372.65 - Proprietary polyglycol ether 12%

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



D2B Materials Causing Other Toxic Effects -irritant

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

For compliance with EU Directive 2011/65/EU, Restriction of Hazardous Substances (RoHS).

Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS). (GHS)

In China:

Decree No. 591: Regulations on the Control over Safety of Hazardous Chemicals GB 30000.2-29-2013, Rules for classification and labeling of chemicals. (GHS)

GB/T 16483-2008, GB/T 17517-2013

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007.

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 1

Fire: 0 Reactivity: 0

Revised Date: 22 FEBRUARY 2017

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.