



**INDIUM CORPORATION OF AMERICA®\EUROPE®\ASIA-PACIFIC®
INDIUM CORPORATION (SUZHOU)®**

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: #16-1020 THINNER

SDS Number: SDS-HG4041

Revised Date: 24 JANUARY 2015

Product Use: Industrial Use – Flux Thinner

MANUFACTURER:

In America:

The Indium Corporation of America
1676 Lincoln Ave., Utica NY 13502
Information: (315) 853-4900
nswarts@indium.com

EMERGENCY PHONE:

CHEMTREC 24 hrs.
USA: 1 (800) 424-9300
Outside USA: +1 (703) 527-3887

In Europe:

Indium Corporation of Europe
7 Newmarket Ct.
Kingston, Milton Keynes, UK, MK 10 OAG
Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America
Asia-Pacific Operations-Singapore
29 Kian Teck Avenue
Singapore 628908
Information: +65 6268-8678

In China:

Indium Corporation (Suzhou) Co., Ltd
No. 428 Xinglong Street
Suzhou Industrial Park
Suchun Industrial Square
Unit No. 14-C
Jiangsu Province, China 215126
Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Eye
 Inhalation
 Skin
 Ingestion
 NTP
 IARC
 OSHA
 Not Listed

Carcinogen listed in

GHS



Signal Word: Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking
 P233 Keep container tightly closed
 P240 Ground/Bond container and receiving equipment
 P241 Use explosion-proof electrical/ventilating/lightening/equipment
 P242 Use only non- sparking tools
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P270 Do not eat, drink or smoke when using this product
 P273 Avoid release to the environment
 P280 Wear protective gloves/protective clothing/eye protection/face protection
 P362 Take off contaminated clothing and wash before reuse
 P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water
 P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification:

Flammable Liquid – Category 2

Eye irritation – Category 2A

Specific target organ toxicity- single exposure – Category 3- central nervous system

POTENTIAL HEALTH EFFECTS:

Eye Contact: Vapors may be irritating, liquid may damage eye tissue.
Ingestion: May result in gastric disturbances such as nausea and vomiting.
Inhalation: May cause mild throat irritation, headache or dizziness.
Skin Contact: May cause irritation.
Chronic: Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of it's

products for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
ISOPROPYL ALCOHOL	55-65	67-63-0 (US)	980	983	1230
		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Singapore)	983	-	1230
		(Mexico)	-	980	1225
		(China)	-	350	700
INERT SOLVENT	35-45	-	N.E	N.E	N.E.

Symbol: Xi, F
N.E. = Not established

Risk Phrases: R36/37/38, R11, R67

PRODUCT DOES NOT CONTAIN ANY EU REACH SUBSTANCES OF VERY HIGH CONCERN

4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

- Flash Point:** 85F **Method:** TCC
- Auto-ignition Temperature:** N/A
- Flammable Limits:** Upper limit 12. Lower limit 2.
- Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions.
- Special Fire Fighting Procedures:** Standard fire fighting equipment

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: DO NOT allow material to enter sewer system or waterway. Wear personal protective equipment, such as gloves and depending on the quantity a respirator with organic cartridges may be required. Clean up by absorption. Eliminate sources of ignition. Keep unnecessary personnel away. Put clean-up materials in a properly labeled metal drum. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

7. HANDLING AND STORAGE

Handling Precautions: Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal protective equipment.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area away from sources of ignition. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation is recommended to keep exposure limits as low as possible.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: A NIOSH approved or EU compliant CE marked air-purifying respirator with a fume/organic chemical cartridge is recommended where airborne concentrations are expected to be elevated.

Skin: Compatible chemical resistant gloves.

Other: Lab coat, eyewash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Practices: Maintain good housekeeping. Clean up spills immediately.

Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Liquid, clear	Boiling Point:	177°F
Odor:	Alcoholic	Melting Point:	Not applicable
Specific Gravity:	0.881@60F	pH:	Not available
Vapor Pressure:	33 mm HG @68°C	Solubility in Water:	Soluble
Vapor Density:	N/A	Evaporation Rate:	1.7
Volatile by Volume:	100%		

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Direct heat, open flames and storage in aluminum.

Incompatible Materials: phosphorus, halogens, anhydrides, monomers, aldehydes, trichlorides

Hazardous Decomposition / Carbon dioxide/carbon monoxide.

Combustion:**Hazardous Polymerization:** Will not occur.**11. TOXICOLOGICAL INFORMATION****Carcinogenicity:****NTP:** No**OSHA:** No**IARC:** No**LD50:**

Not established.

LC50:

Not established.

12. ECOLOGICAL INFORMATION

Product not tested.

13. DISPOSAL CONSIDERATION**Waste Disposal Method:**

Dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

Shipping: UN 1219, Isopropanol, 3, PG II



North America Emergency Guide Book – Guide #129

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

WHMIS: Class B2 Flammable Liquid, D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).



This product has been classified in accordance with the guidelines, as set, by the Dept of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with Mexican regulations NOM-0180STPS-2000 and NOM-010-STPS-1999.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

SARA 313 Listing - 40 CFR 372.65: None

All ingredients are listed on the EPA TSCA Inventory.

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

X_nF

Risk Phrases:

R36/37/38 Irritating to eyes, respiratory system and skin
 R10 Flammable
 R67 Vapors may cause drowsiness and dizziness

Safety Phrases:

S20/21 When using do not eat, drink or smoke
 S23 Do not breathe fumes
 S24/25 Avoid contact with skin and eyes
 S27 Take off immediately all contaminated clothing
 S28 After contact with skin wash immediately with plenty of soap and water
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection
 S62 If swallowed, do not induce vomiting seek medical advice immediately and show container or label
 S7 Keep container tightly closed

16. OTHER INFORMATION

HMIS Hazard Rating:	Health:	1
	Fire:	3
	Reactivity:	0
Revised Date:	24 JANUARY 2015	
Prepared by:	Nancy Swarts, Indium Corporation of America	
Approved by:	Nancy Swarts, Indium Corporation of America	

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.