

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC®\INDIUM CORPORATION (SUZHOU) ® SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: 16-3519 FLUX THINNER

SDS Number: SDS-4090 Revised Date: 8 DECEMBER 2014

Product Use: INDUSTRIAL USE -THINNER

MANUFACTURER:

In America:

The Indium Corporation of America 1676 Lincoln Ave., Utica NY 13502 Information: (315) 853-4900 nswarts@indium.com

In Europe:

Indium Corporation of Europe 7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore 29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou) Co., Ltd.

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 428

Jiangsu Province, China 215126 Information: 86-512-6283-4900

2. HAZARDS IDENTIFICATION

GHS:





Signal Word: Danger Hazard statement(s)

H225 Highly flammable liquid and vapor
H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking

P233 Keep container tightly closed

P240 Ground/Bond container and receiving equipment

P241 Use explosion-proof electrical/ventilating/lightening/equipment

P242 Use only non- sparking tools

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification:

Flammable Liquid – Category 2 Eye irritation – Category 2A

Specific target organ toxicity- single exposure – Category 3- central nervous system

PRIMARY ROUTES OF ENTRY: Carcinogen listed in

XEye XInhalation XSkin XIngestion NTP IARC OSHA XNot Listed

POTENTIAL HEALTH EFFECTS:

Eye Contact: Vapors may be irritating, liquid may damage eye tissue.

Ingestion: May cause persistent nausea, vomiting and abdominal pain.

Inhalation: Vapor may cause headaches and or dizziness. Rosin may cause occupational asthma.

Skin Contact: Prolonged contact may cause irritation and dermatitis.

Chronic: Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its

products for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS					
Components	% wt	CAS Registry #	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
ISOPROPANOL	85-90	67-63-0 (US)	980	983	1225
PROPAN-2-OL		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Singapore)	983	-	1230
		(Mexico)	-	980	1225
		(China)	-	350	700
ROSIN	< 5	8050-09-7 (EU)	N.E. 0.05	N.E. -	N.E. 0.15
TERPENE ALCOHOL	5-10	-	N.E.	N.E.	N.E.
Symbol: Xi, F Risk Phrases: R36/37/38, R11 N.E. = Not established EU = European Exposure Limits					

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: 54 F (12C) Method: Closed Cup

Auto-ignition Temperature: N/A

Flammable Limits: Upper: 12 ; Lower 2

Extinguishing Media: Dry chemical, Water or CO₂. Use extinguishers appropriate for the surrounding fire

conditions.

Special Fire Fighting

Procedures: Wear protective clothing and self - contained breathing apparatus. Use water to cool fire

exposed containers. Flammable vapors may travel great distances to ignition source and flash back.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: DO NOT allow material to enter sewer system or waterway. Wear personal protective equipment. Eliminate sources of ignition. Ventilate area in accordance with regulations. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal

Precautions: protective equipment.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product

label for specific storage temperature requirements. Rotate stock to ensure use before

expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation recommended.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An authority approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended where airborne concentrations are expected to be elevated.

Skin: Compatible chemical resistant gloves. Use gloves such as nitrile, which are compatible with

alcohol's.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume/splash

areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately.

Practices: Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.

Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear Boiling Point: 182 F

Odor: Alcohol odor. Evaporation Rate: Not available

Specific Gravity:0.792pH:3.8Vapor Pressure:44 mm HG @ 25 CSolubility in Water:Slightly

Vapor Density: 2.95 (air=1) % Volatiles by volume: 90%

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Direct heat, open flames and storage in aluminum.

Incompatible Materials: Anhydrides, halogens, phosphorus, trichlorides, monomers, aldehydes

Hazardous Decomposition /

Combustion:

Carbon dioxide/carbon monoxide.

Hazardous Polymerization: Will not occur.

11.TOXICOLOGICAL INFORMATION

Carcinogenicity: No National Toxicity Program **NTP**:

> Occupational Safety & Health Administration OSHA: No International Agency for Research on Cancer IARC: No

LD50: Not established. LC50: Not established.

IPA: NIOSH RTECS - NT8050000

Oral rat LD50 - 4396 mg/kg Dermal rat LD50 - 12800 mg/kg Dermal rabbit - 12870 mg/kg Inhalation rat - 72.6 mg/l 4 h

12. ECOLOGICAL INFORMATION

Product not tested.

IPA: Freshwater Algae - 1000 mg/l EC50 >72h Freshwater Fish - 1400000 ug/l LC50 96h Water Flea - 13299 mg/l EC50 48 h

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local

environmental regulations. In Europe follow the Special Waste Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

UN1219, Isopropanol, 3, PG II (mixture)



North America Emergency Guide Book – Guide #129

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS: Class B2 Flammable Liquid





This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

SARA 313 Listing - 40 CFR 372.65: None

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified under the Mexican regulations NOM-018-STPS-2000 and NOM-010-STPS-1999.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

Xi, F

Risk Phrases:

R36/37/38 Irritating to eyes, respiratory system and skin

R 11 Highly Flammable

R67 Vapors may cause drowsiness and dizziness

Safety Phrases:

S16 Keep away from sources of ignition - "No Smoking"

S20/21 When using do not eat, drink or smoke

S23 Do not breathe fumes

S24/25 Avoid contact with skin and eyes

S28 After contact with skin wash immediately with plenty of soap and water

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection

S62 If swallowed, do not induce vomiting seek medical advice immediately and show container or label

S7 Keep container tightly closed

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 3

Reactivity: 0

Revised Date: 8 DECEMBER 2014

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.