



**INDIUM CORPORATION OF AMERICA®\EUROPE®\ASIA-PACIFIC®  
INDIUM CORPORATION (SUZHOU)®**

**SAFETY DATA SHEET**

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product Identifier:** 16-3565 THINNER

**SDS Number:** SDS-4032

**Revised Date:** 7 FEBRUARY 2015

**Product Use:** INDUSTRIAL USE- THINNER

**MANUFACTURER:**

**In America:**

The Indium Corporation of America  
1676 Lincoln Ave., Utica NY 13502  
Information: (315) 853-4900  
[nswarts@indium.com](mailto:nswarts@indium.com)

**EMERGENCY PHONE:**

**CHEMTREC 24 hrs.**  
**USA: 1 (800) 424-9300**  
**Outside USA: +1 (703) 527-3887**

The Indium Corporation of America  
80 Scott Street  
Elk Grove Village, Illinois 60004  
(847) 439-9135

**In Europe:**

Indium Corporation of Europe  
7 Newmarket Ct.  
Kingston, Milton Keynes, UK, MK 10 OAG  
Information: +44 [0] 1908 580400

**In China:**

Indium Corporation (Suzhou) Co., Ltd  
No. 428 Xinglong Street  
Suzhou Industrial Park  
Suchun Industrial Square  
Unit No. 14-C  
Jiangsu Province, China 215126  
Information: (86) 512-6283-4900

**In Asia:**

Indium Corporation of America  
Asia-Pacific Operations-Singapore  
29 Kian Teck Avenue  
Singapore 628908  
Information: +65 6268-8678

## 2. HAZARDS IDENTIFICATION

### PRIMARY ROUTES OF ENTRY:

\*Eye      \*Inhalation      \*Skin      \*Ingestion      NTP      Carcinogen listed in IARC      OSHA      \*Not Listed

GHS



Signal Word: Danger

### Hazard statement(s)

H225      Highly flammable liquid and vapor  
 H319      Causes serious eye irritation  
 H336      May cause drowsiness or dizziness

### Precautionary statement(s)

P210      Keep away from heat/sparks/open flames/hot surfaces – No smoking  
 P233      Keep container tightly closed  
 P240      Ground/Bond container and receiving equipment  
 P241      Use explosion-proof electrical/ventilating/lightening/equipment  
 P242      Use only non- sparking tools  
 P261      Avoid breathing dust/fume/gas/mist/vapors/spray  
 P270      Do not eat, drink or smoke when using this product  
 P273      Avoid release to the environment  
 P280      Wear protective gloves/protective clothing/eye protection/face protection  
 P362      Take off contaminated clothing and wash before reuse  
 P301 + P314      IF SWALLOWED: Get Medical advice/attention if you feel unwell  
 P302 +P352      IF ON SKIN: Wash with plenty of soap and water  
 P304 + 341      IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing  
 P305 + 351      IF IN EYES: Rinse continuously with water for several minutes (15 mins)

### Classification:

Flammable Liquid – Category 2  
 Eye irritation – Category 2A  
 Specific target organ toxicity- single exposure – Category 3- central nervous system

### POTENTIAL HEALTH EFFECTS:

**Eye Contact:**      Vapors may be irritating, liquid may damage eye tissue.

**Ingestion:**      May cause persistent nausea, vomiting and abdominal pain.

**Inhalation:**      Vapor may cause headaches and or dizziness. High concentrations may cause central nervous system depression.

**Skin Contact:**      Prolonged contact may cause irritation and dermatitis.

**Chronic:**      Repeated skin contact can cause dryness.

**NOTE:** The Indium Corporation does not recommend, manufacture, market or endorse any of its' products for human consumption.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #	PEL mg/m <sup>3</sup>	TLV-TWA mg/m <sup>3</sup>	TLV-STEL mg/m <sup>3</sup>
ISOPROPANOL	100	67-63-0 (US)	980	983	1225
PROPAN-2-OL		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Singapore)	983	-	1230
		(Mexico)	-	980	1225
		(China)	-	350	700
		(Germany)	-	980	-

Symbol: Xi, F

Risk Phrases: R36/37/38, R11, R67

N.E. = Not established

EU = European Exposure Limits

IDLH Level 12,000 ppm

**PRODUCT DOES NOT CONTAIN ANY EU REPORTABLE SUBSTANCES OF VERY HIGH CONCERN (SVHC)**

### 4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

### 5. FIRE FIGHTING MEASURES

- Flash Point:** 12°C (53°F)      **Method:** Closed Cup
- Auto-ignition Temperature:** 750 F
- Flammable Limits:** Upper: 12 ; Lower 2

**Extinguishing Media:** Dry chemical, CO<sub>2</sub>, Dry sand, alcohol foam. Use extinguishers appropriate for the surrounding fire conditions.

**Special Fire Fighting Procedures:** Wear protective clothing and self-contained breathing apparatus. Use water to cool fire exposed containers. Flammable vapors may travel great distances to ignition source and flash back.

## 6. ACCIDENTAL RELEASE MEASURES

**Spill or Leak Procedures:** DO NOT allow material to enter sewer system or waterway. Wear personal protective equipment. Eliminate sources of ignition. Use non-sparking tools. Ventilate area in accordance with regulations. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations. Classified as a flammable liquid.

## 7. HANDLING AND STORAGE

**Handling Precautions:** Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal protective equipment.

**Storage Precautions:** Store product in tightly capped original containers in a cool, dry area. Keep away from sources of ignition. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation recommended when there is a potential for exposure. Heating of product requires ventilation and care when heating a flammable material.

### Personal protection:

**Eyes:** Chemical safety glasses/goggles. Face shield/goggles for splash hazards.

**Respirator:** An approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended where airborne concentrations are expected to be elevated.

**Skin:** Compatible chemical resistant gloves. Use gloves such as nitrile, which are compatible with alcohol.

**Other:** Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume/splash areas.

**Work/Hygienic Practices:** Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	Colorless liquid	<b>Boiling Point:</b>	82°C (180°F)
<b>Odor:</b>	Alcohol odor. 22ppm threshold	<b>Evaporation Rate:</b>	2.4
<b>Specific Gravity:</b>	0.790 @ 60° F	<b>pH:</b>	Neutral
<b>Vapor Pressure:</b>	44 mm HG @ 25 F	<b>Solubility in Water:</b>	Miscible
<b>Vapor Density:</b>	2.1 (air=1)	<b>% Volatiles by volume:</b>	100
<b>Molecular Weight:</b>	60.1	<b>Flash Point:</b>	54F (12C)
<b>Molecular Formula:</b>	C3 H8 O		

**10. STABILITY AND REACTIVITY**

<b>General:</b>	Stable.
<b>Conditions to Avoid:</b>	Direct heat, open flames and storage in aluminum.
<b>Incompatible Materials:</b>	Anhydrides, halogens, phosphorus, trichlorides, monomers, aldehydes, acids
<b>Hazardous Decomposition / Combustion:</b>	Carbon dioxide/carbon monoxide, peroxides.
<b>Hazardous Polymerization:</b>	Will not occur.

**11. TOXICOLOGICAL INFORMATION**

<b>Carcinogenicity:</b>	National Toxicity Program <b>NTP:</b>	No	
	Occupational Safety & Health Administration <b>OSHA:</b>	No	
	International Agency for Research on Cancer <b>IARC:</b>	No	
<b>LD50:</b>	Not established.	<b>LC50:</b>	Not established.

NIOSH RTECS – NT8050000

Oral rat LD50 - 4396 mg/kg  
 Dermal rat LD50 – 12800 mg/kg  
 Dermal rabbit – 12870 mg/kg  
 Inhalation rat – 72.6 mg/l 4 h

**12. ECOLOGICAL INFORMATION**

Freshwater Algae – 1000 mg/l EC50 >72h  
 Freshwater Fish – 1400000 ug/l LC50 96h  
 Water Flea – 13299 mg/l EC50 48 h

**13. DISPOSAL CONSIDERATION**

**Waste Disposal Method:** Dispose of in accordance with all Federal, State and Local

environmental regulations. In Europe follow the Special Waste Regulations. Flammable liquid classification. Recycle/reuse if possible. Empty containers should be considered as hazardous as they contain product residues.

## 14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

UN 1219, Isopropanol, 3, PG II



North America Emergency Guide Book – Guide #129

## 15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

WHMIS: Class B2 Flammable Liquid, D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).



This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

SARA 313 Listing - 40 CFR 372.65: *Only those who manufacture by the strong acid process are subject.*

All ingredients are listed on the EPA TSCA Inventory, listed on the Philippines Inventory of Chemicals and Chemical Substances 2000, listed on the Canadian DSL and listed under EINECS # 200-661-7.

This product has been classified under the Mexican regulations NOM-018-STPS-2000 and NOM-010-STPS-1999.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

This product is in full compliance with the RoHS European Directive regarding the use of certain hazardous substances in electrical and electronic equipment.

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

Xi, F

**Risk Phrases:**

