

# INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

### **SAFETY DATA SHEET**

This safety data sheet represents a family grouping of all metal mixes that are blended with the same flux known as Indium 5.8LS. A product table is provided that lists all metal groupings. To better serve all of our customers Indium Corporation has generated one SDS, for this product, to be used within the United States as well as internationally. Some of the regulatory information contained within may not be applicable to the customer's individual state or country. Unless otherwise stated the health and safety information provided within is applicable to all products.

#### 1. PRODUCT AND COMPANY IDENTIFICATION

General Product Class Identifier: INDALLOY WITH INDIUM 5.8 LS FLUX VEHICLE

(View product table for individual product descriptions)

SDS Number: SDS-4010 Revised Date: 8 SEPTEMBER 2016

**Product Use:** Industrial Use - No-clean solder paste consisting of a flux vehicle blended with an 83-92 % pre-

alloyed metal powder used for solder applications. Review alloy table for listing of metal mixes with

the same family flux.

#### **MANUFACTURER:**

In America:

The Indium Corporation of America 34 Robinson Rd, Clinton NY 13323 Information: (315) 853-4900

nswarts@indium.com

In Europe:

Indium Corporation of Europe 7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore

29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678

**EMERGENCY PHONE:** 

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou), Co., Ltd.

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900 SDS - 4010 INDALLOY WITH INDIUM 5.8 LS

#### 2. HAZARDS IDENTIFICATION

#### PRIMARY ROUTES OF ENTRY:

#### **CARCINOGEN LISTED IN:**

⊗Eye ⊗Inhalation ⊗Skin ⊗Ingestion NTP IARC OSHA ⊗Not Listed

GHS:

#### Lead free products





Signal Word: Warning

Hazard statement(s)

H317 May cause an allergic skin reaction

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation

EUH208 Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

#### Lead containing products







#### Signal Word: Warning

#### Hazard statement(s)

H303 May be harmful if swallowed H317 May cause an allergic skin reaction

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation H351 Suspected of causing cancer

H361 Suspected of damaging fertility or the unborn child

H373 May cause damage to organs through prolonged or repeated exposure

H410 Very toxic to aquatic life with long lasting effects

EUH201A Warning! Contains lead (applicable only to the products listed that contain lead) Review listing.

EUH208 Contains rosin. May produce an allergic reaction

SDS - 4010 INDALLOY WITH INDIUM 5.8 LS

Precautionary statement(s) P233 Keep container tightly closed P261 Avoid breathing dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product P270 Avoid release to the environment P273 Wear protective gloves/protective clothing/eye protection/face protection P280 P362 Take off contaminated clothing and wash before reuse P301 + P314 IF SWALLOWED: Get medical advice/attention if you feel unwell IF ON SKIN: Wash with plenty of soap and water P302 +P352 P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification:

Carcinogenicity (Category 2) (lead)

Reproductive toxicity (Category 2) (lead)

Skin sensitizer-Category 1B

Respiratory sensitizer-Category 1B Acute toxicity, oral-Category 5 (lead) Acute toxicity, inhalation 4 (lead)

Specific target organ toxicity single exposure, respiratory tract- Category 3 Acute aquatic toxicity – Category 1 for lead containing products (H400) Chronic aquatic toxicity – Category 1 for lead containing products (H410)

#### **POTENTIAL HEALTH EFFECTS:**

**Eye Contact:** Contact with material at room temperature or fume from material at typical re-flow temperatures

over 100°C may cause eye irritation.

Ingestion: This product contains alloy powders and organic chemicals. May be harmful if swallowed

**Inhalation:** Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local

irritation to the respiratory system. Rosin fume may cause occupational asthma.

**Skin Contact:** May cause skin irritation. Rosin may cause dermatitis.

**Chronic: LEAD:** Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory

irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and

kidnevs.

**SILVER:** Chronic skin contact or ingestion of silver dust, salts, or fume can result in a condition

known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Has been shown to increase incidence of sarcoma in animal tests. Chronic exposure to tin

dusts and fume may result in "stannosis" a mild form of pneumoconiosis.

**COPPER:** Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever;

dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

WARNING: This product contains a chemical (s) known to the State of California to cause cancer and/or

birth defects (or other reproductive harm). (lead)

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its

products for human consumption.

WARNING: This product may contain lead. Lead may be harmful to your health. US Federal law prohibits

the use of leaded solders in making joints or fittings in any private or public water supply

system. Keep out of the reach of children.

| 3. COMPOSITION / INFORMATION ON INGREDIENTS |         |                        |           |                          |                   |  |  |  |  |
|---|---------|------------------------|-----------|--------------------------|-------------------|--|--|--|--|
| Components                                  |         | CAS Registry #/EINECS# |           | TLV-TWA<br>mg/m³         | TLV-STEL<br>mg/m³ |  |  |  |  |
| TIN   | *       | 7440-31-5/231-141-8    |           |                          |                   |  |  |  |  |
|   |         | (US)                   | 2         | 2                        | -                 |  |  |  |  |
|   |         | (EU)                   | -         | 2                        | 4                 |  |  |  |  |
|   |         | (Canada)               | -         | 2                        | 4                 |  |  |  |  |
|   |         | (Singapore)            | 2         | -                        | -                 |  |  |  |  |
| LEAD  | *       | 7439-92-1/231-100-4    |           |                          |                   |  |  |  |  |
|   |         | (US)                   | 0.05      | 0.05                     | -                 |  |  |  |  |
|   |         | (EU)                   | -         | 0.15                     | -                 |  |  |  |  |
|   |         | (Canada)               | 0.05      | 0.05                     | -                 |  |  |  |  |
|   |         | (Singapore)            | 0.15      | -                        | -                 |  |  |  |  |
|   |         | (Mexico)               | 0.15      | -                        | -                 |  |  |  |  |
|   |         | (China)                | -         | 0.05(dust)<br>0.03(fume) | -                 |  |  |  |  |
| SILVER                                      | *       | 7440-22-4/231-131-3    |           |                          |                   |  |  |  |  |
|   |         | (US)                   | 0.01      | 0.1                      | -                 |  |  |  |  |
|   |         | (EU)                   | -         | 0.1                      | -                 |  |  |  |  |
|   |         | (Canada)               | N.E.      | 0.1                      | 0.3               |  |  |  |  |
|   |         | (Singapore)            | 0.1       | -                        | -                 |  |  |  |  |
|   |         | (Mexico)               | 0.1       | -                        | -                 |  |  |  |  |
| COPPER                                      | *       | 7440-50-8/231-159-6    |           |                          |                   |  |  |  |  |
|   |         | (US)                   | 0.1       | 0.2                      | -                 |  |  |  |  |
|   |         | (EU)                   | -         | 0.2 (fume)               | 2(dust)           |  |  |  |  |
|   |         | (Canada)               | -         | 0.2                      | 0.6               |  |  |  |  |
|   |         | (Singapore)            | 0.2(fume) | 1(dust)                  | -                 |  |  |  |  |
|   |         | (Mexico)               | 0.2       | -                        | 2                 |  |  |  |  |
|   |         | (China)                | -         | 0.2(fume)                | 0.6(fume)         |  |  |  |  |
| віѕмитн                                     | *       | 7440-69-9/231-177-4    | N.E.      | N.E.                     | N.E.              |  |  |  |  |
| ROSIN                                       | 3.0-4.0 | 65997-05-9 (US)        | N.E.      | N.E.                     | N.E.              |  |  |  |  |

(EU) 0.05 - 0.15 (sensitiser)

PROPRIETARY 4.0-14.0 N.E. N.E. N.E.

N.E. = Not established \* See Alloy Table

## **ALLOY TABLE (DATA)**

#### %Metal Mix in Flux

| Indalloy                                     | %TIN      | %SILVER   | %COPPER   | %BISMUTH | %LEAD     | RoHS*                                |  |  |  |  |  |
|--|-----------|-----------|-----------|----------|-----------|--------------------------------------|--|--|--|--|--|
| Mixture<br>Products<br>(%Metal)              | Sn        | Ag        | Cu        | Bi       | Pb        | Compliance<br>(2011/65/EU/<br>RoHS2) |  |  |  |  |  |
| 104<br>(Sn62/Pb36/2Ag<br>)                   | 51.9-57.5 | 1.2-1.8   | -         | -        | 29.9-33.2 | NO                                   |  |  |  |  |  |
| 106<br>(Sn63/37Pb)                           | 52.3-58   | -         | -         | -        | 30.7-34   | NO                                   |  |  |  |  |  |
| LEAD FREE PRODUCTS LISTED BELOW              |           |           |           |          |           |                                      |  |  |  |  |  |
| 121<br>(96.5 Sn/3.5Ag)                       | 80.1-88.8 | 2.9-3.2   | -         | -        | 1         | YES                                  |  |  |  |  |  |
| 241<br>(SAC 387)<br>(95.5Sn/3.8Ag/0<br>.7Cu) | 79.3-87.9 | 3.2-3.5   | 0.58-0.64 | -        | -         | YES                                  |  |  |  |  |  |
| 246<br>(95.5Sn/4Ag/0<br>.5Cu)                | 79.3-87.9 | 3.3-3.7   | 0.42-0.46 | -        | -         | YES                                  |  |  |  |  |  |
| 249<br>(91.8Sn/4.8Bi/<br>3.4Ag)              | 76.2-84.5 | 2.8-3.1   | -         | 4-4.4    | -         | YES                                  |  |  |  |  |  |
| 252<br>(95.5Sn/3.9Ag/0<br>.6Cu)              | 79.3-87.9 | 3.2-3.6   | 0.50-0.55 | -        | -         | YES                                  |  |  |  |  |  |
| 256<br>(SAC 305)<br>(96.5Sn/3Ag/0.5<br>Cu)   | 80.1-88.8 | 2.5-2.8   | 0.42-0.46 | 1        | 1         | YES                                  |  |  |  |  |  |
| 263<br>(99Sn/0.3Ag/0.7<br>Cu)                | 82-91     | 0.25-0.28 | 0.58-0.64 | -        | -         | YES                                  |  |  |  |  |  |
| NS<br>(90Sn/7.5Bi/2Ag<br>/0.5Cu)             | 74.7-82.8 | 1.7-1.8   | 0.42-0.46 | 6.2-6.9  | -         | YES                                  |  |  |  |  |  |

**NS = Non-standard alloy mixture** 

\*RoHS 2 = Restriction of Hazardous Substances

#### 4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

**Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately. **Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

#### 5. FIRE FIGHTING MEASURES

Flash Point: Not established. Method: Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established.

**Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Firefighters must wear NIOSH approved self-contained breathing apparatus and full

**Procedures:** protective clothing.

#### **6. ACCIDENTAL RELEASE MEASURES**

Spill or Leak Procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly

cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose contaminated cloth rags or paper towels following all Federal, State and Local regulations. In the EU refer to the Special Waste

Regulations. Material may have reclaim value.

#### 7. HANDLING AND STORAGE

**Handling**Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate

production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are

washed.

**Storage Precautions:** Store product in tightly capped original containers in a cool, dry area. Refer to product

label for specific storage temperature requirements. Rotate stock to ensure use before

expiration date on the label.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Use only with production equipment (stencil printers and re-flow furnaces) with

adequate ventilation and other safety features specifically designed for use

with solder paste. Control concentration of all components so that exposure levels

are not exceeded.

**Personal protection:** 

**Eyes:** Chemical safety glasses/goggles. Face shield for splash hazards.

SDS - 4010 INDALLOY WITH INDIUM 5.8 LS

**Respirator:** An authority approved or compliant marked air-purifying respirator with a fume/organic chemical

> cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or

exceed exposure limits.

Skin: Compatible chemical resistant gloves. Do not use latex gloves.

Other: Lab coat, eyewash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic **Practices:** 

Maintain good housekeeping. Clean up spills immediately. DO NOT allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point:** Appearance: Grey colored paste. Not applicable. Odor: Mild characteristic odor. **Melting Point:** Not applicable **Specific Gravity:** Not applicable. Not applicable pH: **Vapor Pressure:** Not applicable. Solubility in Water: Insoluble (paste)

Vapor Density: (air=1) Not applicable.

#### 10. STABILITY AND REACTIVITY

General: Stable.

**Conditions to Avoid:** Not established.

Avoid contact with acids, bases or oxidizing agents. **Incompatible Materials:** 

Harmful organic fumes and toxic oxide fumes may form at elevated **Hazardous Decomposition /** 

Combustion: temperatures.

**Hazardous Polymerization:** Will not occur.

#### 11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

> OSHA: No 29CFR1910.1025

IARC: Yes Lead and lead compounds are listed as possible carcinogens.

Not established. LC50: LD50: Not established.

Other: Chronic Toxicity: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational asthma. Lead can cause potential harm to the developing fetus.

No other ingredients are listed as carcinogens or toxic.

# **ECOLOGICAL INFORMATION**

Product not tested.

12.

An environmental hazard cannot be excluded in the event of unprofessional handling. Some ingredients contained are harmful to the environment.

Copper - Toxicity to daphia and other aquatic invertibrates mortality NOEC - Daphnia 0.004 mg/l - 24h.

Lead – Toxicity to fish – mortality LOEC – rainbow trout – 1.19 mg/l – 96h. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Bioaccumulation – Oncorhynchus kisutch – 2 weeks Bioconcentration factor (BCF): 12. Fresh fish: 0.44 mg/l LC50 96h/ 1.32 mg/l LC50 96h/water Flea: 600 ug/l EC50 = 48h

#### 13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for

recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the rules for waste assessments.

#### 14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated (US Department of Transportation).

Not hazardous under shipping regulations, all modes.

Non-hazardous under IATA. Not regulated

UN - none Marine Pollutant: No

North American Emergency Guide Book - Not applicable

#### 15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

California PROP 65(Safe Drinking Water Standard): WARNING:

This product contains a chemical (s) known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (lead)

SARA 313 Listing - 40 CFR 372.65

Lead CAS# 7439-92-1 Silver CAS# 7440-22-4 Copper CAS# 7440-50-8

EPA Genetic Toxicology Program - Lead CAS# 7439-92-1

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS:

D2A - Materials Causing Other Toxic Effects-Very Toxic Material (Chronic). (lead) D2B - Materials Causing Other Toxic Effects (skin irritation/skin sensitization)

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

SDS - 4010 INDALLOY WITH INDIUM 5.8 LS

This product has been classified in accordance with Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

For compliance with EU Directive 2002/95/EC, Restriction of Hazardous Substances (RoHS), see Alloy Table.

#### Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS). (GHS)

#### In China:

Decree No. 591: Regulations on the Control over Safety of Hazardous Chemicals GB 30000.2-29-2013, Rules for classification and labeling of chemicals. (GHS) GB/T 16483-2008, GB/T 17517-2013

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007

All ingredients are listed on the China Chemical Inventory.

#### 16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 1
Reactivity: 0

Revised Date: 8 SEPTEMBER 2016

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container. The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.