

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION(SUZHOU) ®

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH NC-SMQ92V FLUX VEHICLE

MSDS Number: MSDS-IN 650 Revised Date: 5 FEBRUARY 2010

Product Use: Industrial Use: No-clean solder paste consisting of a flux vehicle blended with an 83-92 % pre-

alloyed metal powder.

MANUFACTURER:

In America:

The Indium Corporation of America 1676 Lincoln Ave., Utica NY 13502 Information: (315) 853-4900 nswarts@indium.com

In Europe:

Indium Corporation of Europe 7 Newmarket Ct. Kingston, Milton Keynes, UK, MK 10 OAG

Information: +44 [0] 1908 580400

In Asia:

Asia-Pacific Operations-Singapore 29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: 1 (703) 527-3887

In China:

Indium Corporation (Suzhou), Co., Ltd. Suchun Industrial Square Property

Carcinogen listed in

#428 Xinglong Street

Building 14C

Suzhou Industrial Park Jiangsu, China 215021

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

XEve XInhalation XSkin XIngestion NTP IARC OSHA XNot Listed

GHS:





POTENTIAL HEALTH EFFECTS:

Eye Contact: Contact with material at room temperature or fume from material at typical re-flow temperatures

over 100°C may cause eye irritation.

Ingestion: This product may contain lead alloy powder and organic chemicals. Harmful if swallowed. May

cause systematic lead poisoning and burns to the digestive tract. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous

system, blood system and kidneys.

Inhalation: Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local

irritation to the respiratory system. When heated rosin may be a respiratory sensitizer.

Skin Contact: May cause mild skin irritation. Rosin may cause dermatitis.

Chronic: LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory

irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea,

abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.

SILVER: Chronic skin contact or ingestion of silver dust, salts, or fume can result in a condition

known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Has been shown to increase incidence of sarcoma in animal tests.

WARNING: This product contains a chemical known to the State of California to cause cancer and/or

birth defects (or other reproductive harm).

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its

products for human consumption.

WARNING: This product contains lead. Lead may be harmful to your health. US Federal law prohibits the

use of leaded solders in making joints or fittings in any private or public water supply system.

Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS						
Components	% wt	CAS Registry #/EINECS	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³	
TIN	*	7440-31-5/231-141-8				
		(US)	2	2	-	
		(EU)	-	2	4	
		(Canada)	-	2	4	
		(Singapore)	2	-	<u>-</u>	

MSDS - 650 INDALLOY WITH NC-SMQ92V

WODO - 000				INDALEOT WITH	
LEAD	*	7439-92-1/231-100-4			
		(US)	0.05	0.05	-
		(EU)	_	0.15	_
		(23)		0.10	
		(Canada)	0.05	0.05	-
		(Singapore)	0.15	-	-
		(Mexico)	N.E.	0.15	-
		(China)	-	0.05(dust) 0.03(fume)	-
ROSIN	3.0-4.0	65997-05-9 (US)	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15 (sensitiser)
PROPRIETARY	5.0-13.0		N.E.	N.E.	N.E.
Symbol: X _n		hrases: R20/21/22, R	36/37/38, R42	2/43, R33, R40, R4	8, R61
N.E. = Not established	* S	ee Alloy Table			

ALLOY TABLE

Metal mixed with Flux

Indalloy	%TIN	%LEAD	RoHS Compliance
106(Sn63)	52.3-58	30.7-34	No

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. Method: Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established.

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Firefighters must wear NIOSH approved self-contained breathing apparatus and full

Procedures: protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly

> cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose contaminated cloth rags or paper towels following all Federal, State and Local regulations. In the EU refer to the Special Waste

Regulations.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills. Use only with **Precautions:**

production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are

washed.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product

label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label. Consult Product Data Sheet for additional information.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use only with production equipment (stencil printers and re-flow furnaces) with

adequate ventilation and other safety features specifically designed for use

with solder paste. Control concentration of all components so that the exposure levels

are not exceeded. Avoid exposure to lead fumes.

Personal protection:

Chemical safety glasses/goggles. Eyes:

An authority approved or compliant marked air-purifying respirator with a fume/organic chemical Respirator:

cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or

exceed exposure limits.

Skin: Compatible chemical resistant gloves.

Lab coat, eyewash fountain in work area. Avoid the use of contact lenses in high fume Other:

Work/Hygienic

Maintain good housekeeping. Clean up spills immediately. DO NOT allow rags or Practices:

paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.

Wash hands thoroughly with soap and water immediately upon leaving the work area. Follow

applicable lead work practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Grey colored paste. **Boiling Point:** Not applicable. Mild characteristic odor. **Melting Point:** Not applicable Odor: Not applicable **Specific Gravity:** Not applicable. pH: **Vapor Pressure:** Not applicable. Solubility in Water: Insoluble (paste)

Vapor Density: (air=1) Not applicable.

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Not established.

Incompatible Materials: Avoid contact with acids, bases or oxidizing agents.

Will not occur.

Hazardous Decomposition / Harmful organic fumes and toxic oxide fumes may form at elevated

Combustion: temperatures.

11. TOXICOLOGY

Carcinogenicity: NTP: No

Hazardous Polymerization:

OSHA: No

IARC: Yes Lead and lead compounds are listed as possible carcinogens.

LD50: Not established. **LC50**: Not established.

Other: Chronic Toxicity: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational asthma. Lead can cause potential harm to the developing fetus.

12. ECOLOGICAL INFORMATION

This section is subject to future development. Product not tested.

Biodegradability: Data not established.

Aquatic Toxicity: Data not established.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for

recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations.

MSDS - 650 INDALLOY WITH NC-SMQ92V

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US Department of Transportation. Non hazardous material under shipping regulations.

15. REGULATORY INFORMATION

The information in this Material Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

The information in this Material Safety Data Sheet meets the requirements of the EU under Chemicals (Hazard Information and Packaging for Supply) Regulations 1994 (CHIP 2) Regulation 6.

This product has been classified in accordance with the hazard criteria of the Commission Directive 91/155/EEC and EH40.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic) (lead).

D2B Materials Causing Other Toxic Effects -irritant

This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with the Mexican Standards: NOM-010-STPS-1999 and NOM-018-STPS-2000.

This product has been classified under the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

For Compliance with EU Directive 2002/95/EC, Restriction of Hazardous Substances (RoHS) see Alloy Table.

California PROP 65: WARNING:

This product contains a chemical known to the State of California to cause cancer and/or birth defects (or other reproductive harm).

SARA 313 Listing - 40 CFR 372.65: Lead CAS# 7439-92-1, (Contains trace levels of ethylene oxide and 2, 4 dioxane).

EPA Genetic Toxicology Program – Lead CAS# 7439-92-1

All ingredients are listed on the EPA TSCA Inventory.

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

 X_n

Risk Phrases:

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed

R36/37/38 Irritating to eyes, respiratory system and skin

_		
	R42/43	May cause sensitization by inhalation and by skin contact
	R33	Danger of cumulative effects (lead)
	R40	Limited evidence of carcinogenic effect (lead)
	R48	Danger of serious damage to health by prolonged exposure (lead)
	R61	May cause harm to the unborn child (lead)
	Safety Phra	ases:
	S20/21	When using do not eat, drink or smoke
	S22	Do not breathe dust
	S23	Do not breathe fumes
	S24/25	Avoid contact with skin and eyes
	S28	After contact with skin wash immediately with plenty of soap and water
	S36/37/39	Wear suitable protective clothing, gloves and eye/face protection

16. OTHER INFORMATION

Revised Date:

S7

HMIS Hazard Rating: Health: 2

Keep container tightly closed

Fire: 1
Reactivity: 0
5 FEBRUARY 2010

Prepared by: Nancy Swarts, Indium Corporation of America
Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.