



SAFETY DATA SHEET

This safety data sheet represents a family grouping of all metal mixes that are blended with the same flux known as NC-SMQ 230. A table is provided that lists all metal groupings and their identification Unless otherwise stated the health and safety information provided within is applicable to all products.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH NC-SMQ230 FLUX VEHICLE

SDS Number: SDS-IN 640

Revised Date: 11 JUNE 2018

Product Use: Industrial Use - No-clean solder paste consisting of a flux vehicle blended with 83-92 weight percent pre-alloyed metal powder. See alloy table of metal mixture combinations. An alloy table is provided for all metal mix combinations with the same flux. Review alloy table.

MANUFACTURER:

In America:

The Indium Corporation of America®.

34 Robinson Rd., Clinton, NY 13323

Information: (315) 853-4900

nswarts@indium.com

In Europe:

The Indium Corporation of America® (European Operations)

7 Newmarket Ct

Kingston, Milton Keynes, UK, MK 10 OAG

Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America

Asia-Pacific Operations-Singapore

29 Kian Teck Avenue

Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

CHEMTREC 24 hrs.

USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou), Co., Ltd.

No. 428 Xinglong Street

Suzhou Industrial Park

Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126

Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

GHS:

Lead free products



Signal Word: Warning

Hazard statement(s)

H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
EUH208	Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233	Keep container tightly closed
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P362 + P364	Take off contaminated clothing and wash before reuse
P301 + P314	IF SWALLOWED: Get Medical advice/attention if you feel unwell
P302 + P352	IF ON SKIN: Wash with plenty of soap and water
P304 + 341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + 351	IF IN EYES: Rinse continuously with water for several minutes (15 mins)
P501	Dispose of content/containers in accordance with applicable regulations.

Lead containing products



Signal Word: Warning

Hazard statement(s)

H303	May be harmful if swallowed
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects
EUH201A	Warning! Contains lead. Review listing.
EUH208	Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233	Keep container tightly closed
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P362 + P364	Take off contaminated clothing and wash before reuse
P301 + P314	IF SWALLOWED: Get Medical advice/attention if you feel unwell
P302 + P352	IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)
 P501 Dispose of content/containers in accordance with applicable regulations.

Classification

Eye irritation-Category 2A
 Skin irritation-Category 3
 Carcinogenicity (Category 2) (lead)
 Reproductive toxicity (Category 2) (lead)
 Acute aquatic toxicity – Category 1 for lead containing products
 Chronic aquatic toxicity – Category 1 for lead containing products

PRIMARY ROUTES OF ENTRY:

Eye Inhalation Skin Ingestion NTP IARC OSHA Not Listed

Carcinogen listed in

POTENTIAL HEALTH EFFECTS:

- Eye Contact:** Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause eye irritation.
- Ingestion:** This product contains alloy powder and organic chemicals. May cause irritation or harm.
- Inhalation:** Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to the respiratory system. May be harmful if inhaled.
- Skin Contact:** May cause skin irritation. ANTIMONY and COBALT has been known to cause dermatitis.
- Chronic:** SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.
- LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.
- TIN: Has been shown to increase incidence of sarcoma in animal tests.
- COPPER: Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.
- BISMUTH: May cause kidney damage.
- COBALT: Inhalation of dust may cause pulmonary damage. Animal carcinogen and suspected human carcinogen.
- IRON: Inhalation of large amounts of iron dust may result in iron pneumoconiosis. Chronic exposure to high levels on a daily basis can result in iron being deposited in body tissues and may result in liver cirrhosis and pancreas problems.
- MANGANESE : Inhalation may cause metal fume fever and/or asthma.



WARNING: This product can expose you to chemicals including [lead] which is known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

WARNING: This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making joints or fittings in any private or public water supply system. Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #/ EINECS#	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
TIN	*	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
		(Singapore)	2	-	-
SILVER	*	7440-22-4/231-131-3			
		(US)	0.01	0.1	-
		(EU)	-	0.1	-
		(Canada)	-	0.1	0.3
		(Mexico)	-	0.1	-
		(Singapore)	0.1	-	-
COPPER	*	7440-50-8 (US)	0.1 (fume)	0.2 (fume)	-
		(EU)	-	0.2 (fume)	-
		(Canada)	-	0.2 (fume)	0.6 (fume)
		(Mexico)	-	0.2(fume)	2
		(Singapore)	0.2	-	-
		(China)	-	1(dust)	2.5
				0.2(fume)	0.6
BISMUTH	*	7440-69-9/231-177-4	N.E.	N.E.	N.E.
ANTIMONY	*	7440-36-0/231-146-5			
		(US)	0.5	0.5	-
		(EU)	0.5	-	-
		(Canada)	-	0.5	1.5
		(Mexico)	-	0.5	-

		(Singapore)	0.5	-	-
		(China)	-	0.5	-
COBALT	<1	7440-48-4/231-158-0			
		(US)	0.1	0.02	-
		(EU)	0.1	-	-
		(Canada)	-	0.05	0.1
		(Singapore)	0.02	-	-
IRON	<1	7439-89-6/ 231-096-4	N.E.	N.E.	N.E.
LEAD	*	7439-92-1/231-100-4			
		(US)	0.05	0.05	-
		(EU)	-	0.15	-
		(Canada)	-	0.05	-
		(Mexico)	N.E.	0.15	N.E.
		(Singapore)	0.15	-	-
		(China)	-	0.05(dust) 0.03(fume)	- -
MANGANESE	<1	7439-96-5	5(ceiling)	0.2	3 (fume)
		(EU)	-	1(fume)	3(fume)
		(Canada)	-	1(fume)	3(fume)
		(Singapore)	5(dust)	1(fume)	-
		(Mexico)	1(fume)	0.2	-
		(China)	-	0.15	-
ROSIN	3.0-6.0	65997-05-9 (US)	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15 (sensitiser)
PROPRIETARY	5-11		N.E.	N.E.	N.E.

TWA = TIME WEIGHTED AVERAGE STEL = SHORT TERM EXPOSURE LIMIT

N.E. = Not established * See alloy table

4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. **Method:** Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established.

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Procedures: Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose contaminated cloth rags or paper towels following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

7. HANDLING AND STORAGE

Handling Precautions: Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use only with production equipment (stencil printers and re-flow furnaces) with adequate ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components so that the (exposure limits) are not exceeded.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.

Skin: Compatible chemical resistant gloves. Latex gloves not recommended

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately. DO NOT allow rags or

Practices: paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.
Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Grey colored paste.	Boiling Point:	Not applicable.
Odor:	Mild characteristic odor.	Melting Point:	Not applicable
Specific Gravity:	Not applicable.	pH:	Not applicable
Vapor Pressure:	Not applicable.	Solubility in Water:	Insoluble (paste)
Vapor Density:	(air=1) Not applicable.	Volatile Organic Compounds:	<11,260 ug/KG

10. STABILITY AND REACTIVITY

General:	Stable.
Conditions to Avoid:	Not established.
Incompatible Materials:	Avoid contact with acids, bases or oxidizing agents.
Hazardous Decomposition / Combustion:	Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity:	NTP: No	
	OSHA: No (29CFR 1910.1025 Lead)	
	IARC: Yes - Lead	
LD50:	Not established.	LC50: Not established.

Other: Chronic Toxicity: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational asthma. Lead may cause potential harm to the developing fetus.

12. ECOLOGICAL INFORMATION

Product not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements. Not regulated under US DOT (United States Department of Transportation).

Non - hazardous under all shipping requirements, all modes.

North American Emergency Guide Book – Not Classified

UN – none.

Marine pollutant: No

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).



WARNING: This product can expose you to chemicals including [lead] which is known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

SARA 313 Listing - 40 CFR 372.65

Silver	Copper	Antimony
Cobalt	Lead	Manganese

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS:

D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic) (lead).
D2B Materials Causing Other Toxic Effects –irritant

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with the Mexican guidelines, NOM-018-STPS-2015 and NOM-010-STPS-2014.

For compliance with EU Directive 2011/65/EU, Restriction of Hazardous Substances (RoHS), see Alloy Table.

Japan:

Poisonous and Deleterious Substance Control Law (PDSCL): No ingredients are listed.

Fire Service Law (FSL): Not regulated/not dangerous.

Industrial Safety and Health Law (ISHL): ingredients are listed

PRTR and Promotion of Chemical Management law, Class I Substance: Not applicable.

Waste Disposal and Public Cleaning Law: Specific Harmful Industrial Wastes: Some contents of the family grouping may contain lead within the solder paste. Review alloy table and product label/ purchased and used.

Class II Designated Chemical Substances: No ingredients are listed.

Ingredients are listed on the Japanese Inventory Chemical Substance List/Industrial Safety and Health Law Substance List.

Review SDS and apply regulations where applicable.

Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS). (GHS)

In China:

Decree No. 591: Regulations on the Control over Safety of Hazardous Chemicals

GB 30000.2-29-2013, Rules for classification and labeling of chemicals. (GHS)

GB/T 16483-2008, GB/T 17517-2013

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007.

All ingredients are listed on the China Chemical Inventory.

16. OTHER INFORMATION

HMIS Hazard Rating:	Health:	2
	Fire:	1
	Physical Hazard:	0

Revised Date: 11 JUNE 2018

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

ALLOY TABLE**% Metal Content Blended with Flux**

INDALLOY MIXTURE (%Metal)	TIN Sn	LEAD Pb	COPPER Cu	SILVER Ag	BISMUTH Bi	IRON Fe	COBALT Co	MANGANESE Mn	ANTIMONY Sb	RoHS 2/3*
97 (Sn43/Pb43 /Bi14)	35.7-39.6	35.7-39.6	-	-	11.6-12.9	-	-	-	-	NO
121 (Sn96.5/Ag 3.5)	80.1-88.8	-	-	2.9-3.2	-	-	-	-	-	YES
128 (Sn100)	83-92	-	-	-	-	-	-	-	-	YES
132 (Sn95/Ag5)	78.9-87.4	-	-	4.2-4.6	-	-	-	-	-	YES
133 (Sn95/Sb5)	78.9-87.4	-	-	-	-	-	-	-	4.2-4.6	YES
156 (Sn90/Ag10)	74.7-82.8	-	-	8.3-9.2	-	-	-	-	-	YES
160 (Sn97/Cu3)	80.5-89.2	-	2.5-2.8	-	-	-	-	-	-	YES
209 (Sn65/Ag25 /Sb10)	54.0-59.8	-	-	20.8-23.0	-	-	-	-	8.3-9.2	YES
232 (Sn93.6/Ag 4.7/Cu1.7)	77.7-86.1	-	1.4-1.6	3.9-4.3	-	-	-	-	-	YES
241 (SAC387) (Sn95.5/Ag 3.8/Cu0.7)	79.3-87.9	-	0.6-0.7	3.2-3.5	-	-	-	-	-	YES
243 (Sn99/Cu1)	82.2-91.1	-	0.83-0.92	-	-	-	-	-	-	YES

INDALLOY MIXTURE (%Metal)	TIN Sn	LEAD Pb	COPPER Cu	SILVER Ag	BISMUTH Bi	IRON Fe	COBALT Co	Manganese Mn	ANTIMONY Sb	RoHS 2/3*
244 (Sn99.3/Cu 0.7)	82.4-91.4	-	.58-.64	-	-	-	-	-	-	YES
246 (Sn95.5/Ag 4/Cu0.5)	79.3-87.9	-	0.42-0.46	3.3-3.7	-	-	-	-	-	YES
249 (Sn91.8/Bi 4.8/Ag3.4)	76.2-84.5	-	-	2.8-3.1	4.0-4.4	-	-	-	-	YES
252 (Sn95.5/Ag 3.9/Cu0.6)	79.3-87.9	-	0.50-0.55	3.2-3.6	-	-	-	-	-	YES
256 (SAC305) (Sn96.5/Ag 3/Cu0.5)	80.1-88.8	-	0.41-0.46	2.5-2.8	-	-	-	-	-	YES
281 (Sn60/Bi40)	34.9-38.6	-	-	-	48.1-53.4	-	-	-	-	YES
NS (98.3Sn/1A g/0.5Cu/0.2 Mn)	81.5-90	-	0.42-0.46	0.83-0.92	-	-	-	0.17-0.18	-	YES
NS (95.8Sn/3.7 Ag/0.5Cu)	79.5-88	-	0.4 – 0.46	3.1-3.4	-	-	-	-	-	YES
NS (95.5Sn/3.6 Ag/0.9Cu)	79.3-87.9	-	0.75-0.83	3-3.3	-	-	-	-	-	YES
NS (96Sn/3.7A g/0.3Cu)	79.7-88.3	-	0.25-0.28	3.1-3.4	-	-	-	-	-	YES

INDALLOY MIXTURE (%Metal)	TIN Sn	LEAD Pb	COPPER Cu	SILVER Ag	BISMUTH Bi	IRON Fe	COBALT Co	Manganese Mn	ANTIMONY Sb	RoHS 2/3*
NS (95.4Sn/3.7 Ag/0.9Cu)	79.2-87.8	-	0.75-0.83	3.1-3.4	-	-	-	-	-	YES
NS (95.4Sn/0.7 Cu/3.7Ag/0. 2Fe)	79.2-87.8	-	0.58-0.64	3.1-3.4	-	0.17-0.18	-	-	-	YES
NS (95.4Sn/0.6 Cu/3.7Ag/0. 3Co)	79.2-87.8	-	0.50-0.55	3.1-3.4	-	-	0.25-0.28	-	-	YES
NS (94.5Sn/4.1 Ag/1.4Cu)	78.4-86.9	-	1.2-1.3	3.4-3.8	-	-	-	-	-	YES
NS (96Sn/4Ag)	79.7-88.3	-	-	3.3-3.7	-	-	-	-	-	YES
NS (95Sn/4Ag/ 1Sb)	78.9-85.5	-	-	3.3-3.7	-	-	-	-	0.83-0.92	YES
NS (94Sn/4Ag/ 1Cu/1Sb)	78.0-86.5	-	0.83-0.92	3.3-3.7	-	-	-	-	0.83-0.92	YES
NS (92Sn/1.7C u/4.7Ag/1.5 Sb)	76.4-84.7	-	1.4-1.6	3.9-4.3	-	-	-	-	1.2-1.4	YES

NS = Non - standard alloy mixture

***RoHS 2 = Restriction of Hazardous Substances (2011/65/EU)**

***RoHS 3- products do not contain any listed phthalates**