



SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: 1096 NF

SDS Number: SDS-4094

Revised Date: 22 JUNE 2018

Product Use: INDUSTRIAL USE-WATER SOLUBLE WAVE FLUX

MANUFACTURER:

The Indium Corporation of America®
34 Robinson Rd., Clinton, New York 13323
Information: (315) 853-4900
NSWARTS@INDIUM.COM

CHEMTREC 24 hrs.
USA: 1 (800) 424-9300
Outside USA: +1 (703) 527-3887

In Europe:

Indium Corporation of America ® (European Operations)
7 Newmarket Ct.
Kingston, Milton Keynes, UK, MK 10 OAG
Information: +44 [0] 1908 580400

In China:

Indium Corporation (Suzhou) Co., Ltd
No. 428 Xinglong Street
Suzhou Industrial Park
Suchun Industrial Square
Unit No. 14-C
Jiangsu Province, China 215126
Information: (86) 512-6283-4900

In Asia:

Indium Corporation of America
Asia-Pacific Operations-Singapore
29 Kian Teck Avenue
Singapore 628908
Information: +65 6268-8678

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Eye
 Inhalation
 Skin
 Ingestion
 NTP
 IARC
 OSHA
 Not Listed

Carcinogen listed in

GHS



Signal Word: Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking
 P233 Keep container tightly closed
 P240 Ground/Bond container and receiving equipment
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P270 Do not eat, drink or smoke when using this product
 P273 Avoid release to the environment
 P280 Wear protective gloves/protective clothing/eye protection/face protection
 P362 +P364 Take off contaminated clothing and wash before reuse
 P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell
 P302 +P352 IF ON SKIN: Wash with plenty of soap and water
 P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification:

Flammable Liquid – Category 2

Eye irritation – Category 2A

Specific target organ toxicity- single exposure – Category 3- central nervous system

POTENTIAL HEALTH EFFECTS:

Eye Contact: Vapors may be irritating, liquid may damage eye tissue.

Ingestion: May cause persistent nausea, vomiting and abdominal pain. May cause irritation.

Inhalation: Vapor may cause headaches and or dizziness. May cause irritation.

Skin Contact: Prolonged contact may cause irritation.

Chronic: Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.



WARNING: This product can expose you to chemicals including [trace amounts of 1,4 dioxane, propylene oxide, ethylene oxide] which are known to the State of California to cause cancer and [trace amounts of ethylene oxide] which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
ISOPROPANOL	<80	67-63-0 (US)	980	983	1225
PROPAN-2-OL		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Singapore)	983	-	1230
		(Mexico)	-	980	1225
		(China)	-	350	700
SURFACTANT	<20	-	N.E.	N.E.	N.E.

N.E. = Not established EU = European Exposure Limits

4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

- Flash Point:** 54°F **Method:** Closed Cup
- Auto-ignition Temperature:** 750 F
- Flammable Limits:** Upper: 12 ; Lower 2.0
- Extinguishing Media:** Dry chemical, Water or CO₂. Use extinguishers appropriate for the surrounding fire conditions.
- Special Fire Fighting Procedures:** Wear protective clothing and self-contained breathing apparatus. Use water to cool fire exposed containers. Flammable vapors may travel great distances to ignition source and flash back.

6. ACCIDENTAL RELEASE MEASURES

- Spill or Leak Procedures:** DO NOT allow material to enter sewer system or waterway. Wear personal protective equipment. Eliminate sources of ignition. Ventilate area in accordance with regulations. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

7. HANDLING AND STORAGE

Handling Precautions: Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal protective equipment.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation recommended.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: A NIOSH approved or EU compliant CE marked air-purifying respirator with a fume/organic chemical cartridge is recommended where airborne concentrations are expected to be elevated.

Skin: Compatible chemical resistant gloves. Use gloves such as nitrile, which are compatible with alcohols and lower pH chemicals.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Practices: Maintain good housekeeping. Clean up spills immediately.

Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Amber	Boiling Point:	180 F
Odor:	Alcohol odor.	Evaporation Rate:	>1.5
Specific Gravity:	0.835 @60F	pH:	7
Vapor Pressure:	31 mm HG @ 68F	Solubility in Water:	Soluble
Vapor Density:	>1 (air=1)	% Volatiles by volume:	90

10. STABILITY AND REACTIVITY

General:	Stable.
Conditions to Avoid:	Direct heat, open flames and storage in aluminum.
Incompatible Materials:	Anhydrides, halogens, phosphorus, trichlorides, monomers, aldehydes
Hazardous Decomposition / Combustion:	Carbon dioxide/carbon monoxide.
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity:	National Toxicity Program NTP:	No
	Occupational Safety & Health Administration OSHA:	No
	International Agency for Research on Cancer IARC:	No
LD50:	Not established.	LC50: Not established.

12. ECOLOGICAL INFORMATION

Product not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

Shipping: UN 1219, Isopropanol, 3, PG II



North America Emergency Guide Book – Guide #129

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

WHMIS: Class B2 Flammable Liquid

This product has been classified in accordance with the guidelines, as set, by the Dept of Industrial Health of the Republic of Singapore.

SARA 313 Listing - 40 CFR 372.65: None

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified under the Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

In China:

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007.

Decree No. 591: Regulations on the Control over Safety of Hazardous Chemicals

GB 30000.2-29-2013, Rules for classification and labeling of chemicals. (GHS)

GB/T 16483-2008, GB/T 17517-2013



WARNING: This product can expose you to chemicals including [trace amounts of 1,4 dioxane, propylene oxide, ethylene oxide] which are known to the State of California to cause cancer and [trace amounts of ethylene oxide] which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

16. OTHER INFORMATION

HMIS Hazard Rating:	Health:	2
	Fire:	3
	Reactivity:	0

Revised Date: 22 JUNE 2018

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.