



INDIUM CORPORATION OF AMERICA®\EUROPE®\ASIA-PACIFIC®
INDIUM CORPORATION (SUZHOU)®

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: 2205 ROSIN FLUX

SDS Number: SDS-4511

Revised Date: 11 MAY 2015

Product Use: INDUSTRIAL USE - WAVE FLUX

MANUFACTURER:

In America:

The Indium Corporation of America
 1676 Lincoln Ave., Utica NY 13502
 Information: (315) 853-4900
nswarts@indium.com

EMERGENCY PHONE:

CHEMTREC 24 hrs.
USA: 1 (800) 424-9300
Outside USA: +1 (703) 527-3887

Indium Corporation of America
 Chicago Materials Division
 80 Scott St
 Elk Grove Village, Illinois 60007

In Europe:

Indium Corporation of Europe
 7 Newmarket Ct.
 Kingston, Milton Keynes, UK, MK 10 OAG
 Information: +44 [0] 1908 580400

In China:

Indium Corporation (Suzhou) Co., Ltd
 No. 428 Xinglong Street
 Suzhou Industrial Park
 Suchun Industrial Square
 Unit No. 14-C
 Jiangsu Province, China 215126
 Information: (86) 512-6283-4900

In Asia:

Indium Corporation of America
 Asia-Pacific Operations-Singapore
 29 Kian Teck Avenue
 Singapore 628908
 Information: +65 6268-8678

2. HAZARDS IDENTIFICATION

GHS:



Signal Word: Danger

Hazard Statements:

- H225 Highly Flammable liquid and vapor
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H336 May cause drowsiness or dizziness

Precautionary statement(s)

- P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking
- P233 Keep container tightly closed
- P240 Ground container and receiving equipment
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P270 Do not eat, drink or smoke when using this product
- P273 Avoid release to the environment
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P362 +P364 Take off contaminated clothing and wash before reuse
- P301 +P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell.
- P302 +P352 IF ON SKIN: Wash with plenty of soap and water
- P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305 + P351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification – isopropyl alcohol

Eye irritant – (Category 2A)

Flammable liquids - (Category 2)

Skin irritation- (Category 3)

Specific target organ systemic toxicity (single exposure) – (Category 3), Central nervous system

PRIMARY ROUTES OF ENTRY:

- Eye
 Inhalation
 Skin
 Ingestion
 NTP
 IARC
 OSHA
 Not Listed

Carcinogen listed in

POTENTIAL HEALTH EFFECTS:

Eye Contact: Vapors may be irritating, liquid may damage eye tissue.

Ingestion: May cause persistent nausea, vomiting and abdominal pain. May cause irritation.

Inhalation: Vapor may cause headaches and or dizziness. Rosin may cause irritation or occupational asthma.

Skin Contact: Prolonged contact may cause irritation and dermatitis.

Chronic: Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its

products for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
ISOPROPANOL (PROPAN-2-OL)	72-77	67-63-0 (US)	980	983	1225
		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Mexico)	980	-	1225
		(Singapore)	983	-	1230
		(China)	-	350	700
PROPRIETARY ACTIVATORS 1-5.0		-	N.E.	N.E.	N.E.
ROSIN	23-27	65997-05-9 (US)	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15 (sensitiser)

Symbol: XI, F
N.E. = Not established

Risk Phrases: R36/37/38, R11, R42/43
EU = European Exposure Limits

4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

- Flash Point:** 12°C (54°F) **Method:** Closed Cup
- Auto-ignition Temperature:** N/A
- Flammable Limits:** Upper: 12 @77°F; Lower 2 @ 77°F
- Extinguishing Media:** Dry chemical, Water or CO₂. Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting

Procedures: Wear protective clothing and self - contained breathing apparatus. Use water to cool fire exposed containers. Flammable vapors may travel great distances to ignition source and flash back.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Do not allow chemical material to enter sewer system or waterway. Wear personal protective equipment. Eliminate sources of ignition. Ventilate area in accordance with regulations. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

7. HANDLING AND STORAGE

Handling Precautions: Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal protective equipment. Ground containers. Ventilated area.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation recommended to keep exposures as low as possible. Recommend personal protective equipment, if ventilation equipment is not available or is not adequate.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An authority approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended where airborne concentrations are expected to be elevated.

Skin: Compatible chemical resistant gloves. Use gloves such as nitrile, which are compatible with alcohols.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Practices: Maintain good housekeeping. Clean up spills immediately.

Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colorless	Boiling Point:	81°C (177°F)
Odor:	Alcohol odor.	Evaporation Rate:	1.7
Specific Gravity:	0.808 @ 60° F	pH:	Neutral
Vapor Pressure:	33 mm HG @68 F	Solubility in Water:	Soluble
Vapor Density:	2.1 (air=1)	% Volatiles by volume:	100

10. STABILITY AND REACTIVITY

General:	Stable.
Conditions to Avoid:	Direct heat, open flames and storage in aluminum.
Incompatible Materials:	Anhydrides, halogens, phosphorus, trichlorides, monomers, aldehydes
Hazardous Decomposition / Combustion:	Carbon dioxide/carbon monoxide.
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity:	National Toxicity Program NTP:	No
	Occupational Safety & Health Administration OSHA:	No
	International Agency for Research on Cancer IARC:	No
LD50:	Not established.	LC50: Not established.
Oral LD50 (isopropyl alcohol)		
LD50 Oral- rat- 5,045 mg/kg		
Inhalation LC50 (isopropyl alcohol)		
LC50 inhalation-rat-8h-16000 ppm		
Dermal LD50		
LD50 – Dermal- rabbit-12,800 mg/kg		

12. ECOLOGICAL INFORMATION

Product not tested.

LC50-Pimephales promelas (fathead minnow)- 9,640 mg/l – 96h (isopropyl alcohol)

EC50-Daphnia magna (water flea) – 5,102 mg/l – 24h (isopropyl alcohol)

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local environmental regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.



UN1219, Isopropanol, 3, PG II

North America Emergency Guide Book – Guide #129

MARINE POLLUTANT: NO

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS: Class B2 Flammable Liquid, D2B Toxic material causing other toxic effects (eye irritation in animals)



This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with Mexican regulations: NOM-018-STPS-2000 and NOM-010-STPS-1999.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

SARA 313 Listing - 40 CFR 372.65: None

All ingredients are listed on the EPA TSCA Inventory.

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

XI, F

Risk Phrases:

R36/37/38 Irritating to eyes, respiratory system and skin
 R 11 Highly Flammable
 R42/43 May cause sensitization by inhalation and skin contact
 R67 Vapors may cause drowsiness and dizziness

Safety Phrases:

S16 Keep away from sources of ignition - "No Smoking"
 S20/21 When using do not eat, drink or smoke
 S23 Do not breathe fumes
 S24/25 Avoid contact with skin and eyes
 S28 After contact with skin wash immediately with plenty of soap and water
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection
 S62 If swallowed, do not induce vomiting seek medical advice immediately and show container or label
 S7 Keep container tightly closed

16. OTHER INFORMATION

HMIS Hazard Rating: **Health:** 1
 Fire: 3
 Reactivity: 0

Revised Date: 11 MAY 2015

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.