



This safety data sheet represents a family grouping of all metal mixes that are blended with the same flux. A table is provided that lists all metal groupings. To better serve all of our customers Indium Corporation has generated one SDS, for this product, to be used within the United States as well as internationally. Some of the regulatory information contained within may not be applicable to the customer's individual state or country. Unless otherwise stated the health and safety information provided within is applicable to all products.

## SAFETY DATA SHEET

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** INDALLOY WITH SR-6 FLUX VEHICLE

**SDS Number:** SDS- 5044

**Revised Date:** 25 SEPTEMBER 2018

**Product Use:** Industrial Use - No-clean solder paste consisting of a flux vehicle blended with a pre-alloyed metal powder.

#### MANUFACTURER:

##### In America:

The Indium Corporation of America®.  
34 Robinson Rd., Clinton, NY 13323  
Information: (315) 853-4900  
[nswarts@indium.com](mailto:nswarts@indium.com)

##### EMERGENCY PHONE:

**CHEMTREC 24 hrs.**  
**USA: 1 (800) 424-9300**  
**Outside USA: +1 (703) 527-3887**  
**In China: Emergency 86+ 4008417580**

##### In Europe:

The Indium Corporation of America® (European Operations)  
7 Newmarket Ct.  
Kingston, Milton Keynes, UK, MK 10 OAG  
Information: +44 [0] 1908 580400

##### In China:

Indium Corporation (Suzhou), Co., Ltd.  
No. 428 Xinglong Street  
Suzhou Industrial Park  
Suchun Industrial Square  
Unit No. 14-C  
Jiangsu Province, China 215126  
Information: (86) 512-6283-4900

##### In Asia:

The Indium Corporation of America  
Asia-Pacific Operations-Singapore  
29 Kian Teck Avenue  
Singapore 628908  
Information: +65 6268-8678

## 2. HAZARDS IDENTIFICATION

### PRIMARY ROUTES OF ENTRY:

⊕Eye    ⊕Inhalation    ⊕Skin    ⊕Ingestion    NTP

### Carcinogen listed in

IARC    OSHA    ⊕Not Listed  
\*See Section 11

### GHS:

#### Lead free products



Signal Word: Warning

#### Hazard statement(s)

H317            May cause an allergic skin reaction  
H319            Causes serious eye irritation  
H334            May cause allergy or asthma symptoms or breathing difficulties if inhaled  
EUH208        Contains rosin. May produce an allergic reaction

#### Precautionary statement(s)

P233            Keep container tightly closed  
P261            Avoid breathing dust/fume/gas/mist/vapors/spray  
P270            Do not eat, drink or smoke when using this product  
P273            Avoid release to the environment  
P280            Wear protective gloves/protective clothing/eye protection/face protection  
P362 +P364    Take off contaminated clothing and wash before reuse  
P301 + P314    IF SWALLOWED: Get medical attention/advice if you feel unwell  
P302 +P352    IF ON SKIN: Wash with plenty of soap and water  
P304 + 341    IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305 + 351    IF IN EYES: Rinse continuously with water for several minutes (15 mins)

#### Lead containing products



Signal Word: Warning

#### Hazard statement(s)

H303            May be harmful if swallowed  
H317            May cause an allergic skin reaction  
H319            Causes serious eye irritation  
H334            May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H335            May cause respiratory irritation  
H332            Harmful if inhaled  
H351            Suspected of causing cancer  
H361            Suspected of damaging fertility or the unborn child  
H373            May cause damage to organs through prolonged or repeated exposure  
H410            Very toxic to aquatic life with long lasting harmful effects  
EUH201A        Warning! Contains lead. Review listing.  
EUH208        Contains rosin. May produce an allergic reaction

#### Precautionary statement(s)

P233            Keep container tightly closed  
P261            Avoid breathing dust/fume/gas/mist/vapors/spray  
P270            Do not eat, drink or smoke when using this product

P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P362 +P364	Take off contaminated clothing and wash before reuse
P301 + P314	IF SWALLOWED: Get medical attention/advice if you feel unwell
P302 +P352	IF ON SKIN: Wash with plenty of soap and water
P304 + 341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + 351	IF IN EYES: Rinse continuously with water for several minutes (15 mins)

-----

**Classification:**

Specific target organ toxicity- repeated exposure – Category 2  
 Carcinogenicity (Category 2) (lead)  
 Reproductive toxicity (Category 2 ) (lead)  
 Acute aquatic toxicity – Category 1 for lead containing products  
 Chronic aquatic toxicity – Category 1 for lead containing products  
 Respiratory sensitizer (Category 1B)  
 Skin sensitizer (Category 1B)  
 Eye irritant (Category 2A)

**POTENTIAL HEALTH EFFECTS:**

**Eye Contact:** Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause eye irritation.

**Ingestion:** This product contains alloy powder and organic chemicals. May be harmful if swallowed.

**Inhalation:** Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to the respiratory system. Rosin exposure may cause occupational asthma.

**Skin Contact:** May cause skin irritation. Rosin may cause dermatitis.

**Chronic:** LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.

SILVER: Chronic skin contact or ingestion of silver dust, salts, or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Has been shown to increase incidence of sarcoma in animal tests.

BISMUTH: May cause kidney damage.

INDIUM: May cause damage to respiratory system.



**WARNING:** This product can expose you to chemicals including [lead] which is known to the State of California to cause cancer, and can cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**NOTE:** The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

**Warning:** This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making joints or fittings in any private or public water supply system. Keep out of the reach of children.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Components</b>	<b>% wt</b>	<b>CAS Registry #/EINECS#</b>	<b>PEL mg/m<sup>3</sup></b>	<b>TLV-TWA mg/m<sup>3</sup></b>	<b>TLV-STEL mg/m<sup>3</sup></b>
<b>TIN</b>	*	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
		(Singapore)	2	-	-
<b>LEAD</b>	*	7439-92-1/231-100-4			
		(US)	0.05	0.05	-
		(EU)	-	0.15	-
		(Canada)	0.05	0.05	-
		(Mexico)	0.15	-	-
		(Singapore)	0.15	-	-
		(China)	-	0.05(dust) 0.03(fume)	- -
<b>SILVER</b>	*	7440-22-4/231-131-3			
		(US)	0.01	0.1	-
		(EU)	-	0.1	-
		(Canada)	-	0.1	0.3
		(Mexico)	0.1	-	-
		(Singapore)	0.1	-	-
<b>INDIUM</b>	*	7440-74-8/231-180-0			
		(US)	0.1	0.1	-
		(EU)	-	0.1	0.3
		(Canada)	-	0.1	0.3
		(Mexico)	0.1	-	0.3
		(Singapore)	0.1	-	-
		(China)	-	0.1	0.3
<b>BISMUTH</b>	*	7440-69-9/231-177-4	N.E.	N.E.	N.E.
<b>ROSIN</b>	4.0-5.0	8052-10-6	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15 (sensitiser)

**PROPRIETARY**                      3.0-13.0                      -                      N.E.                      N.E.                      N.E.

N.E. = Not established                      EU = European Union Occupational Exposure Limits

## ALLOY TABLE

### % Metal mix with flux

Indalloy (metal)	RoHS 2/3 Compliance*	%TIN Sn	%SILVER Ag	%LEAD Pb	%BISMUTH Bi	%INDIUM In
<b>1</b> (50In/50Sn)	Yes	41.5-46.0	-	-	-	41.5-46.0
<b>1E</b> (52In/48Sn)	Yes	39.8-44.2	-	-	-	43.2-47.8
<b>2</b> (80In/15Pb/5Ag)	No	-	4.2-4.6	12.5-13.8	-	66.4-73.6
<b>3</b> (90In/10Ag)	Yes	-	8.3-9.2	-	-	74.7-82.8
<b>4</b> (100In)	Yes	-	-	-	-	83.0-92.0
<b>5</b> (37.5Pb/37.5Sn/ 25In)	No	31.1-34.5	-	31.1-34.5	-	20.8-23.0
<b>7</b> (50In/50Pb)	No	-	-	41.5-46.0	-	41.5-46.0
<b>9</b> (70Sn/18Pb/12In )	No	58.1-64.4	-	14.9-16.6	-	10.0-11.0
<b>10</b> (75Pb/25In)	No	-	-	62.3-69.0	-	20.8-23.0
<b>11</b> (95Pb/5In)	Yes	-	-	78.9-87.4	-	4.2-4.6
<b>40</b> (50Bi/31Pb/19Sn )	No	15.8-17.5	-	25.7-28.5	41.5-46.0	-
<b>42</b> (46Bi/34Sn/20Pb )	No	28.0-31.3	-	17.0-18.4	38.0-42.3	-
<b>53</b> (67Bi/33In)	Yes	-	-	-	54.9-61.6	27.1-30.4
<b>70</b> (40In/40Sn/20Pb )	No	32.8-36.8	-	16.4-18.4	-	32.8-36.8
<b>97</b> (43Sn/43Pb/14Bi )	No	36.7-39.6	-	36.7-39.6	11.6-12.9	-
<b>150</b> (81Pb/19In)	No	-	-	67.2-74.5	-	15.8-17.5

Indalloy (metal)	RoHS 2/3 Compliance*	%TIN Sn	%SILVER Ag	%LEAD Pb	%BISMUTH Bi	%INDIUM In
<b>164</b> (92.5Pb/5In/2.5Ag)	Yes	-	2.1-2.3	76.8-85.1	-	4.2-4.6
<b>174</b> (57Bi/26In/17Sn)	Yes	14.1-15.6	-	-	47.3-52.4	21.6-23.9
<b>204</b> (70In/30Pb)	No	-	-	24.9-27.6	-	58.1-64.4
<b>205</b> (60In/40Pb)	no	-	-	33.2-36.8	-	49.8-55.2
<b>206</b> (60Pb/40In)	No	-	-	49.8-55.2	-	33.2-36.8
<b>227</b> (77.2Sn/20In/2.8Ag)	Yes	64.1-71.0	2.3-2.6	-	-	16.6-18.4
<b>230</b> (54Sn/26Pb/20In)	No	44.8-49.7	-	21.6-23.9	-	16.6-18.4
<b>249</b> (91.8Sn/4.8Bi/3.4Ag)	Yes	76.2-84.5	2.8-3.1	-	4.0-4.4	-
<b>254</b> (86.9Sn/10In/3.1Ag)	Yes	72.1-79.9	2.6-2.9	-	-	8.3-9.2
<b>281</b> (58Bi/42Sn)	Yes	34.9-38.6	-	-	48.1-53.4	-
<b>290</b> (97In/3Ag)	Yes	-	2.5-2.8	-	-	80.5-89.2
NON STANDARD ALLOY (88Sn/10In/2Ag)	Yes	73-81	1.7-1.8	-	-	8.3-9.2

\*RoHS 2 = Restriction of Hazardous Substances (review applicable exemption) (2011/65/EU)

RoHS 3 = products do not contain any listed phthalates

#### 4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

## 5. FIRE FIGHTING MEASURES

<b>Flash Point:</b>	Not flammable rated >200F ( >93C)
<b>Auto-ignition Temperature:</b>	Not established.
<b>Flammable Limits:</b>	NA
<b>Extinguishing Media:</b>	Use extinguishers appropriate for the surrounding fire conditions.
<b>Special Fire Fighting Procedures:</b>	Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Spill or Leak Procedures:</b>	Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose of contaminated cloth rags or paper towels following all Federal, State and Local regulations.
----------------------------------	--

## 7. HANDLING AND STORAGE

<b>Handling Precautions:</b>	Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.
<b>Storage Precautions:</b>	Store product in tightly capped original containers in a cool, dry area. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Engineering Controls:</b>	Use only with production equipment (stencil printers and re-flow furnaces) with adequate ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components so that the exposure levels are not exceeded.
<b>Personal protection:</b>	
<b>Eyes:</b>	Chemical safety glasses/goggles. Face shield for splash hazards.
<b>Respirator:</b>	An authority approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.
<b>Skin:</b>	Compatible chemical resistant gloves.
<b>Other:</b>	Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.
<b>Work/Hygienic Practices:</b>	Maintain good housekeeping. Clean up spills immediately. DO NOT allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Grey colored paste.	<b>Boiling Point:</b>	Not applicable.
<b>Odor:</b>	Mild characteristic odor.	<b>Melting Point:</b>	(25-45C above alloy melting temp temperature)
<b>Specific Gravity:</b>	Not applicable.	<b>pH:</b>	Not applicable
<b>Vapor Pressure:</b>	Not applicable.	<b>Solubility in Water:</b>	Insoluble (paste)
<b>Vapor Density:</b>	(air=1) Not applicable.		

## 10. STABILITY AND REACTIVITY

<b>General:</b>	Stable.
<b>Conditions to Avoid:</b>	Not established.
<b>Incompatible Materials:</b>	Avoid contact with acids, bases or oxidizing agents.
<b>Hazardous Decomposition / Combustion:</b>	Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.
<b>Hazardous Polymerization:</b>	Will not occur.

## 11. TOXICOLOGICAL INFORMATION

<b>Carcinogenicity:</b>	<b>NTP:</b> No
	<b>OSHA:</b> No 29CFR1910.1025
	<b>IARC:</b> Yes Lead and lead compounds are listed as possible carcinogens.

Solder paste is not classified under any agency {NTP/OSHA/IARC}. Proprietary ingredients are not listed as carcinogens.

**Other:** Chronic Toxicity: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational asthma. Lead can cause potential harm to the developing fetus.

## 12. ECOLOGICAL INFORMATION

This section is subject to future development. Product not tested.

## 13. DISPOSAL CONSIDERATION

<b>Waste Disposal Method:</b>	Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations.
-------------------------------	---

## 14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements. Not regulated under US DOT (United States Department of Transportation). Not hazardous under UN shipping regulations.

North American Emergency Guide Book – Not classified

Not regulated for ground/IATA/ocean.



## 15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

WHMIS: D2B –Materials Causing Other Toxic Effects (irritant or sensitizer)

WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic) (lead)



This product has been classified in accordance with the Mexican guidelines, NOM-018-STPS-2015 and NOM-010-STPS-2014.

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products

GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals.

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007.

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).



**WARNING:** This product can expose you to chemicals including [lead] which is known to the State of California to cause cancer, and can cause birth defects or other reproductive harm. For more information go to

[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

SARA 313 Listing - 40 CFR 372.65

Lead CAS# 7439-92-1

Silver CAS# 7440-22-4

EPA Genetic Toxicology Program – Lead CAS# 7439-92-1

All ingredients are listed on the EPA TSCA Inventory.

All ingredients are listed on the Canadian Domestic Substance List.

## 16. OTHER INFORMATION

<b>HMIS Hazard Rating:</b>	<b>Health:</b>	2
	<b>Fire:</b>	1
	<b>Reactivity:</b>	0

**Revised Date:** 25 SEPTEMBER 2018

**Prepared by:** Nancy Swarts, Indium Corporation of America

**Approved by:** Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.