

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: WAVE FLUX 3592-35

MSDS Number: MSDS-4030 Revised Date: 11 APRIL 2016

Product Use: Industrial Use - Flux

MANUFACTURER:

In America:

The Indium Corporation of America 1676 Lincoln Ave., Utica NY 13502 Information: (315) 853-4900

nswarts@indium.com

Indium Corporation of America 80 Scott Street Elk Grove Village, Illinois 60007 (847) 439-9135

In Europe:

Indium Corporation of Europe 7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore 29 Kian Teck Avenue

Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou), Co., Ltd

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

GHS



Signal Word: Danger Hazard statement (s)

H225 Highly flammable liquid and vapor
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness

Precautionary statement(s)

P210 Keep away from heat/spark/open flames/hot surfaces – No Smoking

P233 Keep container closed

P240 Ground container and receiving equipment

P242 Use spark resistant tools

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 +P351 IF IN EYES: Rinse cautiously with water for several minutes (15 mins)

Isopropyl alcohol:

Flammable Liquid - Category 2

Serious eye damage/eye irritant - Category 2

Specific target organ systemic toxicity (single exposure) - Category 3 Central Nervous system

PRIMARY ROUTES OF ENTRY:

Carcinogen listed in

⊗Eye ⊗Inhalation ⊗Skin ⊗Ingestion NTP IARC OSHA ⊗Not Listed

POTENTIAL HEALTH EFFECTS:

Eye Contact: Vapors may be irritating, liquid may damage eye tissue.

Ingestion: May cause persistent nausea, vomiting and abdominal pain. Irritating to digestive tract.

Inhalation: Vapor may cause headaches and or dizziness. Avoid inhalation of vapors. Irritating to respiratory

tract.

Skin Contact: Prolonged contact may cause irritation.

Chronic: Over exposure to vapors may be harmful. Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its

products for human consumption.

WARNING: This product contains a chemical (s) known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (Contains trace amounts of 1, 4 Dioxane)

Applicable in the State of California only.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
ISOPROPANOL	80-90	67-63-0 (US)	980	983	1225
(PROPAN-2-OL)		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Mexico)	980	-	1225
		(China)	-	350	700
		(Singapore)	983	-	1230
PROPRIETARY	10-20	-	N.E.	N.E.	N.E.

N.E. = Not established

Product does not contain any substances under RoHS. Therefore it is compliant.

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: 12°C (54°F) Method: Closed Cup

Auto-ignition Temperature: 750 F

Flammable Limits: Upper: 12 @77°F; Lower 2 @ 77°F

Extinguishing Media: Foam/Water. Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting

Procedures: Wear protective clothing and self contained breathing apparatus. Use water to cool fire

exposed containers. Flammable vapors may travel great distances to ignition source and flash back.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: DO NOT allow material to enter sewer system or waterway. Wear personal protective equipment. Eliminate sources of ignition. Ventilate area in accordance with regulations. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal

Precautions: protective equipment. Ground containers when in use. Ground containers.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product

label for specific storage temperature requirements. Rotate stock to ensure use before

expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Face velocity >2.1 cubic feet/minute in confined areas. Overall general exhaust ventilation

recommended. Use ventilation to keep exposures as low as possible.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An authority approved or EU compliant CE marked air-purifying respirator with a fume/organic

Chemical cartridge is recommended where airborne concentrations are expected to be elevated. Use respiratory protection in confined areas. Air purifying respirators will offer no protection in oxygen

deficient areas. Ensure that the protection factors of the respirator are not exceeded.

Skin: Compatible chemical resistant gloves. Use gloves such as nitrile, which are compatible with alcohols.

Other: Lab coat, eye-wash fountain/shower in work area. Avoid the use of contact lenses in high fume/splash

areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately.

Practices: Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.

Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless Boiling Point: 80°C (175°F)

Odor:Alcohol odor.Evaporation Rate:1.7Specific Gravity:0.834 @ 60° FpH:4.0Vapor Pressure:33 mm HG @ 68 FSolubility in Water:Soluble

Vapor Density: 2.1 (air=1) % Volatiles by volume: 90

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Direct heat, open flames and storage in aluminum.

Incompatible Materials: Anhydrides, halogens, phosphorus, trichlorides, monomers, aldehydes

Hazardous Decomposition /

Combustion:

Carbon dioxide/carbon monoxide.

Hazardous Polymerization: Will not occur.

11.TOXICOLOGICAL INFORMATION

Carcinogenicity: National Toxicity Program **NTP**: No

> Occupational Safety & Health Administration **OSHA**: No International Agency for Research on Cancer IARC: No

LD50: Not established. LC50: Not established.

Oral LD50 (isopropyl alcohol)

LD50 Oral- rat- 5,045 mg/kg

Inhalation LC50 (isopropyl alcohol) LC50 inhalation-rat-8h-16000 ppm

Dermal LD50

LD50 - Dermal- rabbit-12,800 mg/kg

RTECS: Isopropyl alcohol NT8050000

12. ECOLOGICAL INFORMATION

Product not tested.

LC50-Pimephales promelas (fathead minnow)- 9,640 mg/l – 96h (isopropyl alcohol)

EC50-Daphnia magna (water flea) – 5,102 mg/l – 24h (isopropyl alcohol)

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local

environmental regulations. In Europe follow the Special Waste Regulations.

TRANSPORT INFORMATION 14.

Transport in accordance with applicable regulations and requirements.



UN1219, Isopropanol, 3, PG II

North American Emergency Guide Book - Guide # 129 Flammable label

MARINE POLLUTANT: NO

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

WARNING: This product contains a chemical (s) known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (Contains trace amounts of 1, 4 Dioxane)

SARA 313 Listing - 40 CFR 372.65: trace levels of 1, 4 dioxane

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



(T)

Canadian WHMIS:

Class B2 Flammable Liquid D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).

This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with Mexican regulations: NOM-018-STPS-2015 and NOM-010-STPS-2014.

Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 3 Physical Hazard: 0

Revised Date: 11 APRIL 2016

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.