

PRODUCT DATA SHEET

# Indium Trichloride

## InCl<sub>3</sub>

### Introduction

**Indium Trichloride** is a white, odorless, and highly deliquescent powder. Its particles are flake-shaped and highly soluble in water and mineral acids. It is used as a starting chemical for the synthesis of other inorganic and organic indium compounds and as an additive to alkaline batteries to reduce outgassing and improve operational efficiency of the battery when under electrical load. **Indium Trichloride** is available as an anhydrous powder and as a solution up to its solubility limit.



### Properties

Chemical Formula	InCl <sub>3</sub>
Molecular Weight	221.18
General Description	White deliquescent powder
Uses	Chemical Synthesis; alkaline battery additive
Purity Grades Available	4N (99.99%), 5N (99.999%)
Solubility	66.11 g/100g of solution @ 22°C
Specific Gravity	3.46 g/cc solid 1.97 g/cc saturated solution
Melting Point	586°C (sublimes at 300°C)
Boiling Point	Volatilizes @ 600°C
Crystalline Form	White plates, deliquescent
Isomorphous with	AlCl <sub>3</sub> , YCl <sub>3</sub>
Coordination Number	6
Theoretical Indium Percentage	51.91
Minimum Indium Percentage	50.5
Nominal Indium Percentage	51.5 +/- 1.0

### Standard Packaging Powder

Quantity*	Container
1.8kg	3.8-liter plastic
0.5kg	1-liter plastic

### Solution

- 1-liter Polyethylene Bottles
- 3.8-liter (1-gallon) Polyethylene Bottles
- 18.9-liter (5-gallon) Polyethylene Bottles

\*All package sizes contain suitable desiccant. Packaging in other sizes or in glass may be available upon request.

### Storage and Shelf Life

**Indium trichloride** is highly deliquescent and the solid crystals will liquefy quickly in humid environments. The container should contain a desiccant and the container kept tightly sealed. **Indium trichloride** has a shelf life of 6 months due to the deliquescent nature of the chemical.

### Safety Data Sheets

The SDS for this product can be found online at <http://www.indium.com/sds>

This product data sheet is provided for general information only. It is not intended, and shall not be construed, to warrant or guarantee the performance of the products described which are sold subject exclusively to written warranties and limitations thereon included in product packaging and invoices. All Indium Corporation's products and solutions are designed to be commercially available unless specifically stated otherwise.

Form No. 97558 R6

[www.indium.com](http://www.indium.com)

[askus@indium.com](mailto:askus@indium.com)

ASIA: Singapore, Cheongju, Malaysia: +65 6268 8678  
 CHINA: Suzhou, Shenzhen: +86 (0)512 628 34900  
 EUROPE: Milton Keynes, Torino: +44 (0) 1908 580400  
 USA: Utica, Clinton, Chicago, Rome: +1 315 853 4900



ISO 9001  
REGISTERED