



## SAFETY DATA SHEET

User must review the contents of this (SDS) and determine what is applicable to their own country laws under Health and Safety and apply them as necessary. This (SDS) will not reference every countries Health and Safety Laws. It is the user's responsibility to determine what is applicable to them, including but not limited to review of any specific chemical lists and apply the requirements as necessary.

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** WF-9959

**SDS Number:** SDS- 4787

**Revised Date:** 11 DECEMBER 2018

**Product Use:** Industrial Use - Liquid flux for soldering related activities

#### MANUFACTURER:

##### In America:

The Indium Corporation of America  
34 Robinson Rd., Clinton, NY 13323  
Information: (315) 853-4900  
[nswarts@indium.com](mailto:nswarts@indium.com)

Indium Corporation of America  
Chicago Material Division  
80 Scott St.  
Elk Grove Village, Illinois 60007  
(847) 439-9134

##### In Europe:

Indium Corporation of Europe  
7 Newmarket Ct.  
Kingston, Milton Keynes, UK, MK 10 OAG  
Information: +44 [0] 1908 580400

##### In Asia:

The Indium Corporation of America  
Asia-Pacific Operations-Singapore  
29 Kian Teck Avenue  
Singapore 628908  
Information: +65 6268-8678

#### EMERGENCY PHONE:

**CHEMTREC 24 hrs.**

**USA: 1 (800) 424-9300**

**Outside USA: +1 (703) 527-3887**

**In China: Emergency 86+ 4008417580**

##### In China:

Indium Corporation(Suzhou) Co., Ltd.  
No. 428 Xinglong Street  
Suzhou Industrial Park  
Suchun Industrial Square  
Unit No. 14-C  
Jiangsu Province, China 215126  
Information: (86) 512-6283-4900

## 2. HAZARDS IDENTIFICATION

### PRIMARY ROUTES OF ENTRY:

Eye   
 Inhalation   
 Skin   
 Ingestion   
 NTP   
 IARC   
 OSHA   
 Not Listed

### Carcinogen listed in

GHS:



Signal Word: Danger

#### Hazardous statement(s)

- H319 Causes serious eye irritation
- H225 Highly flammable liquid and vapor
- H317 May cause an allergic skin reaction
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness and dizziness

#### Precautionary statement(s)

- P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking
- P233 Keep container tightly closed
- P240 Ground container and receiving equipment
- P242 Use only non-sparking equipment
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P270 Do not eat, drink or smoke when using this product
- P273 Avoid release to the environment
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P362 + P364 Take off contaminated clothing and wash before reuse
- P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water
- P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

#### Classification:

- Flammable Liquid – Category 2
- Eye irritation – Category 2A
- Skin sensitization- Category 1B
- Respiratory sensitization- Category 1B
- Specific target organ toxicity- single exposure – Category 3- central nervous system

### POTENTIAL HEALTH EFFECTS:

- Eye Contact:** Irritating to the eyes and if not removed promptly, may result in serious eye injury. Do not allow material to come in contact with the eyes.
- Ingestion:** May be harmful if swallowed. May cause irritation and damage to the mouth, esophagus, gastrointestinal tract. May cause headache, dizziness or lowered blood pressure.
- Inhalation:** Heated vapor concentrations may be harmful if inhaled. Moderately toxic. Moderately irritating to respiratory tract. Inhalation of high concentrations may cause headache or central nervous system depression. Rosin may cause occupational asthma.
- Skin Contact:** May cause skin irritation or dryness. Allergic reactions/dermatitis are possible, especially with

repeated or prolonged exposure.

**Chronic:** Target organs: CNS

**NOTE:** The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #/EINECS	PEL mg/m <sup>3</sup>	TLV-TWA mg/m <sup>3</sup>	TLV-STEL mg/m <sup>3</sup>
<b>ROSIN FLUX</b>	40-50	65997-05-9	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15
<b>ISOPROPYL ALCOHOL</b> (Propan-2ol)	35-40	67-63-0/200-661-7	980	983	1230
		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Singapore)	983	-	1230
		(Mexico)	-	980	1225
		(China)	-	350	700
<b>METHYL ETHYL KETONE</b> (Butanone)	10-20	78-93-3/201-159-0	590	590	885
		(EU)	N.E.	600	899
		(Canada)	N.E.	590	885
		(Singapore)	590	-	885
		(Mexico)	-	590	885
		(China)	-	300	600

N.E. = Not established      EU = European Union Occupational Exposure Limits

### 4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

## 5. FIRE FIGHTING MEASURES

<b>Flash Point:</b>	11 C (52 F)	<b>Method:</b>	Not available
<b>Auto-ignition Temperature:</b>	Not established.		
<b>Flammable Limits:</b>	Limits not established. Flammable		
<b>Extinguishing Media:</b>	Use extinguishers appropriate for the surrounding fire conditions. Foam, dry chemical, water spray.		
<b>Special Fire Fighting Procedures:</b>	Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing. Evacuate area and fight fire from a safe distance. Containers can build up pressure if exposed to heat (fire) or flame.		

## 6. ACCIDENTAL RELEASE MEASURES

<b>Spill or Leak Procedures:</b>	Wear a respirator and appropriate Personal Protective (See Exposure Controls/Personal Protective Section). Size of spill shall determine respiratory protection from air purifying to self contained breathing apparatus. Keep unnecessary and unprotected personnel from entering the spill area. Extinguish or remove all ignition sources. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.
----------------------------------	--

## 7. HANDLING AND STORAGE

<b>Handling Precautions:</b>	Keep containers tightly closed when not in use. Use care to avoid spills. Avoid breathing vapors from heated material. Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Ground containers.
<b>Storage Precautions:</b>	Store product in tightly capped original containers in a cool, dry area. Keep away from heat and flame. Store away from incompatible materials. Empty containers may be hazardous as they contain product residue.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Engineering Controls:</b>	Exhaust ventilation is necessary control airborne levels and any potential exposures.
<b>Personal protection:</b>	
<b>Eyes:</b>	Chemical safety glasses/ splash goggles. Face shield for splash hazards.
<b>Respirator:</b>	An approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated.
<b>Skin:</b>	Compatible chemical resistant gloves. Protective outer garment, apron. Sleeves as appropriate. Face shield is recommended when there is a possibility for splash hazards.
<b>Other:</b>	Eyewash fountain in work area. Avoid the use of contact lenses.
<b>Work/Hygienic Practices:</b>	Maintain good housekeeping. Clean up spills immediately. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	Liquid	<b>Boiling Point:</b>	84 C (183 F)
<b>Odor:</b>	Slight characteristic odor.	<b>Melting Point:</b>	Not applicable
<b>Specific Gravity:</b>	0.88	<b>pH:</b>	Not applicable
<b>Vapor Pressure:</b>	Not applicable.	<b>Solubility in Water:</b>	Not established
<b>Vapor Density:</b>	(air=1) Not applicable.		

**10. STABILITY AND REACTIVITY**

<b>General:</b>	Stable.
<b>Conditions to Avoid:</b>	High temperatures, open flame, oxidizing agents, strong reducing agents.
<b>Incompatible Materials:</b>	Excessive heat
<b>Hazardous Decomposition / Combustion:</b>	Not established
<b>Hazardous Polymerization:</b>	Will not occur.

**11. TOXICOLOGICAL INFORMATION**

<b>Carcinogenicity:</b>	<b>NTP:</b> No		
	<b>OSHA:</b> No		
	<b>IARC:</b> No		
<b>LD50:</b>	Not established.	<b>LC50:</b>	Not established.
<b>Other:</b>	Methyl ethyl ketone LD50 Oral, rat, 2,737 mg/kg LD50 Dermal, rabbit, 6,480 mg/kg		

**12. ECOLOGICAL INFORMATION**

Product not tested.

**13. DISPOSAL CONSIDERATION**

**Waste Disposal Method:** Dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations.

**14. TRANSPORT INFORMATION**

Transport in accordance with applicable international regulations and requirements.

Shipping Name: UN 1993, Flammable Liquid, N.O.S., 3, PG II (methyl ethyl ketone, isopropanol)



North American Emergency Guide Book – Guide # 128

## 15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS: Class B Division 2 Flammable, D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).



This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products

GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2007.

SARA 313 Listing - 40 CFR 372.65 - Methyl Ethyl Ketone CAS# 78-93-3

All ingredients are listed on the EPA TSCA Inventory.

## 16. OTHER INFORMATION

<b>HMIS Hazard Rating:</b>	<b>Health:</b>	2
	<b>Fire:</b>	3
	<b>Physical Hazard:</b>	0

**Revised Date:** 11 DECEMBER 2018

**Prepared by:** Nancy Swarts, Indium Corporation of America

**Approved by:** Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.