



INDIUM CORPORATION OF AMERICA
®\EUROPE®\ASIA-PACIFIC®/INDIUM CORPORATION (SUZHOU) ®

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: TIN PLATED NANOFOIL®

SDS Number: SDS-5950

Revised Date: 8 OCTOBER 2014

Product Use: INDUSTRIAL USE – FOIL: MIXTURE OF ALUMINUM AND NICKEL ENCAPSULATED IN InCuSiI Cladding NF-30,40,50,60,80,100,125,150 and 200 micron Series. This is a multilayer foil material also known as a pyrotechnic initiator of two reactive metals. PLATING: Material is then plated with 25-30% tin.

Nanofoil is used in applications such as soldering as a source of heat. The components can be joined when the foil is between layers to be joined. When initiated the heat energy across the area will join the pieces.

MANUFACTURER:

In America:

The Indium Corporation of America
 1676 Lincoln Ave., Utica NY 13502
 Information: (315) 853-4900
 nswarts@indium.com

EMERGENCY PHONE:

CHEMTREC 24 hrs.
USA: 1 (800) 424-9300
Outside USA: +1 (703) 527-3887

The Indium Corporation of America
 Chicago Materials Division
 80 Scott Street
 Elk Grove Village, Illinois 60007
 Information: (847) 439-9135

In Europe:

Indium Corporation of Europe
 7 Newmarket Ct.
 Kingston, Milton Keynes, UK, MK 10 OAG
 Information: +44 [0] 1908 580400

In China:

Indium Corporation (Suzhou) Co., Ltd.
 No. 428 Xinglong Street
 Suzhou Industrial Park
 Suchun Industrial Square
 Unit No. 14-C
 Jiangsu Province, China 215126
 Information: (86) 512-6283-4900

In Asia:

Indium Corporation of America
 Asia-Pacific Operations-Singapore
 29 Kian Teck Avenue
 Singapore 628908
 Information: +65 6268-8678

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

⊕Eye ⊕Inhalation ⊕Skin ⊕Ingestion

CARCINOGEN LISTED IN:

NTP IARC OSHA ⊕Not Listed



Signal Word: Danger/Flammable Solid

Hazard statement(s):

H228 Flammable Solid
 H313 May be harmful in contact with skin
 H317 May cause an allergic skin reaction
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H351 Suspected of causing cancer (nickel)
 H412 Harmful to aquatic life with long lasting effects

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking
 P233 Keep container tightly closed
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P270 Do not eat, drink or smoke when using this product
 P273 Avoid release to the environment
 P280 Wear protective gloves/protective clothing/eye protection/face protection
 P362 Take off contaminated clothing and wash before reuse
 P302 +P352 IF ON SKIN: Wash with plenty of soap and water
 P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

At this time full GHS review is still on-going regarding proper classification for this product

IMPORTANT EMERGENCY OVERVIEW: In the un-reacted, metallic foil or sheet form, layered aluminum and nickel are highly reactive and ignition will result in generation of heat. Once ignited, reaction of the entire sheet/foil is for all practical purposes instantaneous and impossible to extinguish. In solid form, the product is not considered hazardous to health other than the potential for burns should ignition occur while actually handling. Avoid inhalation of fumes.

POTENTIAL HEALTH EFFECTS:

WARNING - HANDLE WITH CARE. Metallic sheets vary in sizes and thickness. An exothermic reaction in the material may be initiated for example by electric spark, electric current, direct contact with flame, sudden or rapid increase in temperature, high intensity laser beam, concentrated microwave energy, intense mechanical impact, or abrasion such as friction. Other activities such as dropping of the sheet onto a floor, banging sheet against an object, dropping something onto a sheet or just knocking a corner could set the reaction off.

The foil or metallic sheet glows yellow when reacting and can reach temperatures of 1500C (2732F) instantly upon ignition.

Eye Contact: Reaction fumes may cause irritation.

Ingestion: Not expected to be a route of entry. Ingestion of fumes may cause irritation

Inhalation: Inhalation of reaction fumes may cause irritation. Nickel fume may cause allergic asthma. Inhalation of fumes from initiation of the exothermic reaction in the material or generation of dust by grinding or abrasion may aggravate allergy symptoms in sensitized individuals or trigger an attack in asthmatic

individuals.

Skin Contact: Normal handling should not cause any adverse health effects. However, contact or close proximity during reaction may cause thermal burns. Nickel may cause skin sensitivity or dermatitis.

Chronic:

SILVER: Chronic skin contact or ingestion of silver dusts, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

COPPER: Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

INDIUM: May cause damage to respiratory system.

NICKEL: May cause a form of dermatitis known as nickel itch. Intestinal irritation, which may cause disorders, convulsions and asphyxia.

ALUMINUM: inhalation of finely divided aluminum powder may cause pulmonary fibrosis.

TIN: Has been shown to increase incidence of sarcoma in animal tests. Chronic exposure to tin dusts and fume may result in "stannosis" a mild form of pneumoconiosis.

WARNING: **Applicable in the State of California under the Safe Drinking Water Standard, Prop 65. This product contains a chemical known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (trace levels of lead), nickel**

NOTE: **The Indium Corporation does not recommend, manufacturer, market or endorse any of its products for human consumption.**

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #/EINECS#	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
NICKEL	55 – 65	7440-02-0			
		(US)	1	0.015	-
		(Canada)	-	1	2
		(Singapore)	1	-	-
		(Mexico)	1	-	-
ALUMINUM	25 - 35	7429-90-5			
		(US)	15	10	-
		(EU)	-	10*	-
		(Canada)	-	10	20
		(Mexico)	-	5	-
VANADIUM	1 – 5	7440-62-2/231-171-1	N.E.	N.E.	N.E.

INDIUM	<2	7440-74-6/231-180-0	(US)	0.1	0.1	-
			(EU)	-	0.1	0.3
			(Canada)	-	0.1	0.3
			(Singapore)	0.1	-	-
			(Mexico)	-	0.1	0.3
			(China)	-	0.1	0.3
			SILVER	1 - 10	7440-22-4/231-131-3	(US)
			(EU)	-	0.1	-
			(Canada)	-	0.1	0.3
			(Singapore)	0.1	-	-
			(Mexico)	-	0.1	-
COPPER	1 - 5	7440-50-8/231-159-6	(US)	0.1	0.2	-
			(EU)	-	0.2(fume)	-
			(Canada)	-	0.2	0.6
			(Singapore)	0.2	-	-
			(Mexico)	-	0.2	2
			(China)	-	0.2(fume)	0.6
			TIN	25 - 30	7440-31-5/231-141-8	(US)
			(EU)	-	2	4
			(Canada)	-	2	4
			(Singapore)	2	-	-
<p>Immediately Dangerous To Life and Health (IDLH) – Nickel 10 mg/m3</p> <p>Reacted material is Nickel Aluminide CAS# 12003-78-0 (EINECS 231-111-4)</p> <p>PRODUCT DOES NOT CONTAIN ANY LISTED EU SUBSTANCES OF VERY HIGH CONCERN (SVHC)</p> <p>N.E. = Not established EU = European Union Occupational Exposure Limits</p>						

4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists. Flash may cause burns to the eyes, seek medical advice.
- Ingestion:** Not likely a route of entry. If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention. Generally not considered to be a route of entry.
- Skin Contact:** Contact may cause thermal burns. Remove any contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If burned seek medical attention.

5. FIRE FIGHTING MEASURES

- Flash Point:** Not established. **Method:** Not established.
- Auto-ignition Temperature:** Reaction Temp: 1500C (2732F) instantaneously
- Flammable Limits:** Limits not established.
- Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions. Once ignited the reaction is instantaneous and complete.
- Special Fire Fighting Procedures:** Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.
- Note:** Unusual fire hazards: Material is a self - heating and self - reacting product. Once it is ignited it will react immediately. Material is not explosive and will extinguish itself provided it is away from combustible materials. Material is not explosive.
- Fire could occur with secondary sources having direct contact with the initial reaction of the Nanofoil.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures:

Un-reacted material is sensitive to ignition sources. Keep away from sources of heat or spark. If dust or powder do not dry sweep material. Wet materials prior, for clean-up. Do not use compressed air or vacuum for clean-up. Place inside metal container, cover and label. Material is considered to be a flammable solid. Keep unauthorized personnel away.

Non spark tools.

Re-acted material clean up by using wet sweeping and avoid dust generation. Place into metal container, cover and label. Caution handle with care to ensure all material has reacted completely. If in doubt handle only as a flammable solid.

Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

7. HANDLING AND STORAGE

- Handling** Handle away from sources of ignition. Avoid static charges.
- Precautions:** Wear leather gloves when handling. Handle with care. Keep all combustible materials away from

product. Product can flash and while it does burn quickly the hazard could be any secondary fire.

WARNING - HANDLE WITH CARE. Metallic sheets vary in sizes and thickness. An exothermic reaction in the material may be initiated for example by electric spark, electric current, direct contact with flame, sudden or rapid increase in temperature, high intensity laser beam, concentrated microwave energy, intense mechanical impact, or abrasion such as friction. Other activities such as dropping of the sheet onto a floor, banging sheet against an object, dropping something onto a sheet or just knocking a corner could set off the reaction.

The foil or metallic sheet glows yellow when reacting and can reach temperatures of 1500C (2732F) instantly upon ignition.

Storage Precautions: Store in electrically grounded, antistatic, closed containers. Keep away from sources of heat, open flames, sparks, combustibles and sources of static charge. Store in cool dry environment. Safe storage in flammable cabinet is required. Handle material with care. Keep away from material that could be a secondary source of fire should the Nanofoil react. Keep away from busy work areas where there might be a potential for the material to be disturbed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Local exhaust ventilation is required to control any metal containing air contaminants. Control concentration of all components so that their exposure levels are not exceeded. Metal fume must be properly vented. Employees should avoid potential exposure. Use shields when reacting the metal to avoid splash hazards from ignition. Keep hands away.

Personal protection:

Eyes: Chemical safety glasses/goggles and face shield with reactive metal.

Respirator: An authority approved or compliant marked air-purifying respirator with a fume/dust chemical cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated. Protect against exposures to fume and dust. Avoid breathing fumes.

Skin: Gloves-leather type. Heat resistant gloves if handling hot metal. Avoid direct skin contact.

Other: Lab coat, safety shower and eye-wash fountain in work area. Avoid the use of contact lenses in high fume/splash areas.

Work/Hygienic Practices: Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Silver grey solid metal	Boiling Point:	Not applicable.
Odor:	Odorless	Melting Point:	See Below
Specific Gravity:	Not available	pH:	Not applicable
Vapor Pressure:	Not applicable.	Solubility in Water:	Insoluble
Vapor Density:	(air=1) Not applicable.		
Melting Points:	Al = 660C, Ni = 1455C, InCuSil-15 =705C		

Note: Material can flash quickly. Fire will occur quickly and burn out. It will not sustain.

10. STABILITY AND REACTIVITY

General: Stable at room temperature and pressure. Product is self-heating and self- reacting

	upon initiation. Handle with care. Review Sections 2 and 7.
Conditions to Avoid:	Sudden temperature increase, high oxygen content atmosphere and initiation sources. Known initiation sources are flame, laser, concentrated microwaves, static discharges and electric or mechanical sparking.
Incompatible Materials:	Avoid contact with halogens, strong acids, strong alkalis, oxidizing agents, flammables and combustibles. Reacts with hydrochloric acid, performic acid, ammonium nitrate.
Hazardous Decomposition / Combustion:	Harmful organic fumes, metal oxide and toxic oxide fumes may form at elevated temperatures.
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION	
Carcinogenicity: National Toxicity Program (NTP):	Yes (nickel)
Occupational Safety & Health Administration (OSHA):	Yes (nickel)
U.N. International Agency for Research on Cancer (IARC):	Yes (nickel)
RTECS QR5950000, for additional information (nickel)	
RTECS GL 5325000, for additional information (copper)	
RTECS NL 1050000 for additional information (indium)	
RTECS BD0330000 for additional information (aluminum)	
RTECS VW3500000 for additional information (silver)	

12. ECOLOGICAL INFORMATION	
No information available at this time.	

13. DISPOSAL CONSIDERATION	
Waste Disposal Method:	Dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations. Material should be properly managed. Un-reacted material is a flammable solid. When disposing ensure material is properly handled. Always handle as if not all material was flashed off. Hazardous material. Keep away from combustibles. If in pieces package in metal drums and layer with sand to protect from friction between pieces and possible ignition. Full sheet wrap to prevent friction between the layers. Consult waste disposer for guidance.

14. TRANSPORT INFORMATION	
Transport in accordance with applicable regulations and requirements.	
UN 3178, Flammable Solid, Inorganic, N.O.S., 4.1, PG II (nickel aluminum foil)	
North America Emergency Guide Book – Guide #133	Flammable Solid



Passenger aircraft: 15 kg
Cargo aircraft: 50 kg

Packaging must be in an approved overpack containers.

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS: flammable solid



This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

This product has been classified in accordance with the Mexican regulations NOM-018-STPS-2000 and NOM-010-STPS-1999.

State of California Safe Drinking Water Standard - PROP 65: WARNING : This product contains a chemical known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (trace levels of lead), nickel

US EPA - SARA 313 Listing - 40 CFR 372.65: Nickel, Silver, Copper

All ingredients are listed on the US EPA TSCA Inventory.

Tariff Code: 7506.20.5000

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

X_n, F

Risk Phrases:

R36/37/38 Irritating to eyes, respiratory system and skin
R43 May cause sensitization by skin contact
R40 Limited evidence of carcinogenic effect (nickel)
R10 Flammable

Safety Phrases:

S16 Keep away from sources of ignition-No smoking

S20/21	When using do not eat, drink or smoke
S22	Do not breathe dust
S23	Do not breathe fumes
S24/25	Avoid contact with skin and eyes
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection

16. OTHER INFORMATION

HMIS Hazard Rating:	Health:	3
	Fire:	1
	Physical Hazard:	2

Revised Date: 8 OCTOBER 2014

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container. The Indium Corporation does not recommend, manufacturer, market or endorse any of its products for human consumption.