



SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: BiAgX®WITH INDIUM 7.16 FLUX VEHICLE

SDS Number: SDS-6003

Revised Date: 27 SEPTEMBER 2018

Product Use: Industrial Use – (Mixture) solder paste consisting of a flux vehicle blended with weight percent 89-93% pre-alloyed metal powder.

MANUFACTURER:

In America:

The Indium Corporation of America®
34 Robinson Rd., Clinton, New York 13323
Information: (315) 853-4900
Outside USA: (IDD) +1-315-853-4900
Fax: (IDD) + 1-315-853-1000
nswarts@indium.com

EMERGENCY PHONE (SPILL):

CHEMTREC 24 hrs.
USA: 1 (800) 424-9300
Outside USA: +1 (703) 527-3887
In China: Emergency 86+ 4008417580

In Europe:

Indium Corporation of America (European Operations)
7 Newmarket Ct.
Kingston, Milton Keynes, UK, MK 10 OAG
Information: +44 [0] 1908 580400

In China:

Indium Corporation (Suzhou) Co., Ltd.
No. 428 Xinglong Street
Suzhou Industrial Park
Suchun Industrial Square
Unit No. 14-C
Jiangsu Province, China 215126
Information: (86) 512-6283-4900

In Asia:

Indium Corporation of America
Asia-Pacific Operations-Singapore
29 Kian Teck Avenue
Singapore 628908
Information: +65 6268-8678

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

⊗Eye ⊗Inhalation ⊗Skin ⊗Ingestion NTP IARC OSHA ⊗Not Listed

Carcinogen listed in

GHS:



Signal Word: Warning

Hazard statement (s)

H317 May cause an allergic skin reaction
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
 EUH208: Contains rosin. May produce an allergic reaction.

Precautionary statement(s)

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P270 Do not eat, drink or smoke when using this product
 P273 Avoid release to the environment
 P280 Wear protective gloves/protective clothing/eye protection/face protection
 P362 Take off contaminated clothing and wash before reuse
 P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell
 P302 +P352 IF ON SKIN: Wash with plenty of soap and water
 P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305 +P351 IF IN EYES: Rinse cautiously with water (15 minutes)

POTENTIAL HEALTH EFFECTS:

Eye Contact: Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause serious eye irritation.

Ingestion: This product contains metal alloy powders and organic chemicals. May cause irritation or harm.

Inhalation: Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to the respiratory system. Inhalation of rosin fume may cause occupational asthma.

Skin Contact: May cause skin irritation. Rosin may cause dermatitis.

Chronic: SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

BISMUTH: May cause kidney damage.



WARNING: This product can expose you to chemicals including [trace amounts of lead] which is known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #/ EINECS#	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
TIN	1 - 5	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
SILVER	2 - 20	(Singapore)	2	-	-
		7440-22-4/231-131-3			
		(US)	0.01	0.1	-
		(EU)	-	0.1	-
		(Canada)	-	0.1	0.3
		(Mexico)	-	0.1	-
		(Singapore)	0.1	-	-
BISMUTH	70 - 95	7440-69-9/231-177-4	N.E.	N.E.	N.E.
ROSIN	3 - 5	65997-05-9	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15 (sensitiser)
POLYGLYCOL ETHER	2 - 3	9038-95-3	N.E.	N.E.	N.E.
CARBOXYLIC ACID	2 - 3	68937-69-9	N.E.	N.E.	N.E.

N.E. = Not established

4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

- Flash Point:** Not established. **Method:** Not established.
- Auto-ignition Temperature:** Not established.
- Flammable Limits:** Limits not established.

Extinguishing Media:	Use extinguishers appropriate for the surrounding fire conditions.
Special Fire Fighting Procedures:	Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures:	Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose contaminated cloth rags or paper towels following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.
----------------------------------	---

7. HANDLING AND STORAGE

Handling Precautions:	Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.
Storage Precautions:	Store product in tightly capped original containers in a cool, dry area. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Use only with production equipment (such as stencil printers and re-flow furnaces) with adequate ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components so that any permissible exposure limits are not exceeded.
Personal protection:	
Eyes:	Chemical safety glasses/goggles. Face shield for any splash hazards.
Respirator:	An authority approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.
Skin:	Compatible chemical resistant gloves.
Other:	Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.
Work/Hygienic Practices:	Maintain good housekeeping. Clean up spills immediately. Do not allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Grey colored paste.	Boiling Point:	Not applicable.
--------------------	---------------------	-----------------------	-----------------

Odor:	Mild characteristic odor.	Melting Point:	Not applicable
Specific Gravity:	1 g/cc	pH:	4-6 (flux)
Vapor Pressure:	Not applicable.	Solubility in Water:	Insoluble (paste)
Vapor Density:	(air=1) Not applicable.	Flash Point:	Not applicable

10. STABILITY AND REACTIVITY

General:	Stable.
Conditions to Avoid:	Not established.
Incompatible Materials:	Avoid contact with acids, bases or oxidizing agents.
Hazardous Decomposition / Combustion:	Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.
Hazardous Polymerization:	Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity:	NTP: No		
	OSHA: No		
	IARC: No		
LD50:	Not established.	LC50:	Not established.
Other:	Chronic Toxicity: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational asthma.		

12. ECOLOGICAL INFORMATION

Product not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method:	Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations. In USA: Classified as non - hazardous under US EPA regulations. Do not dispose of into any waterway.
-------------------------------	--

14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements. Not regulated under US DOT (United States Department of Transportation).

Non hazardous under shipping regulations and requirements (USDOT/IATA/IMDG).

UN - none

North American Emergency Guide Book – Not Classified

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

SARA 313 Listing - 40 CFR 372.65
Silver



WARNING: This product can expose you to chemicals including [trace amounts of lead] which is known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

All ingredients are listed on the US EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS: Class D 2B Materials Causing Other Toxic Effects (irritant)

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with the Mexican guidelines, NOM-018-STPS-2015 and NOM-010-STPS-2014.

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products

GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals.

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007.

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

16. OTHER INFORMATION

HMIS Hazard Rating:	Health:	1
	Fire:	1
	Reactivity:	0

Revised Date: 27 SEPTEMBER 2018

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.