

# INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC®\INDIUM CORPORATION SUZHOU® SAFETY DATA SHEET

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: 5RMA-RC FLUX

SDS Number: SDS-6114 Revised Date: 9 SEPTEMBER 2016

Product Use: Industrial Use - Flux

**MANUFACTURER:** 

In America: EMERGENCY PHONE:

The Indium Corporation of America CHEMTREC 24 hrs. 1676 Lincoln Ave., Utica NY 13502 USA: 1 (800) 424-9300

Information: (315) 853-4900 Outside USA: +1 (703) 527-3887 nswarts@indium.com

Information: +65 6268-8678

In Europe: In China:

Indium Corporation of Europe Indium Corporation Suzhou Co., Ltd

7 Newmarket Ct.

No. 428 Xinglong Street
Kingston, Milton Keynes, UK, MK 10 OAG
Suzhou Industrial Park
Information: +44 [0] 1908 580400
Suchun Industrial Square

Unit No. 14-C

In Asia: Jiangsu Province, China 215126

Indium Corporation of America

Asia-Pacific Operations-Singapore Information: (86) 512-6283-4900 29 Kian Teck Avenue Singapore 628908

## 2. HAZARDS IDENTIFICATION

# PRIMARY ROUTES OF ENTRY: Carcinogen listed in

⊗Eye ⊗Inhalation ⊗Skin ⊗Ingestion NTP IARC OSHA ⊗Not Listed

GHS:







# Signal Word: Danger Hazard Statements:

H225 Highly Flammable liquid and vapor
 H317 May cause an allergic skin reaction
 H319 Causes serious eye irritation

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking

P233 Keep container tightly closed

P240 Ground/Bond container and receiving equipment
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 minutes)

#### Classification:

Eye irritant – (Category 2A)

Flammable liquids - (Category 2)

Specific target organ systemic toxicity (single exposure) – (Category 3), Central nervous system

Skin sensitizer- Category 1B

Respiratory sensitizer- Category 1B

## **POTENTIAL HEALTH EFFECTS:**

**Eye Contact:** Vapors may be irritating, liquid may irritate eye tissue.

**Ingestion:** May result in gastric disturbances such as nausea and vomiting. Irritating to digestive tract.

**Inhalation:** May cause throat irritation, headache or dizziness. Irritating to respiratory tract. Rosin may

cause occupational asthma.

**Skin Contact:** Prolonged contact may cause irritation or dermatitis. Rosin may cause skin sensitization.

**Chronic:** Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of it's

products for human consumption.

components	% wt	CAS Registry #/EINECS#	<b>PEL</b> mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
ISOPROPYL ALCOHOL	60-65	67-63-0/200-661-7 (US)	980	983	1230
		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Singapore)	983	-	1230
		(Mexico)	-	980	1225
		(China)	-	350	700
ROSIN	20-25	8050-09-7	N.E	N.E	N.E.
		(EU)	0.05	-	0.15
ISOBUTYL ALCOHOL	10-15	78-83-1/201-148-0	300	152	-
		(Canada)	-	152	227
		(Singapore)	152	-	-
		(Mexico)	-	150	225

## 4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

**Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

## 5. FIRE FIGHTING MEASURES

Flash Point: 61F Method: TCC

**Auto-ignition Temperature:** 750 F

Flammable Limits: Upper limit 12 @ 77F. Lower limit 2 @ 77 F.

**Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Standard fire fighting equipment. Water spray/CO2

Procedures:

#### 6. ACCIDENTAL RELEASE MEASURES

**Spill or Leak Procedures:** Do not allow material to enter sewer system or waterway. Wear personal protective equipment, such as gloves and depending on the quantity a respirator with organic cartridges may be required. Clean up by absorption. Eliminate sources of ignition. Keep unnecessary personnel away. Put clean-up materials in a properly labeled metal drum. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

#### 7. HANDLING AND STORAGE

**Handling** Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal

**Precautions:** protective equipment. Ground containers from static charge.

**Storage Precautions:** Store product in tightly capped original containers in a cool, dry area away from sources of

ignition. Refer to product label for specific storage temperature requirements. Rotate stock

to ensure use before expiration date on the label.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation is recommended

to keep exposure limits as low as possible.

Personal protection:

**Eyes:** Chemical safety glasses/goggles. Face shield for splash hazards.

**Respirator:** An approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended where airborne concentrations are expected to be elevated.

**Skin:** Compatible chemical resistant gloves.

Other: Lab coat, eyewash fountain in work area. Avoid the use of contact lenses in high fume/splash

areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately.

**Practices:** Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.

Wash hands thoroughly with soap and water immediately upon leaving the work area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Amber **Boiling Point:** 177°F

Odor:AlcoholicMelting Point:Not applicableSpecific Gravity:0.865pH:Not availableVapor Pressure:33 mm HG @68°CSolubility in Water:Insoluble

Vapor Density: 2.1 Evaporation Rate: 1.7

Volatile by Volume: 75%

## 10. STABILITY AND REACTIVITY

General: Stable.

**Conditions to Avoid:** Direct heat, open flames and storage in aluminum.

Incompatible Materials: phosphorus, halogens, anhydrides, monomers, aldehydes, trichlorides

**Hazardous Decomposition /** 

Combustion:

Carbon dioxide/carbon monoxide.

Hazardous Polymerization: Will not occur.

## 11.TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

OSHA: No IARC: No

**LD50:** Not established. **LC50:** Not established.

# 12. ECOLOGICAL INFORMATION

Product not tested.

## 13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local

environmental regulations. In Europe follow the Special Waste Regulations.

## 14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

Shipping: UN 1987, Alcohols, N.O.S., 3, PG II (isopropanol, isobutyl alcohol)

North American Emergency Guide Book – Guide #127 Flammable label



#### 15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

SARA 313 Listing - 40 CFR 372.65: None

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

WHMIS: Class B Flammable Division 2 Canadian WHMIS: Class B Division 2 Flammable, D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).





This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with Mexican regulations NOM-0180STPS-2015 and NOM-010-STPS-2014.

#### Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS). (GHS)

#### In China:

Decree No. 591: Regulations on the Control over Safety of Hazardous Chemicals GB 30000.2-29-2013, Rules for classification and labeling of chemicals. (GHS)

GB/T 16483-2008, GB/T 17517-2013

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007

## **16. OTHER INFORMATION**

HMIS Hazard Rating: Health: 2

Fire: 3 Reactivity: 0

**Revised Date:** 9 SEPTEMBER 2016

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.