

# **SAFETY DATA SHEET**

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH INDIUM 3.2HFA FLUX VEHICLE

SDS Number: SDS-6249 Revised Date: 6 AUGUST 2018

**Product Use:** Industrial Use (mixture) - Solder paste consisting of a flux vehicle blended with 85-90 weight

percent pre-alloyed metal powder. Consult alloy table for list of alloys mixed with the same flux.

### **MANUFACTURER:**

In America:

The Indium Corporation of America® 34 Robinson Rd., Clinton, New York 13323

Information: (315) 853-4900 NSWARTS@INDIUM.COM

In Europe:

Indium Corporation of America ® (European Operations)

7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG

Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore

29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678

**EMERGENCY PHONE(SPILL ONLY):** 

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887 In China: Emergency 86+ 4008417580

In China:

Indium Corporation (Suzhou) Co., Ltd

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

### 2. HAZARDS IDENTIFICATION

#### PRIMARY ROUTES OF ENTRY:

## Carcinogen listed in

⊕Eye ⊕Inhalation ⊕Skin ⊕Ingestion NTP IARC OSHA ⊕Not Listed

See Section 11

#### GHS:

#### Lead free products





# Signal Word: Warning Hazard statement(s)

H317 May cause an allergic skin reaction H319 Causes serious eye irritation H335 May cause respiratory irritation

## Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 + P364 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing

P305 + P351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

### Lead containing products







# Signal Word: Warning Hazard statement(s)

H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H335 May cause respiratory irritation
H351 Suspected of causing cancer

H361 Suspected of damaging fertility or the unborn child

H373 May cause damage to organs through prolonged or repeated exposure

H410 Very toxic to aquatic life with long lasting effects

EUH201A Warning! Contains lead. Review listing

### Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 + P364 Take off contaminated clothing and wash before reuse

P301 + P314	IF SWALLOWED: Get Medical advice/attention if you feel unwell
1 301 1 314	II SWALLOWED. Get Medical advice/attention if you leef driven
P302 +P352	IF ON SKIN: Wash with plenty of soap and water
P304 + P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position
i .	comfortable for breathing
P305 + P351	IF IN EYES: Rinse continuously with water for several minutes (15 mins)
	= . =

------

#### CLASSIFICATION:

Sensitization, skin-Category 1B
Serious eye irritation-Category 2A
Carcinogenicity-Category 2 (lead)
Specific target organ, repeated exposure-Category 2 (lead)
Reproductive toxicity-Category 1B (lead)
Hazardous to aquatic environment- Category 1 (lead)

#### **POTENTIAL HEALTH EFFECTS:**

**Eye Contact:** Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause eye irritation.

**Ingestion:** This product contains metal alloy powders and chemicals. Irritating to digestive tract.

**Inhalation:** Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause irritation to the respiratory system.

**Skin Contact:** May Cause skin irritation. May cause allergic skin reaction with repeated exposures.

#### **Chronic:**

<u>SILVER</u>: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Has been shown to increase incidence of sarcoma in animal tests.

<u>COPPER:</u> Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

<u>LEAD:</u> Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.

Note: The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

WARNING: This product can expose you to chemicals including [lead, trace amounts of propylene oxide] which are known to the State of California to cause cancer and [lead] which can cause birth defects or other reproductive harm. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

WARNING: This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making of joints in any private or public potable (drinking) water supply system. Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS					
Components	% wt	CAS Registry #/ EINECS#	<b>PEL</b> mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
TIN	*	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
SILVER	*	(Singapore) 7440-22-4/231-131-3	2	-	-
		(US)	0.01	0.1	-
		(EU)	-	0.1	-
		(Canada)	-	0.1	0.3
		(Mexico)	-	0.1	-
		(Singapore)	0.1	-	-
COPPER	*	7440-50-8/231-159-6			
		(US)	0.1 (fume)	0.2 (fume)	-
		(EU)	-	0.2 (fume)	-
		(Canada)	-	0.2 (fume)	0.6 (fume)
		(Mexico)	-	0.2(fume)	2
		(Singapore)	0.2	-	-
		(China)	-	1(dust)	2.5
				0.2(fume)	0.6
LEAD	*	7439-92-1/231-100-4			
		(US)	0.05	0.05	-
		(EU)	-	0.15	-
		(Canada)	-	0.05	-
		(Singapore)	0.15	-	-
		(Mexico)	-	0.15	-
		(China)	-	0.05(dust)	-
			-	0.03(fume)	-
ANTIMONY	*	7440-36-0/231-146-5			
		(US)	0.5	0.5	-
		(EU)	0.5	-	-
		(Canada)	N.E.	0.5	1.5

SDS - 6	249
---------	-----

SDS – 6249		INDA	LLOY WITH INDIUM 3.2	?HFA		
		(Singapore)	0.5	-	-	
		(Mexico)	0.5	-	-	
		(China)	-	0.5	-	
POLYGLYCOL ETHER	5.0-6.0	67700-97-4	N.E.	N.E.	N.E.	
PROPRIETARY 5.0-9.0		-	N.E.	N.E.	N.E.	
N.E. = Not established						

### 4. FIRST AID MEASURES

**Eve Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

### 5. FIRE FIGHTING MEASURES

Flash Point: Not established. Method: Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established.

**Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Procedures: Firefighters must wear NIOSH approved self-contained breathing apparatus and

full protective clothing.

#### 6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose contaminated cloth rags or paper towels following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations. Wear personal protective equipment.

### 7. HANDLING AND STORAGE

Handling Precautions: Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. Do not touch or rub eyes until hands are washed.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product

label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Use only with production equipment (such as stencil printers and re-flow furnaces) with adequate ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components so that any permissible exposure limits are not exceeded. Exhaust ventilation is recommended when heating this product. When applicable, protect operators from potential lead fumes.

## Personal protection:

**Eyes:** Chemical safety glasses/goggles. Face shield for any splash hazards.

**Respirator:** An authority approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.

**Skin:** Compatible chemical resistant gloves. Latex gloves are not recommended.

**Other:** Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

**Work/Hygienic Practices:** Maintain good housekeeping. Clean up spills immediately. Do not allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Grey colored paste.Boiling Point:Not applicable.Odor:Mild characteristic odor.Melting Point:Not applicableSpecific Gravity:1.1 g/cc (flux)pH:4 -8 (flux)

Vapor Pressure: Not applicable. Solubility in Water: Insoluble (paste)

Vapor Density: (air=1) Not applicable.

#### 10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Not established.

**Incompatible Materials:** Avoid contact with acids, bases or oxidizing agents.

Hazardous Decomposition / Combustion: Harmful organic fumes and toxic oxide fumes may form at elevated

temperatures.

Hazardous Polymerization: Will not occur.

# 11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

OSHA: No IARC: No

LD50: Not established. LC50: Not established.

RTECS: OF7525000 (lead)

Lead

reproductive toxicity – rat –inhalation reproductive toxicity – rat – oral reproductive toxicity – mouse-oral

Teratogencity

Developmental toxicity – rat- inhalation

Developmental toxicity- rat- oral

Suspected human reproductive toxicant

GHS- Specific target organ toxicity- repeated exposure

May cause damage to organs through prolonged or repeated exposure

Lead- OSHA Hazards- carcinogen/target organ effect/harmful by ingestion/teratogen.

## 12. ECOLOGICAL INFORMATION

Product not tested.

. Lead:

Toxicity to fish:

Rainbow trout- 1.19mg/l-96h

LC50 micropterus dolomieui- 2.2 mg/l-96h

Mortality NOEC-salvelinus fontinalis-1.7 mg/l-10d

Toxicity to algae

Mortality EC50-skeletonema costatum-7.94mg/l-10d

An environmental hazard cannot be excluded in the event of unprofessional handling, use and or disposal of this product.

May contain a substance (lead) that is very toxic to aquatic life with long lasting effects.

# 13. DISPOSAL CONSIDERATION

**Waste Disposal Method:** Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the waste assessment rules.

### 14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements. Not regulated under US DOT (United States Department of Transportation). Non hazardous under shipping requirements.

North American Emergency Guide Book - Not Classified

UN - none

#### 15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

WARNING: This product can expose you to chemicals including [lead, trace amounts of propylene oxide] which are known to the State of California to cause cancer and [lead] which can cause birth defects or other reproductive harm. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

SARA 313 Listing - 40 CFR 372.65
Silver Copper 3.5% Proprietary glycol ether

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified in accordance with the Mexican guidelines, NOM-018-STPS-2015 and NOM-010-STPS-2014.

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products

GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007.

All ingredients are listed on the Korean Existing Chemical Inventory.

# %Metal mix with flux (85-90%)

INDALLOY (METAL MIX)	%COPPER Cu	%TIN Sn	%SILVER Ag	%LEAD Pb	%ANTIMONY Sb	*RoHS 2/3 Compliance
106 (Sn63/Pb37)	-	53.6-56.7	-	30.6-33	-	No
133 (95Sn/5Sb)	-	80.8-85.5	-	-	4.25-4.5	Yes
241 (SAC387) (95.5Sn/3.8Ag/0.7Cu)	0.6-0.63	81-85.9	3.2-3.42	-	-	Yes
256 (SAC305) (96.5Sn/3Ag/0.5Cu)	0.425-0.45	82-86.9	2.55-2.7	-	-	Yes
96Sn/4Ag	-	81.6-86.4	3.4-3.6	-	-	Yes
99.3 Sn/0.7 Cu	0.6-0.63	84.4-89.4	_	-	_	Yes

<sup>\*</sup>RoHS 2- (2011/65/EU)

## **16. OTHER INFORMATION**

HMIS Hazard Rating: Health: 2

Fire: 1
Physical Hazard: 0

Revised Date: 6 AUGUST 2018

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

<sup>\*</sup>RoHS 3- products do not contain any listed phthalates