



THE INDIUM CORPORATION OF AMERICA®\EUROPE®\ASIA-PACIFIC®
INDIUM CORPORATION (SUZHOU)®

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier: INDALLOY WITH INDIUM 8.9HFA FLUX VEHICLE

SDS Number: MSDS-5050X

Revised Date: 19 MARCH 2014

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product Use: Industrial Use (Mixture) - Solder paste consisting of a flux vehicle blended with 83 - 92 weight percent pre-alloyed metal powder used for soldering applications. Review alloy table for exact product identification. Note: this SDS covers various metal mixtures using the same flux.

See alloy table for listing of products included under this SDS.

1.3 Details of the supplier of the safety data sheet

MANUFACTURER/SUPPLIER/IMPORTER:

In America:

The Indium Corporation of America
1676 Lincoln Ave., Utica NY 13502
Technical & Safety Information: (315) 853-4900 (8AM-5PM, EST)
Safety & SDS Information: nswarts@indium.com
Corporation web page: <http://www.indium.com>

In Europe:

Indium Corporation of Europe
7 Newmarket Ct.
Kingston, Milton Keynes, UK, MK 10 OAG
Information: (normal business hours) +44 [0] 1908 580400
EU Contact: aday@indium.com

In China:

Indium Corporation (Suzhou) Co., Ltd.
 No. 428 Xinglong Street
 Suzhou Industrial Park
 Suchun Industrial Square
 Unit No. 14-C
 Jiangsu Province, China 215126

Information: (86) 512-6283-4900

In Asia:

Indium Corporation of America
 Asia-Pacific Operations-Singapore
 29 Kian Teck Avenue
 Singapore 628908
 Information: +65 6268-8678

1.4 Emergency telephone number

FOR CHEMICAL EMERGENCY ONLY PHONE *:

CHEMTREC 24 hrs.

USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

*** Used only for spill/leak/fire/exposure/accident**

ALL OTHER INQUIRIES: TOLL FREE: +1-800-448-9240 Indium Corporation

SECTION 2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Eye Inhalation Skin Ingestion

Carcinogen listed in

NTP IARC OSHA Not Listed

2.1 Classification of the substance or mixture

Risk Phrases:

Symbol Xi R36/37/38, R42/43

2.2 Label elements

Labeling according to Regulation (EC) No. 1272/2008

General GHS:



Signal Word: Warning

Hazard statement(s)

H315 Causes skin irritation
 H317 May cause an allergic skin reaction
 H319 Causes serious eye irritation

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
EUH208	Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233	Keep container tightly closed
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P362	Take off contaminated clothing and wash before reuse
P301 + P314	IF SWALLOWED: Get Medical advice/attention if you feel unwell
P302 +P352	IF ON SKIN: Wash with plenty of soap and water
P304 + 341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + 351	IF IN EYES: Rinse continuously with water for several minutes (15 mins)

2.3 OTHER HAZARDS:**POTENTIAL HEALTH EFFECTS:**

Eye Contact: Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause severe eye irritation.

Ingestion: Irritating to digestive tract. May cause burns.

Inhalation: Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to the respiratory system. Rosin may cause occupational asthma.

Skin Contact: May cause skin irritation or dermatitis. Rosin may cause skin sensitization.

Chronic: SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Has been shown to increase incidence of sarcoma in animal tests.

COPPER: Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS**3.2 Mixture:**

Components	% wt	CAS Registry #/ EINECS#	
TIN	*	7440-31-5/231-141-8	[R36/37] [S26/S37/39]
SILVER	*	7440-22-4/231-131-3	[S24/25]

COPPER	*	7440-50-8 /231-159-6	[R36/37/38] [S26,S37/39]
ANTIMONY	*	7440-36-0/231-146-5	R20/22), R51/53]
BISMUTH	*	7440-69-9/231-177-4	[S23/S39]
ROSIN	4.0-7.0	65997-05-9	[R42/43] [S23, S24, S28, S36/37/39]
POLYGLYCOL ETHER	3.0 – 5.0	9038-95-3	[R36/37/38]
PROPRIETARY (NON CLASSIFIED/NON HAZARDOUS) ACTIVATORS	1.0 - 6.0	-	[R36/37/38]

**THIS PRODUCT DOES NOT CONTAIN ANY REPORTABLE EU REPORTABLE SUBSTANCES OF VERY HIGH CONCERN (SVHC).
THIS PRODUCT DOES NOT CONTAIN ANY PFOS/PFOA SUBSTANCES.**

N.E. = Not established

* See Alloy Table for breakdown of percentages of alloy mixtures

<http://www.indium.com>

ALLOY TABLE

%Metal mixed with flux

INDALLOY (METAL)	%COPPER Cu	%TIN Sn	%SILVER Ag	%ANTIMONY Sb	%BISMUTH Bi	^RoHS 2 Compliance
121 (96.5Sn/3.5Ag)	-	80-88.8	2.9-3.2	-	-	Yes
133 (95Sn/5Sb)	-	79-87	-	4.2-4.6	-	Yes
241 (SAC387) (95.5Sn/3.8Ag/0.7Cu)	0.58-0.64	79.2-87.9	3.2-3.5	-	-	Yes
256 (SAC 305) (96.5Sn/3Ag/ 0.5Cu)	0.42-0.46	80.1-88.8	2.5-2.8	-	-	Yes
258 (SAC105) (98.5Sn/1Ag/0.5Cu)) Doped with Mn 100-500 ppm	81.8-90.6	0.83-0.92	0.42-0.46	-	-	Yes
259	74.7-82.8	-	-	8.3-9.2	-	Yes

90Sn/10Sb						
263 (SAC0307) (99Sn/0.3Ag/0.7Cu)	82-91	0.25-0.28	0.58-0.64	-	-	Yes
Non Standard Alloy Mix 99.2Sn/0.5Cu/0.3Bi	82.3-91.3	-	0.42-0.46	-	0.25-0.28	Yes

^RoHS 2 = Restriction of Hazardous Substances (2011/65/EU)

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures:

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

4.2 Most important symptoms and effect, both acute and delayed:

Skin contact may cause irritation. Long term contact may cause dermatitis.
Inhalation of decomposed rosin fume may cause irritation or occupational asthma.
Exposure to metal fumes may cause irritation to the respiratory system.
Exposure can cause eye irritation and can cause serious irritation especially during fuming.

4.3 Indication of any immediate medical attention and special treatment needed:

No specific special treatment information is available on this mixture. Review data provided in this document to understand the hazards when working with the product. No other information is available at this time.

SECTION 5. FIRE FIGHTING MEASURES

- 5.1 Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions. Water, CO2, foam media.
- 5.2 Special hazards arising from the substance or mixture:**
May produce toxic fumes of carbon monoxide if burning or metal oxide fumes.
- 5.3 Advice for Firefighters** Firefighters must wear approved self-contained breathing apparatus and full protective clothing.

Material product is not flammable. No other information is available.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Keep away from the spill. Remove sources of ignition. Keep exhaust ventilation system running. In the event of a fire evacuate area.

For emergency responders:

Wear safety glasses, gloves when cleaning up any spill. Other equipment may be necessary based on the immediate area and other chemicals unrelated to the product that may be in use. Adequate ventilation should be available. Keep unnecessary personnel away from area during clean up.

6.2 Environmental Precautions: Dispose contaminated cloth rags or paper towels following all applicable governmental regulations. Material may have reclaim value. Material is non - hazardous. It however does contain metals and organic chemicals which may not be suited for release to any body of water including drains.

6.3 Methods and material for containment and cleaning up:

Spill or leak procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol.

6.4 Reference to other sections: See Section 8 for exposure levels.

SECTION 7. HANDLING AND STORAGE

7.1 Precautions For Safe Handling:

Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed. Do not eat, drink or smoke when handling this product. Utilize exhaust ventilation when heating product. Emissions may contain metal fumes, rosin and organic compounds.

7.2 Conditions for Safe Storage, including any incompatibilities:

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product label and product data sheet for specific storage temperature requirements. Rotate stock to ensure use before expiration date.

7.3 Specific End Use(s): Soldering applications

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters:

		<u>TWA</u>	<u>STEL</u>
	<u>CAS#/EINECS#</u>	mg/m3	mg/m3
TIN	* 7440-31-5/231-141-8		
	(UK)	2	4
	(Belgium)	2	-
	(Germany)	2	-

		(Netherlands)	2	-
		(Spain)	2	-
		(Poland)	2	-
SILVER	*	7440-22-4/231-131-3		
		(UK)	0.1	0.3
		(Belgium)	0.1	-
		(France)	0.1	-
		(Germany)	0.1	-
		(Netherlands)	0.1	-
		(Spain)	0.1	-
		(Poland)	0.05	-
COPPER	*	7440-50-8 /231-159-6		
		(UK)	0.2 (fume)	0.6(fume)
		(France)	2	0.2(fume)
		(Belgium)	1	-
			0.2(fume)	
		(Spain)	1	-
			0.2(fume)	
		(Portugal)	1	0.2(fume)
		(Netherlands)	0.1	-
		(Finland)	1	-
			0.1	
		(Denmark)	1	-
			0.1	
		(Austria)	1	4
			0.1(fume)	0.4
		(Switzerland)	0.1	0.2
		(Norway)	1	0.1
		(Ireland)	1	2
			0.2 (fume)	
		(Poland)	0.2	-
ANTIMONY	*	7440-36-0/231-146-5		
		(UK)	0.5	-

		(France)	0.5	-
		(Belgium)	0.5	-
		(Spain)	0.5	-
		(Portugal)	0.5	-
		(The Netherlands)	0.5	-
		(Finland)	0.5	-
		(Denmark)	0.5	-
		(Austria)	0.5	5
		(Switzerland)	0.5	-
		(Poland)	0.5	-
		(Norway)	0.5	-
		(Ireland)	0.5	-
ROSIN	4.0-7.0	65997-05-9		
		(EU)	0.05	N.E. 0.15 (sensitiser)

POLYGLYCOL ETHER	3.0 – 5.0	9038-95-3	N.E.	N.E.	N.E.
PROPRIETARY ACTIVATORS	1.0 - 6.0	-	N.E.	N.E.	N.E.

N.E. = Not established

TWA = time weighted average
STEL = short term exposure limit.

8.2 Exposure Controls:

Engineering Controls: Use only with production equipment (stencil printers and re-flow furnaces) with adequate exhaust ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components with established exposure limits so they are not exceeded. Use exhaust ventilation when heating product. Air emission control equipment may be necessary based on the local governmental requirements for contaminants entering the atmosphere. Emissions may contain metal fume, rosin and organic compounds.

Personal protection:

- Eyes:** Chemical safety glasses/goggles. Face shield for splash hazards.
- Respiratory:** An approved or EU compliant CE marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.
- Skin:** Compatible chemical resistant gloves. Recommend a nitrile disposable or other chemical glove.
- Other:** Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.
- Work/Hygienic** Maintain good housekeeping. Clean up spills immediately. Do not allow rags or

Practices: paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.
Wash hands thoroughly with soap and water immediately upon leaving the work area.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:	Grey colored solid paste	Boiling Point/Range:	Not determined
Odor:	Mild characteristic odor.	Melting Point/Freezing Point:	Not applicable
Odor Threshold:	Not established	Evaporation Rate:	Not applicable
Specific Gravity:	1 g/cc	pH:	4 – 8 (flux)
Vapour Pressure:	Not applicable.	Solubility in Water:	Insoluble (paste)
Vapour Density:	(air=1) Not applicable.	Partition coefficient:	Not established
Relative Density:	Not established	Flammability:	Not applicable, not flammable
Flash Point:	Not applicable	Method:	Not applicable
Auto-ignition Temperature:	Not applicable	Flammable Limits:	Limits not established
UEL/LEL Limits:	Not applicable	Decomposition Temp:	Not applicable
Viscosity:	Not established	Explosive properties:	Not applicable
Oxidizing Properties:	Not established		

Other Information: Above data for the whole mixture.

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity: Stable.

10.2 Chemical Stability: Stable

10.3 Possibility of Hazardous Reactions: Not established

10.4 Conditions To Avoid: None known

10.5 Incompatible Materials: Avoid contact with acids, bases or oxidizing agents.

10.6 Hazardous Decomposition / Combustion: Harmful organic fumes and toxic oxide fumes may form at elevated temperatures. Metal oxide fumes.

Hazardous Polymerization: Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

<u>Acute toxicity:</u>	Not established	<u>Mutagenicity:</u>	Not established
<u>Irritation:</u>	Not established	<u>Toxicity for Reproduction:</u>	Not Established
<u>Corrosivity:</u>	Not applicable	<u>Absence of specific data:</u>	None available (not tested)
<u>Sensitization:</u>	Not available		
<u>Repeated dose toxicity:</u>	Not established		
<u>Carcinogenicity:</u>	Not established		

Likely Routes of Entry: eyes (irritation) /skin (irritation or sensitization) /inhalation (irritation/sensitization) ingestion (may be harmful)

Interactive effects: None known

Symptoms related to the physical, chemical and toxicological characteristics:

May cause irritation or sensitization by skin and inhalation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Exposure to rosin fume has been known to cause occupational asthma.

Mixture verses substance information: None known

Other Information:

Carcinogenicity: NTP: No (National Toxicity Program)

Listing OSHA: No (US Occupational Safety & Health Administration)

IARC: No (International Agency for Research on Cancer)

Copper - LD50 – intraperitoneal mouse 3.5 mg/kg.

Silver – LD50 oral – rat > 5,000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Product mixtures not tested.

12.1 Toxicity: No information available

12.2 Persistence and degradability: No information available

12.3 Bioaccumulative potential: No information available

12.4 Mobility in soil: No information available

12.5 Results of PBT and vPvB assessments: No data is available

12.6 Other adverse effects: No information is available for mixture. Avoid release to environment.

Copper – Toxicity to daphnia and other aquatic invertebrate's mortality NOEC – Daphnia 0.004 mg/l – 24h.

SECTION 13. DISPOSAL CONSIDERATION

13.1 Waste treatment method: Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with environmental regulations. Containerize material and classify according to applicable regulations. No pre-treatment on site is recommended. Do not dispose of down any drain or waterway. Utilize the same personal protective equipment as the user when handling for disposal.

RoHS (Restriction of Hazardous Substances): product mixtures are RoHS compliant because they are lead free. Product mixtures do not contain any PBB or PBDT brominated compounds. Review alloy table for products.

SECTION 14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.
 Solder Paste is non - hazardous.
 Not regulated/non - hazardous under US DOT (United States Department of Transportation).
 Not regulated/non - hazardous under international shipping requirements.

- 14.1 UN number** None
14.2 UN proper shipping name: None
14.3 Transport hazard class(s): None
14.4 Packing group: None
14.5 Environmental hazards: None
14.6 Special precautions for user: None
- Transport in bulk:** Not applicable

SECTION 15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

All ingredients are listed on the USEPA TSCA Inventory.

All ingredients are listed on EINECS. Note Rosin was recently listed under the No Longer Polymer List, Notification of New Chemical Substances in Accordance with Directive 67/548/EEC.

Safety data sheet was developed using EC 1907/2006 amended as of 20 May 2010 EU No 453/2010 and information as stated under regulation EC No 1272/2008 CLP Regulation.

GHS = Global Harmonized System

CLP= Classification, labeling and packaging

Product does not contain any substances ozone depleting substances and therefore not subject to EC 2037/2000.

15.2 Chemical safety assessment: None performed for mixture.

SECTION 16. OTHER INFORMATION

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

Risk Phrases:

- R42/43 May cause sensitization by inhalation or by skin contact
 R36/37/38 Irritating to eyes, respiratory system and skin
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment (antimony)

Safety Phrases:

- S20/21 When using do not eat, drink or smoke

- | | |
|-----------|--|
| S23 | Do not breathe fumes |
| S24/25 | Avoid contact with skin and eyes |
| S27 | Take off immediately all contaminated clothing |
| S28 | After contact with skin wash immediately with plenty of soap and water |
| S36/37/39 | Wear suitable protective clothing, gloves and eye/face protection |
| S7 | Keep container tightly closed |

Revised Date: 19 MARCH 2014

Prepared by: Nancy Swarts, The Indium Corporation of America, nswarts@indium.com

Approved by: Nancy Swarts, The Indium Corporation of America

Changes provided on this SDS were based on the requirements of EU No. 453/2010 of May 20, 2010 regarding amendments to EC No. 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.