



THE INDIUM CORPORATION OF AMERICA®\EUROPE®\ASIA-PACIFIC®  
INDIUM CORPORATION (SUZHOU)®

## SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product Identifier:** INDALLOY WITH INDIUM 5.5LT FLUX VEHICLE

**SDS Number:** SDS-4677

**Revised Date:** 20 SEPTEMBER 2013

**Product Use:** Industrial Use (Mixture) - Solder paste consisting of a flux vehicle blended with 83-92 weight percent pre-alloyed metal powder used for soldering applications. Review alloy table for exact product identification. Note: this SDS covers various metal mixtures using the same flux.

See alloy table for listing of products included under this SDS.

**FOR CHEMICAL EMERGENCY ONLY PHONE \*:**

**CHEMTREC 24 hrs.**

**USA: 1 (800) 424-9300**

**Outside USA: +1 (703) 527-3887**

**\* Used only for spill/leak/fire/exposure/accident**

**ALL OTHER INQUIRIES: TOLL FREE: +1-800-448-9240 Indium Corporation**

**MANUFACTURER/SUPPLIER/IMPORTER:**

**In America:**

The Indium Corporation of America  
1676 Lincoln Ave., Utica NY 13502  
Technical & Safety Information: (315) 853-4900  
Safety & SDS Information: [nswarts@indium.com](mailto:nswarts@indium.com)  
Corporation web page: <http://www.indium.com>

**In Europe:**

Indium Corporation of Europe  
7 Newmarket Ct.  
Kingston, Milton Keynes, UK, MK 10 OAG  
Information: (normal business hours) +44 [0] 1908 580400  
EU Contact: [aday@indium.com](mailto:aday@indium.com)

**In China:**

Indium Corporation (Suzhou) Co., Ltd.  
 No. 428 Xinglong Street  
 Suzhou Industrial Park  
 Suchun Industrial Square  
 Unit No. 14-C  
 Jiangsu Province, China 215126  
 Information: (86) 512-6283-4900

**In Asia:**

The Indium Corporation of America  
 Asia-Pacific Operations-Singapore  
 29 Kian Teck Avenue  
 Singapore 628908  
 Information: +65 6268-8678

**2. HAZARDS IDENTIFICATION****PRIMARY ROUTES OF ENTRY:**

Eye    Inhalation    Skin    Ingestion    NTP    IARC    OSHA    Not Listed

**Carcinogen listed in****Classification:**

Risk Phrases:

General listing: R20/21/22, R36/37/38, R42/43, R33, R40, R48, R61, R50/53

General GHS:



lead containing products

Signal Word: Warning

**Hazard statement(s)**

H303            May be harmful if swallowed  
 H315            Causes skin irritation  
 H317            May cause an allergic skin reaction  
 H319            Causes serious eye irritation  
 H334            May cause allergy or asthma symptoms or breathing difficulties if inhaled  
 H335            May cause respiratory irritation  
 H332            Harmful if inhaled  
 H351            Suspected of causing cancer (lead)  
 H360            May damage fertility or the unborn child (applicable to lead containing product)  
 H373            May cause damage to organs through prolonged or repeated exposure (applicable to lead containing product)  
 H412            Harmful to aquatic life with long lasting harmful effects  
 EUH208        Contains rosin. May produce an allergic reaction  
 EUH201A      Warning! Contains lead (applicable only to the products listed that contain lead) Review listing.

**Precautionary statement(s)**

P233	Keep container tightly closed
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P362	Take off contaminated clothing and wash before reuse
P301 + P314	IF SWALLOWED: Get Medical advice/attention if you feel unwell
P302 +P352	IF ON SKIN: Wash with plenty of soap and water
P304 + 341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + 351	IF IN EYES: Rinse continuously with water for several minutes (15 mins)

**OTHER HAZARDS:****POTENTIAL HEALTH EFFECTS:**

- Eye Contact:** Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause eye irritation.
- Ingestion:** This product contains metal alloy powders and organic chemicals. May be harmful if swallowed. May cause burns to the digestive tract and systematic effects.
- Inhalation:** Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to the respiratory system. Harmful if inhaled. Rosin may cause occupational asthma.
- Skin Contact:** May cause skin irritation or dermatitis. Rosin may cause skin sensitization.
- Chronic:** SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.
- TIN: Has been shown to increase incidence of sarcoma in animal tests.
- BISMUTH: May cause kidney damage.
- LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.
- INDIUM: May cause damage to respiratory system.

**3. COMPOSITION / INFORMATION ON INGREDIENTS****3.2 Mixture:**

Components	% wt	CAS Registry #/ EINECS#	
TIN	*	7440-31-5/231-141-8	[R36/37] [S26/S37/39]

SILVER	*	7440-22-4/231-131-3	[S24/25]
BISMUTH	*	7440-69-9/231-177-4	[S23/S39]
LEAD	*	7439-92-1/231-100-4	[R20/22, R33, R40, R48, R61, R52/53] [S45, S53, S61]
INDIUM	*	7440-74-6/231-180-0	[R20,R36/37/38]
ROSIN	4.0-8.0	65997-05-9	[R42/43]
POLYGLYCOL ETHER	3.0-6.0	9038-95-3	[S37/39]
PROPRIETARY (NON CLASSIFIED/NON HAZARDOUS)	3.0 - 5.0	-	

**THIS PRODUCT DOES NOT CONTAIN ANY EU REPORTABLE SUBSTANCES OF VERY HIGH CONCERN (SVHC)**

N.E. = Not established

\* See Alloy Table for breakdown of percentages of alloy mixtures

<http://www.indium.com>

## 4. FIRST AID MEASURES

### Description of first aid measures:

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

### Most important symptoms and effect, both acute and delayed:

Skin contact may cause irritation. Long term contact may cause dermatitis.  
Inhalation of decomposed rosin fume may cause irritation or occupational asthma.  
Exposure to metal fumes may cause irritation to the respiratory system. Long term exposure by inhalation to metal fumes may cause illness such as metal fume fever.

### Indication of any immediate medical attention and special treatment needed:

No specific special treatment information is available on this mixture. Review data provided in this document to understand the hazards when working with the product. No other information is available at this time.

## 5. FIRE FIGHTING MEASURES

**Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions. Water, CO2, foam

media.

**Special hazards arising from the substance or mixture:**

May produce toxic fumes of carbon monoxide if burning or metal oxide fumes.

**Advice for Firefighters**

Firefighters must wear approved self-contained breathing apparatus and full protective clothing.

Material product is not flammable. No other information is available.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Keep away from the spill. Remove sources of ignition. Keep exhaust ventilation system running. In the event of a fire evacuate area.

**For emergency responders:**

Wear safety glasses, gloves when cleaning up any spill. Other equipment may be necessary based on the immediate area and other chemicals unrelated to the product that may be in use. Adequate ventilation should be available. Keep unnecessary personnel away from area during clean up.

**Environmental Precautions:** Dispose contaminated cloth rags or paper towels following all applicable governmental regulations. Material may have reclaim value. Material is non - hazardous. It however does contain metals and organic chemicals which may not be suited for release to any body of water including drains.

**Methods and material for containment and cleaning up:**

Spill or leak procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol.

**Reference to other sections:** See Section 8 for exposure levels.

## 7. HANDLING AND STORAGE

**Precautions**

**For Safe Handling:**

Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed. Do not eat, drink or smoke when handling this product. Utilize exhaust ventilation when heating product. Emissions may contain metal fumes, rosin and organic compounds.

**Conditions for Safe Storage, including any incompatibilities:**

**Storage Precautions:** Store product in tightly capped original containers in a cool, dry area. Refer to product label and product data sheet for specific storage temperature requirements. Rotate stock to ensure use before expiration date.

**Specific End Use(s):** Soldering applications

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Control Parameters:**

		<u>CAS#/EINECS#</u>	<u>TWA</u> mg/m3	<u>STEL</u> mg/m3
<b>TIN</b>	*	7440-31-5/231-141-8		
		(UK)	2	4
		(Belgium)	2	-
		(Germany)	2	-
		(Netherlands)	2	-
		(Spain)	2	-
		(Poland)	2	-
		(Finland)	2	-
<b>SILVER</b>	*	7440-22-4/231-131-3		
		(UK)	0.1	0.3
		(Belgium)	0.1	-
		(France)	0.1	-
		(Germany)	0.1	-
		(Netherlands)	0.1	-
		(Spain)	0.1	-
		(Poland)	0.05	-
<b>BISMUTH</b>	*	7440-69-9/231-177-4	N.E.	N.E.
<b>LEAD</b>	*	7439-92-1/231-100-4		
		(UK)	0.15	-
		(France)	0.1	-
		(Spain)	0.15	-
		(Italy)	0.15	-
		(Portugal)	0.05	-
	(Finland)	0.1	-	

			(Denmark)	0.05	-	
			(Austria)	0.1	0.4	
			(Switzerland)	0.1	0.8	
			(Poland)	0.05	-	
			(Norway)	0.05	-	
			(Ireland)	0.15	-	
<b>INDIUM</b>	*	7440-74-6/231-180-0				
			(UK)	0.1	0.3	
			(Belgium)	0.1	-	
			(Spain)	0.1	-	
			(Portugal)	0.1	-	
			(Finland)	0.1	-	
			(Denmark)	0.1	-	
			(Austria)	0.1	0.2	
			(Switzerland)	0.1	-	
			(Norway)	0.1	-	
			(Ireland)	0.1	0.3	
<b>ROSIN</b>	4.0- 8.0	65997-05-9				
			(EU)	0.05	N.E.	0.15 (sensitiser)
<b>POLYGLYCOL ETHER</b>	3.0 – 6.0	9038-95-3		N.E.	N.E.	N.E.
<b>PROPRIETARY</b>	3.0 - 5.0	-		N.E.	N.E.	N.E.
N.E. = Not established		* See Alloy Table				
TWA = time weighted average						
STEL = short term exposure limit						
<b><u>Exposure Controls:</u></b>						
<b>Engineering Controls:</b> Use only with production equipment (stencil printers and re-flow furnaces) with adequate exhaust ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components with established exposure limits so they are not exceeded. Use exhaust ventilation when heating product. Air emission control equipment may be necessary based on the local governmental requirements for contaminants entering the atmosphere. Emissions may contain metal fume, rosin and organic compounds.						

**Personal protection:**

<b>Eyes:</b>	Chemical safety glasses/goggles. Face shield for splash hazards.
<b>Respiratory:</b>	An approved or EU compliant CE marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.
<b>Skin:</b>	Compatible chemical resistant gloves. Recommend a nitril disposable or other chemical glove.
<b>Other:</b>	Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.
<b>Work/Hygienic Practices:</b>	Maintain good housekeeping. Clean up spills immediately. Do not allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area. Follow standard lead work practices, if applicable.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties:**

<b>Appearance:</b>	Grey colored solid paste	<b>Boiling Point/Range:</b>	Not determined
<b>Odor:</b>	Mild characteristic odor.	<b>Melting Point/Freezing Point:</b>	Not applicable
<b>Odor Threshold:</b>	Not established	<b>Evaporation Rate:</b>	Not applicable
<b>Specific Gravity:</b>	Not applicable.	<b>pH:</b>	Not applicable
<b>Vapour Pressure:</b>	Not applicable.	<b>Solubility in Water:</b>	Insoluble (paste)
<b>Vapour Density:</b>	(air=1) Not applicable.	<b>Partition coefficient:</b>	Not established
<b>Relative Density:</b>	Not established	<b>Flammability:</b>	Not applicable
<b>Flash Point:</b>	Not applicable	<b>Method:</b>	Not applicable
<b>Auto-ignition Temperature:</b>	Not applicable	<b>Flammable Limits:</b>	Limits not established
<b>UEL/LEL Limits:</b>	Not applicable	<b>Decomposition Temp:</b>	Not applicable
<b>Viscosity:</b>	Not established	<b>Explosive properties:</b>	Not applicable
<b>Oxidizing Properties:</b>	Not established		

**Other Information:** Above data for the whole mixture.

**10. STABILITY AND REACTIVITY**

<b><u>Reactivity:</u></b>	Stable.
<b><u>Chemical Stability:</u></b>	Stable
<b><u>Possibility of Hazardous Reactions:</u></b>	Not established
<b><u>Conditions To Avoid:</u></b>	None known
<b><u>Incompatible Materials:</u></b>	Avoid contact with acids, bases or oxidizing agents.
<b><u>Hazardous Decomposition / Combustion:</u></b>	Harmful organic fumes and toxic oxide fumes may form at elevated temperatures. Metal oxide fumes.
<b><u>Hazardous Polymerization:</u></b>	Will not occur.



## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects:

<b>Acute toxicity:</b>	Not established	<b>Mutagenicity:</b>	Not established
<b>Irritation:</b>	Not established	<b>Toxicity for Reproduction:</b>	Not Established
<b>Corrosivity:</b>	Not applicable	<b>Absence of specific data:</b>	None available (not tested)
<b>Sensitization:</b>	Not available		

**Repeated dose toxicity:** Not established

**Carcinogenicity:** Not established

**Likely Routes of Entry:** eyes (irritation) /skin (irritation or sensitization) /inhalation (irritation/sensitization) ingestion (may be harmful)

**Interactive effects:** None known

### Symptoms related to the physical, chemical and toxicological characteristics:

May cause irritation or sensitization by skin and inhalation.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Exposure to rosin fume has been known to cause occupational asthma.

**Mixture verses substance information:** None known

### Other Information:

**Carcinogenicity:** NTP: No (National Toxicity Program)

**Listing** OSHA: No (US Occupational Safety & Health Administration)

IARC: Yes - Lead and lead compounds are listed as possible carcinogens. (International Agency for Research on Cancer).

Silver – LD50 oral – rat > 5,000 mg/kg

Bismuth – LD50 oral-rat 5,000 mg/kg

## 12. ECOLOGICAL INFORMATION

This section is subject to future development. Product mixtures not tested.

**Toxicity:** No information available

**Persistence and degradability:** No information available

**Bioaccumulative potential:** No information available

**Mobility in soil:** No information available

**Results of PBT and vPvB assessments:** No data is available

**Other adverse effects:** No information is available for mixture. Avoid release to environment.

### 13. DISPOSAL CONSIDERATION

**Waste treatment method:** Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with environmental regulations. Containerize material and classify according to applicable regulations. No pre-treatment on site is recommended. Do not dispose of down any drain or waterway. Utilize the same personal protective equipment as the user when handling for disposal.

**RoHS (Restriction of Hazardous Substances):** some of the product mixtures are RoHS compliant because they are lead free. Product mixtures do not contain any PBB or PBDT brominated compounds.  
RoHS – Note that some of the product mixtures do contain lead and are therefore not complaint with RoHS. Users should review their particular use for any applicable exemptions that may apply. Review alloy table for products. Follow waste assessment rules for categorizing the waste.

### 14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

Solder Paste is non - hazardous.

Not regulated/non - hazardous under US DOT (United States Department of Transportation).

Not regulated/non - hazardous under international shipping requirements.

**UN proper shipping name:** None

**Transport hazard class(s):** None

**Packing group:** None

**Environmental hazards:** None

**Special precautions for user:** None

**Transport in bulk:** Not applicable

### 15. REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture:**

The information in this Material Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

All ingredients are listed on the USEPA TSCA Inventory.

All ingredients are listed on EINECS. Note Rosin was recently listed under the No Longer Polymer List, Notification of New Chemical Substances in Accordance with Directive 67/548/EEC.

Safety data sheet was developed using EC 1907/2006 amended as of 20 May 2010 EU No 453/2010 and information as stated under regulation EC No 1272/2008 CLP Regulation.

GHS = Global Harmonized System

CLP= Classification, labeling and packaging

Product does not contain any substances ozone depleting substances and therefore not subject to EC 2037/2000.

**Chemical safety assessment:** None performed for mixture.

## 16. OTHER INFORMATION

**NOTE:** The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

### Risk Phrases:

- R42/43 May cause sensitization by inhalation or by skin contact  
R36/37/38 Irritating to eyes, respiratory system and skin  
R20/21/22 Harmful by inhalation in contact with skin and if swallowed  
R33 Danger of cumulative effects (lead)  
R40 Limited evidence of carcinogenic effect (lead)  
R48 Danger of serious damage to health by prolonged exposure (lead)  
R61 May cause harm to the unborn child (lead)  
R50/53 Very toxic to aquatic organisms and may cause long-term effects in the aquatic environment

### Safety Phrases:

- S20/21 When using do not eat, drink or smoke  
S23 Do not breathe fumes  
S24/25 Avoid contact with skin and eyes  
S27 Take off immediately all contaminated clothing  
S28 After contact with skin wash immediately with plenty of soap and water  
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection  
S45 In case of accident or if feel unwell seek medical advice immediately  
S53 Avoid exposure  
S7 Keep container tightly closed  
S61 Avoid release to environment

**Revised Date:** 20 SEPTEMBER 2013

**Prepared by:** Nancy Swarts, The Indium Corporation of America, nswarts@indium.com

**Approved by:** Nancy Swarts, The Indium Corporation of America

Changes provided on this SDS were based on the requirements of EU No. 453/2010 of May 20, 2010 regarding amendments to EC No. 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

**ALLOY TABLE**

## Metal mixed with flux

<b>Indalloy (metal mixture)</b>	<b>%TIN Sn</b>	<b>%BISMUTH Bi</b>	<b>%LEAD Pb</b>	<b>%SILVER Ag</b>	<b>%INDIUM In</b>	<b>RoHS Compliance</b>
42 (46Bi/34Sn/20Pb)	28-31	38.2-42	16.6-18.4	-	-	NO
53 (67Bi/33In)	-	55.6-61.6	-	-	27.4-30.4	YES
281 (58Bi/42Sn)	34.9-38.6	48.1-53.4	-	-	-	YES
282 (57Bi/42Sn/1Ag)	34.9-38.6	47-52	-	0.83-0.92	-	YES