



## SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**1.1 Product Identifier:** INDALLOY WITH RMA-SMQ51/A/C/AC AND NC-SMQ51S/C/SC FLUX VEHICLE

**SDS Number:** SDS-IN 282

**Revised Date:** 22 NOVEMBER 2019

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product Use:** Industrial Use (Mixture) - Solder paste consisting of a flux vehicle blended with 83-92 weight percent pre-alloyed metal powder used for soldering applications. Review alloy table for exact product identification. Note: this SDS covers various metal mixtures using the same flux.

See alloy table for listing of products included under this SDS.

#### 1.3 Details of the supplier of the safety data sheet

##### MANUFACTURER/SUPPLIER/IMPORTER:

###### **In America:**

**The Indium Corporation of America®.**

34 Robinson Road, Clinton NY 13323

Technical & Safety Information: (315) 853-4900

Safety & SDS Information: [nswarts@indium.com](mailto:nswarts@indium.com)

Corporation web page: <http://www.indium.com>

###### **In Europe:**

**The Indium Corporation of America® (European Operations)**

7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG

Information: (normal business hours) +44 [0] 1908 580400

EU Contact: [aday@indium.com](mailto:aday@indium.com)

###### **In China:**

Indium Corporation (Suzhou) Co., Ltd.

No. 428 Xinglong Street

Suzhou Industrial Park

Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126

Information: (86) 512-6283-4900

###### **In Asia:**

The Indium Corporation of America

Asia-Pacific Operations-Singapore

29 Kian Teck Avenue

Singapore 628908

Information: +65 6268-8678

**1.4 Emergency telephone number****FOR CHEMICAL EMERGENCY ONLY PHONE \*:****CHEMTREC 24 hrs.****USA: 1 (800) 424-9300****Outside USA: +1 (703) 527-3887****China: Emergency 86+ 4008417580****\* Used only for spill/leak/fire/exposure/accident****ALL OTHER INQUIRIES: TOLL FREE: +1-800-448-9240 Indium Corporation****2. HAZARDS IDENTIFICATION****PRIMARY ROUTES OF ENTRY:** Eye Inhalation Skin Ingestion

NTP

**Carcinogen listed in**

IARC

OSHA

 Not Listed**2.1 Classification of the substance or mixture**

Review alloy table to determine which alloys are used in the particular product

**2.2 Label elements**

Labeling in accordance with Regulation (EC) No. 1272/2008

General GHS:

Lead Free Products



Signal Word: Warning

**Hazard statement(s)**

H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
EUH208	Contains rosin. May produce an allergic reaction

**Precautionary statement(s)**

P233	Keep container tightly closed
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P362 +P364	Take off contaminated clothing and wash before reuse
P302 +P352	IF ON SKIN: Wash with plenty of soap and water
P304 + 341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + 351	IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Lead Containing Products



Signal Word: Warning

Hazard statement(s)

H303	May be harmful if swallowed
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects
EUH201A	Warning! Contains lead. Review listing.
EUH208	Contains rosin. May produce an allergic reaction

Precautionary statement(s)

P233	Keep container tightly closed
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P362 +P364	Take off contaminated clothing and wash before reuse
P302 +P352	IF ON SKIN: Wash with plenty of soap and water
P304 + 341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + 351	IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification:

Specific target organ toxicity- repeated exposure – Category 2  
 Carcinogenicity (Category 2) (lead)  
 Reproductive toxicity (Category 2 ) (lead)  
 Skin sensitization – Category1B  
 Respiratory sensitization- Category1B  
 Acute aquatic toxicity – Category 1 for lead containing products  
 Chronic aquatic toxicity – Category 1 for lead containing products  
 For product containing both lead and antimony the Acute and Chronic Classification is (Category 2)

**2.3 OTHER HAZARDS:**

**POTENTIAL HEALTH EFFECTS:**

**Eye Contact:** Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause serious eye damage.

**Ingestion:** This product contains metal alloy powders and organic chemicals. May be harmful if swallowed.

**Inhalation:** Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to the respiratory system. May be harmful if inhaled. Rosin may cause occupational asthma.

**Skin Contact:** May cause skin irritation or dermatitis. Rosin and antimony may cause skin sensitization.

**Chronic:** SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

**TIN:** Has been shown to increase incidence of sarcoma in animal tests.

**LEAD:** Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys. Signs and symptoms of exposure – anemia. Possible carcinogenic to humans.

**INDIUM:** Harmful if inhaled, swallowed or in contact with skin. Indium may cause damage to respiratory system. Kidney and liver damage from injection of indium compounds has been reported based on limited animal testing.

**COPPER:** Over exposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever, dry throat, cough, weakness, lassitude) metallic or sweet taste; discoloration of skin and hair.

**ZINC:** Fresh fume inhaled may cause a disease known as “ brass founders”, throat dryness, cough, weakness, generalized aching, fever, nausea and vomiting.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

#### 3.2 Mixture:

Components	% wt	CAS Registry #/ EINECS#			
TIN	*	7440-31-5/231-141-8			
SILVER	*	7440-22-4/231-131-3			
INDIUM	*	7440-74-6/231-180-0			
LEAD	*	7439-92-1/231-100-4			
BISMUTH	*	7440-69-9/231-177-4			
ANTIMONY	*	7440-36-0/231-146-5			
COPPER	*	7440-50-8/231-159-6			
GOLD	*	7440-57-5/231-165-9			
GERMANIUM	*	7440-56-4/231-164-3			
ZINC	*	7440-66-6/231-175-3			
ROSIN	5.0- 6.0	65997-05-9			
POLYGLYCOL ETHER	2.0 -4.0	9038-95-3	N.E.	N.E.	N.E.
MODIFIED CASTER OIL	1.0 – 7.0	61788-85-0	N.E.	N.E.	N.E.

N.E. = Not established

\* See Alloy Table at the end of this document for a breakdown of percentages of alloy mixtures

### 4. FIRST AID MEASURES

**4.1 Description of first aid measures:**

**Eye Contact:** Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Causes eye damage therefore seek medical advice.

**Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.

**Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

**4.2 Most important symptoms and effect, both acute and delayed:**

Skin contact may cause irritation. Long term contact may cause dermatitis. Inhalation of decomposed rosin fume may cause irritation or occupational asthma. Exposure to metal fumes may cause irritation to the respiratory system. Long term exposure by inhalation to metal fumes may cause illness such as metal fume fever.

Exposure to lead fume may cause harm. Sign of overexposure is anemia. Signs or symptoms of over exposure to antimony is headache, vomiting, nausea or dizziness. Target organs (antimony) – heart and respiratory system.

**4.3 Indication of any immediate medical attention and special treatment needed:**

No specific special treatment information is available on this mixture. Review data provided in this document to understand the hazards when working with the product. No other information is available at this time.

**5. FIRE FIGHTING MEASURES**

**5.1 Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions. Water, CO2, foam media.

**5.2 Special hazards arising from the substance or mixture:**  
May produce toxic fumes of carbon monoxide if burning or metal oxide fumes.

**5.3 Advice for Firefighters** Fire fighters must wear approved self-contained breathing apparatus and full protective clothing.

Material product is not flammable. No other information is available.

**6. ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Keep away from the spill. Remove sources of ignition. Keep exhaust ventilation system running. In the event of a fire evacuate area.

**For emergency responders:**

Wear safety glasses, gloves when cleaning up any spill. Other equipment may be necessary based on the immediate area and other chemicals unrelated to the product that may be in use. Adequate ventilation should be available. Keep unnecessary personnel away from area during clean up.

**6.2 Environmental Precautions:** Dispose contaminated cloth rags or paper towels following all applicable governmental regulations. Material may have reclaim value. Material is non - hazardous. It however does contain metals and organic chemicals which may not be suited for release to any body of water including drains. Contains a substance that is harmful to aquatic life with long lasting effects.

**6.3 Methods and material for containment and cleaning up:**

Spill or leak procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol.

**6.4 Reference to other sections:** See Section 8 for exposure levels.

## 7. HANDLING AND STORAGE

### 7.1 Precautions For Safe Handling:

Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed. Do not eat, drink or smoke when handling this product. Utilize exhaust ventilation when heating product. Emissions may contain metal fumes, rosin and organic compounds.

### 7.2 Conditions for Safe Storage, including any incompatibilities:

**Storage Precautions:** Store product in tightly capped original containers in a cool, dry area. Refer to product label and product data sheet for specific storage temperature requirements. Rotate stock to ensure use before expiration date.

**7.3 Specific End Use(s):** Soldering applications

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control Parameters:

			<u>TWA</u>	<u>STEL</u>
		<u>CAS#/EINECS#</u>	mg/m <sup>3</sup>	mg/m <sup>3</sup>
<b>TIN</b>	*	7440-31-5/231-141-8		
		(UK)	2	4
		(Belgium)	2	-
		(Germany)	2	-
		(Netherlands)	2	-
		(Spain)	2	-
		(Poland)	2	-
<b>SILVER</b>	*	7440-22-4/231-131-3		
		(UK)	0.1	0.3
		(Belgium)	0.1	-
		(France)	0.1	-
		(Germany)	0.1	-
		(Netherlands)	0.1	-
		(Spain)	0.1	-
	(Poland)	0.05	-	

<b>INDIUM</b>	*	7440-74-6/231-180-0		
		(UK)	0.1	0.3
		(Belgium)	0.1	-
		(Spain)	0.1	-
		(Portugal)	0.1	-
		(Finland)	0.1	-
		(Denmark)	0.1	-
		(Austria)	0.1	0.2
		(Switzerland)	0.1	-
		(Norway)	0.1	-
		(Ireland)	0.1	0.3
<b>LEAD</b>	*	7439-92-1/231-100-4		
		(UK)	0.15	-
		(France)	0.1	-
		(Spain)	0.15	-
		(Italy)	0.15	-
		(Portugal)	0.05	-
		(Finland)	0.1	-
		(Denmark)	0.05	-
		(Austria)	0.1	0.4
		(Switzerland)	0.1	0.8
		(Poland)	0.05	-
		(Norway)	0.05	-
		(Ireland)	0.15	-
<b>BISMUTH</b>	*	7440-69-9/231-177-4		
		(UK)	N.E.	N.E.
<b>ANTIMONY</b>	*	7440-36-0/231-146-5		
		(UK)	0.5	-
		(France)	0.5	-
		(Belgium)	0.5	-
		(Spain)	0.5	-

			(Portugal)	0.5	-
			(The Netherlands)	0.5	-
			(Finland)	0.5	-
			(Denmark)	0.5	-
			(Austria)	0.5	5
			(Switzerland)	0.5	-
			(Poland)	0.5	-
			(Norway)	0.5	-
			(Ireland)	0.5	-
<b>ZINC</b>	*	7440-66-6/231-175-3	N.E.	N.E.	N.E.
<b>GOLD</b>	*	7440-57-5/231-165-9	N.E.	N.E.	N.E.
<b>GERMANIUM</b>	*	7440-56-4/231-164-3	N.E.	N.E.	N.E.
<b>COPPER</b>	*	7440-50-8 /231-159-6			
			(UK)	0.2 (fume)	0.6(fume)
			(France)	2	0.2(fume)
			(Belgium)	1	-
				0.2(fume)	
			(Spain)	1	-
				0.2(fume)	
			(Portugal)	1	0.2(fume)
			(Netherlands)	0.1	-
			(Finland)	1	-
				0.1	
			(Denmark)	1	-
				0.1	
			(Austria)	1	4
				0.1(fume)	0.4
			(Switzerland)	0.1	0.2
			(Norway)	1	0.1
			(Ireland)	1	2
				0.2 (fume)	
			(Poland)	0.2	-
<b>ROSIN</b>	5.0- 6.0	65997-05-9			



		(EU)	0.05	N.E.	0.15 (sensitiser)
<b>POLYGLYCOL ETHER</b>	2.0 -4.0	9038-95-3	N.E.	N.E.	N.E.
<b>MODIFIED CASTER OIL</b>	1.0 – 7.0	61788-85-0	N.E.	N.E.	N.E.

N.E. = Not established

TWA= time weighted average

STEL= short term exposure level

## 8.2 Exposure Controls:

**Engineering Controls:** Use only with production equipment (stencil printers and re-flow furnaces) with adequate exhaust ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components with established exposure limits so they are not exceeded. Use exhaust ventilation when heating product. Air emission control equipment may be necessary based on the local governmental requirements for contaminants entering the atmosphere. Emissions may contain metal fume, rosin and organic compounds.

### Personal protection:

**Eyes:** Chemical safety glasses/goggles. Face shield for splash hazards.

**Respiratory:** An approved or EU compliant CE marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.

**Skin:** Compatible chemical resistant gloves. Recommend a nitril disposable or other chemical glove.

**Other:** Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

**Work/Hygienic Practices:** Maintain good housekeeping. Clean up spills immediately. Do not allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area. Follow standard lead work practices, if applicable.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

<b>Appearance:</b>	Grey colored solid paste	<b>Boiling Point/Range:</b>	Not determined
<b>Odor:</b>	Mild characteristic odor.	<b>Melting Point/Freezing Point:</b>	Not applicable
<b>Odor Threshold:</b>	Not established	<b>Evaporation Rate:</b>	Not applicable
<b>Specific Gravity:</b>	Not applicable.	<b>pH:</b>	Not applicable
<b>Vapour Pressure:</b>	Not applicable.	<b>Solubility in Water:</b>	Insoluble (paste)
<b>Vapour Density:</b>	(air=1) Not applicable.	<b>Partition coefficient:</b>	Not established
<b>Relative Density:</b>	Not established	<b>Flammability:</b>	Not applicable
<b>Flash Point:</b>	Not applicable	<b>Method:</b>	Not applicable
<b>Auto-ignition Temperature:</b>	Not applicable	<b>Flammable Limits:</b>	Limits not established
<b>UEL/LEL Limits:</b>	Not applicable	<b>Decomposition Temp:</b>	Not applicable
<b>Viscosity:</b>	Not established	<b>Explosive properties:</b>	Not applicable
<b>Oxidizing Properties:</b>	Not established		

**Other Information:** Above data for the whole mixture.

## 10. STABILITY AND REACTIVITY

**10.1 Reactivity:** Stable.

**10.2 Chemical Stability:** Stable

**10.3 Possibility of Hazardous Reactions:** Not established

**10.4 Conditions To Avoid:** None known

**10.5 Incompatible Materials:** Avoid contact with acids, bases or oxidizing agents.

**10.6 Hazardous Decomposition/Combustion:**  
Harmful organic fumes and toxic oxide fumes may form at elevated temperatures. Metal oxide fumes.

**10.7 Hazardous Polymerization:** Will not occur.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

**Acute toxicity:** Not established

**Irritation:** Not established

**Corrosivity:** Not applicable

**Sensitization:** Not available

**Repeated dose toxicity:** Not established

**Carcinogenicity:** Not established

**Likely Routes of Entry:** eyes (damage) /skin (irritation or sensitization) /inhalation (irritation/sensitization) ingestion (may be harmful)

**Interactive effects:** None known

**Mutagenicity:** Not established

**Toxicity for Reproduction:** Not Established

**Absence of specific data:** None available (not tested)

### 11.2 Symptoms related to the physical, chemical and toxicological characteristics:

May cause irritation or sensitization by skin and inhalation. Causes serious eye damage.

### 11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Exposure to rosin fume has been known to cause occupational asthma. Exposure to lead fume, if applicable, may cause harm by inhalation and ingestion. Chronic exposures to lead fume, if applicable, can cause potential harm to the developing fetus. Lead exposure can be toxic.

**Mixture verses substance information:** None known

### Other Information:

**Carcinogenicity:** **NTP:** No (National Toxicity Program)

**Listing** **OSHA:** No (US Occupational Safety & Health Administration)

**IARC:** Yes - Lead and lead compounds are listed as possible carcinogens. (International Agency for Research on Cancer).

Silver – LD50 oral – rat > 5,000 mg/kg

Bismuth – LD50 oral-rat 5,000 mg/kg

Lead – Suspected human reproductive toxicant. May cause damage to organs through prolonged or repeated exposure. Reproductive toxicity – rat –inhalation, oral/ effects on newborn.

## 12. ECOLOGICAL INFORMATION

Product mixtures not tested.

**12.1 Toxicity:** No information available

**12.2 Persistence and degradability:** No information available

**12.3 Bioaccumulative potential:** No information available

**12.4 Mobility in soil:** No information available

**12.5 Results of PBT and vPvB assessments:** No data is available

**12.6 Other adverse effects:** No information is available for mixture. Avoid release to environment.

Lead – Toxicity to fish – mortality LOEC – rainbow trout – 1.19 mg/l – 96h. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Bioaccumulation – Oncorhynchus kisutch – 2 weeks  
Bioconcentration factor (BCF): 12. Fresh fish: 0.44 mg/l LC50 96h/ 1.32 mg/l LC50 96h/water Flea: 600 ug/l EC50 = 48h

Contains substances that are harmful to aquatic life.

## 13. DISPOSAL CONSIDERATION

**13.1 Waste treatment method:** Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with environmental regulations. Containerize material and classify according to applicable regulations. No pre-treatment on site is recommended. Do not dispose of down any drain or waterway. Utilize the same personal protective equipment as the user when handling for disposal.

**RoHS (Restriction of Hazardous Substances):** some of the product mixtures are RoHS compliant because they are lead free. Product mixtures do not contain any PBB or PBDT brominated compounds.

RoHS – Note that some of the product mixtures do contain lead and are therefore not compliant with RoHS. Users should review their particular use for any applicable exemptions that may apply. Review alloy table for products.

## 14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements.

Solder Paste is non - hazardous.

Not regulated/non - hazardous under US DOT (United States Department of Transportation).

Not regulated/non - hazardous under international shipping requirements.

**14.1 UN number:** None

**14.2 UN proper shipping name:** None

**14.3 Transport hazard class(s):** None

**14.4 Packing group:** None

**14.5 Environmental hazards:** None

**14.6 Special precautions for user:** None

**14.7 Transport in bulk:** Not applicable

## 15. REGULATORY INFORMATION

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

All ingredients are listed on the USEPA TSCA Inventory.

All ingredients are listed on EINECS. Note Rosin was recently listed under the No Longer Polymer List, Notification of New Chemical Substances in Accordance with Directive 67/548/EEC.

Safety data sheet was developed using EC 1907/2006 amended as of 20 May 2010 EU No 453/2010, 2015/830 and information as stated under regulation EC No 1272/2008 CLP Regulation.

GHS = Global Harmonized System

CLP= Classification, labeling and packaging

Product does not contain any substances ozone depleting substances and therefore not subject to EC 2037/2000.

**15.2 Chemical safety assessment:** None performed for mixture.

## 16. OTHER INFORMATION

**NOTE:** The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

**Revised Date:** 22 NOVEMBER 2019

**Prepared by:** Nancy Swarts, The Indium Corporation of America, nswarts@indium.com

**Approved by:** Nancy Swarts, The Indium Corporation of America

Changes provided on this SDS were based on the requirements of EU No. 453/2010 of May 20, 2010 regarding amendments to EC No. 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

**ALLOY TABLE**

<b>Indalloy MetalAlloyMix</b>	<b>%Sn Tin</b>	<b>%Pb Lead</b>	<b>%Ag Silver</b>	<b>%In Indium</b>	<b>%Bi Bismuth</b>	<b>%Sb Antimony</b>	<b>%Cu Copper</b>	<b>%Zn Zinc</b>	<b>%Au Gold</b>	<b>%Ge Germanium</b>	<b>RoHS 2/3 Compliance</b>
<b>9 (Sn70/Pb18/In12)</b>	58.1-64.4	14.9-16.6	-	10-11	-	-	-	-	-	-	NO
<b>10 (Pb75/In25)</b>	-	63.3-69	-	20.8-23	-	-	-	-	-	-	NO
<b>42 Bi46/Sn34/Pb20)</b>	28-31.3	17-18.4	-	-	38-42.3	-	-	-	-	-	NO
<b>97 Sn43/Pb43/Bi14)</b>	35.7-39.6	35.7-39.6	-	-	11.6-12.9	-	-	-	-	-	NO
<b>100 (Sn62.6/Pb37/ Ag0.4)</b>	52.0-57.6	30.7-34.0	.33-.37	-	-	-	-	-	-	-	NO
<b>104 (Sn62/Pb36/Ag2)</b>	51.9-57.5	29.9-33.2	1.2-1.8	-	-	-	-	-	-	-	NO
<b>106 (Sn63/Pb37)</b>	52.3-58	30.7-34	-	-	-	-	-	-	-	-	NO
<b>109 (Sn60/Pb40)</b>	49.8-55.2	33.2-36.8	-	-	-	-	-	-	-	-	NO
<b>111 (Pb55.5/Sn40.5/ Bi4)</b>	33.6-37.3	46-51	-	-	3.3-3.7	-	-	-	-	-	NO
<b>116 (Sn50/Pb50)</b>	41.5-46	41.5-46	-	-	-	-	-	-	-	-	NO
<b>118 (Sn90/Pb10)</b>	74.7-82.8	8.3-9.2	-	-	-	-	-	-	-	-	NO
<b>121 Sn96.5/Ag3.5)</b>	80.1-88.8	-	2.9-3.2	-	-	-	-	-	-	-	YES
<b>122 (Sn95/Pb5)</b>	78.9-87.4	4.2-4.6	-	-	-	-	-	-	-	-	NO
<b>127 Pb60/Sn37/Ag3)</b>	30.7-34	49.8-55.2	2.5-2.8	-	-	-	-	-	-	-	NO
<b>128 (Sn100)</b>	83-92	-	-	-	-	-	-	-	-	-	YES
<b>129 (Sn99/Sb1)</b>	82.2-91.1	-	-	-	-	083-0.92	-	-	-	-	YES

Indalloy Metal Alloy Mix	%Sn	%Pb	%Ag	%In	%Bi	%Sb	%Cu	%Zn	%Au	%Ge	RoHS 2/3 Compliance
<b>130</b> <b>(Pb60/Sn40)</b>	33.2-36.8	49.8-55.2	-	-	-	-	-	-	-	-	NO
<b>131</b> <b>(Sn97/Sb3)</b>	80.5-89.2	-	-	-	-	2.5-2.8	-	-	-	-	YES
<b>132</b> <b>(Sn95/Ag5)</b>	78.9-87.4	-	4.2-4.6	-	-	-	-	-	-	-	YES
<b>133</b> <b>(Sn95/Sb5)</b>	78.9-87.4	-	-	-	-	4.2-4.6	-	-	-	-	YES
<b>141</b> <b>(Pb70/Sn30)</b>	24.9-27.6	58.1-64.4	-	-	-	-	-	-	-	-	NO
<b>143</b> <b>(Pb90/Sb10)</b>	-	74.7-82.8	-	-	-	8.3-9.2	-	-	-	-	YES
<b>145</b> <b>Pb75/Sn25)</b>	20.8-23	62.3-69	-	--	-	-	-	-	-	-	NO
<b>149</b> <b>(Pb80/Sn20)</b>	16.6-18.4	66.4-73.6	-	-	-	-	-	-	-	-	NO
<b>150</b> <b>(Pb81/In19)</b>	-	67.2-74.5	-	15.8-17.5	-	-	-	-	-	-	NO
<b>151</b> <b>(Pb92.5/Sn5/ Ag2.5)</b>	4.2-4.6	76.8-85	2-2.3	-	-	-	-	-	-	-	YES
<b>152</b> <b>(Pb92/Sn5/Sb3)</b>	4.2-4.6	76.4-85.6	-	-	-	2.5-2.8	-	-	-	-	YES
<b>155</b> <b>(Pb90/Ag5/Sn5)</b>	4.2-4.6	74.7-82.8	4-4.6	-	-	-	-	-	-	-	YES
<b>159</b> <b>(Pb90/Sn10)</b>	8.3-9.2	74.7-82.8	-	-	-	-	-	-	-	-	YES
<b>160</b> <b>(Sn97/Cu3)</b>	80.5-89.2	-	-	-	-	-	2.5-2.8	-	-	-	YES
<b>161</b> <b>(Pb97.5/Ag2.5)</b>	-	80.9-89.7	2-2.3	-	-	-	-	-	-	-	YES
<b>163</b> <b>(Pb95.5/Ag2.5/ Sn2)</b>	1.7- 1.9	79.3-87.9	2.1-2.3	-	-	-	-	-	-	-	YES

<b>Indalloy Metal Alloy Mix</b>	%Sn	%Pb	%Ag	%In	%Bi	%Sb	%Cu	%Zn	%Au	%Ge	RoHS 2/3 Compliance
<b>164 (Pb92.5/In5/Ag2.5)</b>	-	76.8-85.1	2.1-2.3	4.2-4.6	-	-	-	-	-	-	YES
<b>165 (Pb97.5/Ag1.5/ Sn1)</b>	0.8-0.9	80.9-89.7	1.2-1.4	-	-	-	-	-	-	-	YES
<b>171 (Pb95/Sn5)</b>	4.2-4.6	78.9-87.4	-	-	-	-	-	-	-	-	YES
<b>175 (Pb95/Ag5)</b>	-	78.9-87.4	4.2-4.6	-	-	-	-	-	-	-	YES
<b>182 (Au80/Sn20)</b>	16.6-18.4	-	-	-	-	-	-	-	66.4-73.6	-	YES
<b>183 (Au88/Ge12)</b>	-	-	-	-	-	-	-	-	73-81	10-11	YES
<b>201 (Sn91/Zn9)</b>	75.5-83.7	-	-	-	-	-	-	7.5-8.3	-	-	YES
<b>206 (Pb60/In40)</b>	-	49.8-55.2	-	33.2-36.8	-	-	-	-	-	-	NO
<b>209 (Sn65/Ag25/Sb10)</b>	54-59.8	-	20.8-23	-	-	8.3-9.2	-	-	-	-	YES
<b>227 (Sn77.2/In20/ Ag2.8)</b>	64-71	-	2.3-2.6	16.6-18.4	-	-	-	-	-	-	YES
<b>228 (Pb88/Sn10/Ag2)</b>	8.3-9.2	73-81	1.7-1.8	-	-	-	-	-	-	-	YES
<b>233 (Pb85/Sb10/Sn5)</b>	4.2-4.6	70.6-78.2	-	-	-	8.3-9.2	-	-	-	-	YES
<b>236 (Pb83/Sb10/Sn5/ Ag2)</b>	4.2-4.6	68.9-76.4	1.7-1.8	-	-	8.3-9.2	-	-	-	-	NO
<b>238 (Sn90/Au10)</b>	74.7-82.8	-	-	-	-	-	-	-	8.3-9.2	-	YES

<b>Indalloy Metal Alloy Mix</b>	%Sn	%Pb	%Ag	%In	%Bi	%Sb	%Cu	%Zn	%Au	%Ge	RoHS 2/3 Compliance
<b>240 (Sn46/Pb46/Bi8)</b>	38.2-42.3	38.2-42.3	-	-	6.6-7.4	-	-	-	-	-	NO
<b>241 (Sn95.5/Ag3.8/ Cu0.7)</b>	79-87.9	-	3.2-3.5	-	-	-	0.58-0.64	-	-	-	YES
<b>244 (Sn99.3/Cu0.7)</b>	82.4-91.4	-	-	-	-	-	0.58-0.64	-	-	-	YES
<b>249 (Sn91.8/Bi4.8/ Ag3.4)</b>	76.2-84.5	-	2.8-3.1	-	4-4.4	-	-	-	-	-	YES
<b>255 (Bi55.5/Pb44.5)</b>	-	36.9-40.9	-	-	46-51	-	-	-	-	-	NO
<b>256 (96.5Sn/3Ag/ 0.5Cu)</b>	80-88.8	-	2.5-2.8	-	-	-	0.42-0.46	-	-	-	YES
<b>259 (Sn90/Sb10)</b>	74.7-82.8	-	-	-	-	8.3-9.2	-	-	-	-	YES
<b>264 (91.5Sn/8.5Sb)</b>	75.9-84.2	-	-	-	-	7.06-7.8	-	-	-	-	YES
<b>266 (93.5Pb/5Sn/1.5Ag)</b>	4.2-4.6	77.6-86	1.2-1.4	-	-	-	-	-	-	-	YES
<b>281 (Bi58/Sn42)</b>	34.9-38.6	-	-	-	48.1-53.4	-	-	-	-	-	YES
<b>281-338 (Sn60/Bi40)</b>	49.8-55.2	-	-	-	33.2-36.8	-	-	-	-	-	YES
<b>NS (Sn25/Au75)</b>	20.8-23	-	-	-	-	-	-	-	62-69	-	YES
<b>NS (Sn30/Au70)</b>	24.9-27.6	-	-	-	-	-	--	-	58-64.4	-	YES
<b>NS ( (Sn5/Pb93.5/Ag1.5)</b>	4.2-4.6	77.6-86	1.2-1.4	-	-	-	-	-	-	-	YES
<b>NS (Sn15/Pb82.5/ Ag2.55)</b>	12.5-13.8	68.5-75.9	2.1-2.3	-	-	-	-	-	-	-	NO
<b>NS (Sn20/Pb77/Ag3)</b>	16.6-18.4	63.9-70.8	2.5-2.8	-	-	-	-	-	-	-	NO



<b>Indalloy</b>	%Sn	%Pb	%Ag	%In	%Bi	%Sb	%Cu	%Zn	%Au	%Ge	RoHS 2/3 Compliance
<b>Metal Alloy Mix</b>											
<b>NS</b> <b>(Sn23/Au77)</b>	19.1-21.2	-	-	-	-	-	-	-	63.9-70.8	-	YES
<b>NS</b> <b>(Sn96/Ag4)</b>	79.7-88.3	-	3.3-3.7	-	-	-	-	-	-	-	YES
<b>NS</b> <b>(Sn3.5/Pb84.5/ Sb12)</b>	2.9-3.2	70.1-78.2	-	-	-	9.5-10.6	-	-	-	-	YES

**NS = Non Standard Alloy Mix**

RoHS 2 = Restriction of Hazardous Substances. Please review any applicable exemptions that may apply. This information is provided as information only. It is the responsibility of the customer to determine compliance with their particular specifications and restrictions. (2011/65/EU)

RoHS 3- products do not contain any listed phthalates