



SAFETY DATA SHEET

This safety data sheet represents a family grouping of all metal mixes that are blended with the same flux known as NC-SMQ 92J. A table is provided that lists all metal groupings.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier Product Name/Group: INDALLOY WITH NC-SMQ92J FLUX VEHICLE (Lead free)
SDS Number: SDS-IN 540-LF **Revised Date:** 18 DECEMBER 2020

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product Use: Industrial Use (Mixture) - Solder paste consisting of a flux vehicle blended with 83-92 weight percent pre-alloyed metal powder used for soldering applications. Review alloy table for exact product identification. Note: this SDS covers various metal mixtures using the same flux.

See alloy table for listing of products included under this SDS.

1.3 Details of the supplier of the safety data sheet

MANUFACTURER/SUPPLIER/IMPORTER:

In America:

The Indium Corporation of America®.

34 Robinson Road, Clinton NY 13323

Technical & Safety Information: (315) 853-4900

Safety & SDS Information: nswarts@indium.com

Corporation web page: <http://www.indium.com>

In Europe:

The Indium Corporation of America® (European Operations)

7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG

Information: (normal business hours) +44 [0] 1908 580400

EU Contact: aday@indium.com

In China:

Indium Corporation (Suzhou) Co., Ltd.

No. 428 Xinglong Street

Suzhou Industrial Park

Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126

Information: (86) 512-6283-4900

In Asia:

Indium Corporation of America

Asia-Pacific Operations-Singapore

29 Kian Teck Avenue

Singapore 628908

Information: +65 6268-8678

1.4 Emergency telephone number**FOR CHEMICAL EMERGENCY ONLY PHONE *:****CHEMTREC 24 hrs.****USA: 1 (800) 424-9300****Outside USA: +1 (703) 527-3887****In China: 86+ 4001-204937***** Used only for spill/leak/fire/exposure/accident****France: 33-975181407****In France emergency information (French poison center): INRS (ORFILA) +33 (0) 1 45 42 59 59****Germany: toll free- 0800-181-7059 or (Frankfurt) 49-69643508409****Italy: toll free- 800-789-767****Poland: (Warsaw) 48-223988029****Portugal: 351-308801773****Hungary: (Budapest) 36-18088425****Romania: 40-37-6300026****United Kingdom: (London) 44-870-8200418 and 44-2038073798****ALL OTHER INQUIRIES: TOLL FREE: +1-800-448-9240 Indium Corporation****SECTION 2. HAZARDS IDENTIFICATION****PRIMARY ROUTES OF ENTRY:** Eye Inhalation Skin Ingestion**Carcinogen listed in**

NTP

IARC

OSHA

 Not Listed**2.1 Classification of the substance or mixture**

Skin sensitizer-Category 1B

Respiratory sensitizer-Category 1B

2.2 Label elements

Labeling in accordance with Regulation (EC) No. 1272/2008

GHS



Signal Word: Warning

Hazard statement(s)

H317 May cause an allergic skin reaction

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 +P364 Take off contaminated clothing and wash before reuse

P301 +P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing

IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Supplemental information:

EUH208 Contains rosin. May produce an allergic reaction

2.3 Other hazards

POTENTIAL HEALTH EFFECTS:

Eye Contact: Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause eye irritation.

Ingestion: This product contains metal alloy powders and organic chemicals. May be harmful if swallowed. May cause burns to the digestive tract and systematic effects.

Inhalation: Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to the respiratory system. May be harmful if inhaled. Rosin may cause occupational asthma.

Skin Contact: May cause skin irritation or dermatitis. Rosin may cause skin sensitization.

Chronic: SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Has been shown to increase incidence of sarcoma in animal tests.

COPPER: Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

ANTIMONY: May cause dermatitis.

BISMUTH: May cause kidney damage.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixture:

Components	% wt	CAS Registry #/ EINECS#	
TIN	*	7440-31-5/231-141-8	01-2119486474-28-0077
SILVER	*	7440-22-4/231-131-3	01-2119555669-21-0093
BISMUTH	*	7440-69-9/231-177-4	01-2119560575-33--0017
ANTIMONY	*	7440-36-0/231-146-5	X
COPPER	*	7440-50-8 /231-159-6	01-2119480154-42-0208

POLYGLYCOL ETHER

4.0-14.0

9038-95-3

X

N.E. = Not established

* See Alloy Table for breakdown of percentages of alloy mixtures

<http://www.indium.com>

ALLOY TABLE

Alloy in flux mix = paste

Indalloy Alloy	%TIN Sn	%SILVER Ag	%ANTIMONY Sb	%BISMUTH Bi	%COPPER Cu	RoHS 2/3* Compliance
121 (96.5Sn/3.5Ag)	80.1-88.8	2.9-3.2	-	-	-	Yes
132 (95Sn/5Ag)	78.9-87.4	4.2-4.6	-	-	-	Yes
133 (95Sn/5Sb)	78.9-87.4	-	4.2-4.6	-	-	Yes
241 (SAC387) (95.5Sn/3.8Ag/0.7Cu)	79.3-87.9	3.2-3.5	-	-	0.6-0.7	Yes
244 (99.3Sn/0.7Cu)	82.4-91.4	-	-	-	0.58-0.64	Yes
281 (58Bi/42Sn)	34.9-38.6	-	-	48.1-53.4	-	Yes

NS= Non Standard Alloy Mix

*RoHS 2 (2011/65/EU) Restriction of Hazardous Substances

*RoHS 3- products do not contain any listed phthalates

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures:

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

4.2 Most important symptoms and effect, both acute and delayed:

Skin contact may cause irritation. Long term contact may cause dermatitis. Inhalation of decomposed rosin fume may cause irritation or occupational asthma. Exposure to metal fumes may cause irritation to the respiratory system. Long term exposure by inhalation to metal fumes may cause illness such as metal fume fever.

4.3 Indication of any immediate medical attention and special treatment needed:

No specific special treatment information is available on this mixture. Review data provided in this document to understand the hazards when working with the product. No other information is available at this time.

SECTION 5. FIRE FIGHTING MEASURES

5.1 Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions. Water, CO₂, foam media.

5.2 Special hazards arising from the substance or mixture:
May produce toxic fumes of carbon monoxide if burning or metal oxide fumes.

5.3 Advice for Firefighters Fire fighters must wear approved self-contained breathing apparatus and full protective clothing.

5.4 Further information
Material product is not flammable. No other information is available.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Keep away from the spill. Remove sources of ignition. Keep exhaust ventilation system running. In the event of a fire evacuate area.

For emergency responders:

Wear safety glasses, gloves when cleaning up any spill. Other equipment may be necessary based on the immediate area and other chemicals unrelated to the product that may be in use. Adequate ventilation should be available. Keep unnecessary personnel away from area during clean up.

6.2 Environmental Precautions: Dispose contaminated cloth rags or paper towels following all applicable governmental regulations. Material may have reclaim value. Material is non-hazardous. It however does contain metals and organic chemicals which may not be suited for release to any body of water including drains.

6.3 Methods and material for containment and cleaning up:

Spill or leak procedures: Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol.

6.4 Reference to other sections: See Section 8 for exposure levels. Section 13 for disposal.

SECTION 7. HANDLING AND STORAGE

7.1 Precautions For Safe Handling: Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed. Do not eat, drink or smoke when handling this product. Utilize exhaust ventilation when heating product. Emissions may contain metal fumes, rosin and organic compounds.

7.2 Conditions for Safe Storage, including any incompatibilities:

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product label and product data sheet for specific storage temperature requirements. Rotate stock to ensure use before expiration date.

7.3 Specific End Use(s): Soldering applications

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

			<u>TWA</u>	<u>STEL</u>
		<u>CAS#/EINECS#</u>	mg/m3	mg/m3
TIN	*	7440-31-5/231-141-8		
		(UK)	2	4
		(Belgium)	2	-
		(Germany)	2	-
		(Netherlands)	2	-
		(Spain)	2	-
		(Poland)	2	-
SILVER	*	7440-22-4/231-131-3		
		(UK)	0.1	0.3
		(Belgium)	0.1	-
		(France)	0.1	-
		(Germany)	0.1	-
		(Netherlands)	0.1	-
		(Spain)	0.1	-
	(Poland)	0.05	-	
BISMUTH	*	7440-69-9/231-177-4		
		(UK)	N.E.	N.E.
ANTIMONY	*	7440-36-0/231-146-5		
		(UK)	0.5	-
		(France)	0.5	-
		(Belgium)	0.5	-
		(Spain)	0.5	-
		(Portugal)	0.5	-

(The Netherlands)	0.5	-
(Finland)	0.5	-
(Denmark)	0.5	-
(Austria)	0.5	5
(Switzerland)	0.5	-
(Poland)	0.5	-
(Norway)	0.5	-
(Ireland)	0.5	-

COPPER

* 7440-50-8 /231-159-6

(UK)	0.2 (fume)	0.6(fume)
(France)	2	0.2(fume)
(Belgium)	1	-
	0.2(fume)	
(Spain)	1	-
	0.2(fume)	
(Portugal)	1	0.2(fume)
(Netherlands)	0.1	-
(Finland)	1	-
	0.1	
(Denmark)	1	-
	0.1	
(Austria)	1	4
	0.1(fume)	0.4
(Switzerland)	0.1	0.2
(Norway)	1	0.1
(Ireland)	1	2
	0.2 (fume)	
(Poland)	0.2	-

ROSIN

3.0-4.0 65997-05-9

(EU)	0.05	N.E.	0.15 (sensitiser)
------	------	------	-------------------

POLYGLYCOL ETHER

4.0-14.0 9038-95-3 N.E. N.E. N.E.

N.E. = Not established

STEL = short term exposure limits TWA = 8hr. worker time weighted average

8.2 Exposure Controls

Engineering Controls: Use only with production equipment (such as stencil printers and re-flow furnaces) with adequate exhaust ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components with established exposure limits so they are not exceeded. Use exhaust ventilation when heating product. Air emission control equipment may be necessary based on the local governmental requirements for contaminants entering the atmosphere. Emissions may contain metal fume, rosin and organic compounds.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respiratory: An approved or EU compliant CE marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.

Skin: Compatible chemical resistant gloves. Recommend a nitrile disposable or other chemical glove.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Practices: Maintain good housekeeping. Clean up spills immediately. Do not allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:	Grey colored solid paste	Boiling Point/Range:	Not determined
Odor:	Mild characteristic odor.	Melting Point/Freezing Point:	Not applicable
Odor Threshold:	Not established	Evaporation Rate:	Not applicable
Specific Gravity:	Not applicable.	pH:	Not applicable
Vapour Pressure:	Not applicable.	Solubility in Water:	Insoluble (paste)
Vapour Density:	(air=1) Not applicable.	Partition coefficient:	Not established
Relative Density:	Not established	Flammability:	Not applicable
Flash Point:	Not applicable	Method:	Not applicable
Auto-ignition Temperature:	Not applicable	Flammable Limits:	Limits not established
UEL/LEL Limits:	Not applicable	Decomposition Temp:	Not applicable
Viscosity:	Not established	Explosive properties:	Not applicable
Oxidizing Properties:	Not established		

9.2 Other Information: Above data for the whole mixture.

SECTION 10. STABILITY AND REACTIVITY

- 10.1 Reactivity:** Stable.
- 10.2 Chemical Stability:** Stable
- 10.3 Possibility of Hazardous Reactions:** Not established
- 10.4 Conditions To Avoid:** None known
- 10.5 Incompatible Materials:** Avoid contact with acids, bases or oxidizing agents.
- 10.6 Hazardous Decomposition / Combustion:** Harmful organic fumes and toxic oxide fumes may form at elevated temperatures, metal oxide fumes.
- Hazardous Polymerization:** Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

<u>Acute toxicity:</u>	Not established	<u>Mutagenicity:</u>	Not established
<u>Irritation:</u>	Not established	<u>Toxicity for Reproduction:</u>	Not Established
<u>Corrosivity:</u>	Not applicable	<u>Absence of specific data:</u>	None available (not tested)
<u>Sensitization:</u>	contains rosin		
<u>Repeated dose toxicity:</u>	Not established		
<u>Carcinogenicity:</u>	Not established		
<u>Likely Routes of Entry:</u>	eyes (irritation) /skin (irritation or sensitization) /inhalation (irritation/sensitization) ingestion (may be harmful)		
<u>Interactive effects:</u>	None known		

Symptoms related to the physical, chemical and toxicological characteristics:

May cause irritation or sensitization by skin and inhalation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Exposure to rosin fume has been known to cause occupational asthma.

Mixture verses substance information: None known

11.2 Other Information:

<u>Carcinogenicity:</u>	NTP: No (National Toxicity Program)
<u>Listing</u>	OSHA: No (US Occupational Safety & Health Administration)
	IARC: No (International Agency for Research on Cancer).

Copper - LD50 – intraperitoneal mouse 3.5 mg/kg.

Silver – LD50 oral – rat > 5,000 mg/kg

Bismuth – LD50 oral-rat 5,000 mg/kg

Antimony - LD50 oral – rat 7,000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Product mixtures not tested.

12.1 Toxicity: No information available

12.2 Persistence and degradability: No information available

12.3 Bioaccumulative potential: No information available

12.4 Mobility in soil: No information available

12.5 Results of PBT and vPvB assessments: No data is available

12.6 Endocrine disrupting properties: No information available-none

12.7 Other adverse effects: No information is available for mixture. Avoid release to environment.

Copper – Toxicity to daphnia and other aquatic invertebrates mortality NOEC – Daphnia 0.004 mg/l – 24h.

Antimony – Toxicity to fish – mortality NOEC (sheepshead minnow) 6.2 mg/l – 96h. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

SECTION 13. DISPOSAL CONSIDERATION

13.1 Waste treatment method: Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with environmental regulations. Containerize material and classify according to applicable regulations. No pre-treatment on site is recommended. Do not dispose of down any drain or waterway. Utilize the same personal protective equipment as the user when handling for disposal. Follow waste assessment rules.

RoHS 2 (Restriction of Hazardous Substances) (2011/65/EU): Product mixtures do not contain any PBB or PBBD brominated compounds. RoHS – Users should review their particular use for any applicable exemptions that may apply. Review alloy table for products.

14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements.

Solder Paste is non- hazardous.

Not regulated/non- hazardous under US DOT (United States Department of Transportation).

Not regulated/non- hazardous under international shipping requirements (IATA/IMDG).

14.1 UN number or ID number: None

14.2 UN proper shipping name: None

14.3 Transport hazard class(s): None

14.4 Packing group: None

14.5 Environmental hazards: None

14.6 Special precautions for user: None

14.7 Maritime transport in bulk according to IMO instruments: Not applicable

SECTION 15. REGULATORY INFORMATION

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

All ingredients are listed on the USEPA TSCA Inventory.

All ingredients are listed on EINECS. Note Rosin was recently listed under the No Longer Polymer List.

Safety data sheet was developed using guidance from EC 1907/2006 amended as of Feb 2020 EU No 453/2010, 2015/830 changes under 2020/878 June 2020 and information as stated under regulation EC No 1272/2008 CLP Regulation.

GHS = Global Harmonized System

CLP= Classification, labeling and packaging

Product does not contain any substances ozone depleting substances and therefore not subject to EC 1005/2009.

15.2 Chemical safety assessment: None performed for mixture.

SECTION 16. OTHER INFORMATION

NOTE: **The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.**

Revised Date: 18 DECEMBER 2020
Prepared by: Nancy Swarts, The Indium Corporation of America, nswarts@indium.com
Approved by: Nancy Swarts, The Indium Corporation of America

Changes provided on this SDS were based on the requirements of EU No. 453/2010 of Feb 2020 and 2020/878 June 2020 regarding amendments to EC No. 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.