

PRODUCT DATA SHEET

Flux Coatings for Solder Preforms


Introduction

Preforms are precise shapes of solder that are manufactured to tight tolerances to give repeatable, accurate solder amounts that are efficiently introduced into the manufacturing process.

Adding the flux directly onto the solder allows for an exact, correct amount of flux to properly complete the soldering process. It also puts the flux between the solder and the substrate, where it is the most effective.

Flux coatings for preforms are available in no-clean and solvent cleanable chemistries, with a variety of activity levels to suit your substrate metallizations.

Indium Corporation's unique coating process can control the amount of flux to tight tolerances. **Flux coatings** are measured and applied by weight percentage. The standard weight percentage ranges from 1–3% ± 0.5%. The **flux coating** is applied after the dimensions of the preform have been verified.



Features

- Eliminates the need for a separate fluxing step
- Eliminates excessive flux residue
- Delivers flux precisely where it is needed
- Provides a uniform amount of flux every time

Additional Information

Please visit www.indium.com/technical-documents/ for more information on solder preforms and **flux coatings**, or visit our blogs at www.indium.com/blog

Product Data Sheets

- LV2K Flux Coating
- No-Clean Fluxes for Coating Solder Preforms
- Solder Preforms

Application Notes

- Fluxless Soldering
- Flux and Solder Compatibility
- Storage and Handling of Flux-Coated Preforms in Tape & Reel

Technical Support

Indium Corporation's internationally experienced engineers provide in-depth technical assistance to our customers. Thoroughly knowledgeable in all facets of Materials Science as it applies to the electronics and semiconductor sectors, Technical Support Engineers provide expert advice in solder properties, alloy compatibility and selection of solder preforms, wire, ribbon, and paste. Indium Corporation's Technical Support engineers provide rapid response to all technical inquiries.

Flux Coating	IPC Classification	Substrate Finishes	J-STD-004B SIR & ECM
LV2K	ROL0	Au, Ag, Pd, Pt, Cu, HASL, ENIG, Sn	Pass
NC-7	ROL0	Au, Ag, Pd, Pt, Cu, HASL, ENIG, Sn	Pass
RA-2	ROL1	Au, Ag, Pd, Pt, Cu, HASL, ENIG, Sn	Pass
NC-299	ROL1	Au, Ag, Pd, Pt, Cu, Ni, HASL, ENIG, Sn	Pass
LV299	ROL1	Au, Ag, Pd, Pt, Cu, Ni, HASL, ENIG, Sn	Pass
RSA	ROM1	Cu, Ni, Cu Alloys (Brass, Bronze)	Cleaning recommended
RA-42	ROH1	Cu, Ni, Cu Alloys (Brass, Bronze), Alloy 42	Cleaning recommended

*See *Flux and Solder Compatibility* application note for details on fluxes and their recommended solder alloys.

Safety Data Sheets

Please refer to the SDS document within the product shipment, or contact our local team to receive a copy.

This product data sheet is provided for general information only. It is not intended, and shall not be construed, to warrant or guarantee the performance of the products described which are sold subject exclusively to written warranties and limitations thereon included in product packaging and invoices. All Indium Corporation's products and solutions are designed to be commercially available unless specifically stated otherwise.

All of Indium Corporation's solder paste and preform manufacturing facilities are IATF 16949:2016 certified. Indium Corporation is an ISO 9001:2015 registered company.

From One Engineer To Another®

Contact our engineers: askus@indium.com

Learn more: www.indium.com

Form No. 97824 R11

ASIA +65 6268 8678 • CHINA +86 (0) 512 628 34900 • EUROPE +44 (0) 1908 580400 • USA +1 315 853 4900



©2022 Indium Corporation